



PSD2-TPP Technical Design

Version: 1.7.1 (rev)

February 2020

Authorisations and version control

Version	Date	Affects	Brief description of the change
1.6.0	February 2019	EVERYTHING	Initial Version
1.7.0	June 2019	3. DESCRIPTION OF CORE SERVICES	New API 3.4 FCS support: Establish consent for the fund confirmation service
1.7.1	February 2020	3.3 AIS: Account data reading service	Added new field ownerName to return the PSU name in account detail service

CONTENTS

1. INTRODUCTION	1
1.1 SCOPE	1
1.2 CONTEXT	1
1.3 GLOSSARY	1
2. GENERAL DESCRIPTION OF THE SYSTEM	3
3. DESCRIPTION OF CORE SERVICES	5
3.1 PIS: PAYMENT INITIATION SERVICE	5
3.1.1 PAYMENT INITIATION	5
3.1.1.1 Request	5
3.1.1.2 Response	10
3.1.1.3 Examples	14
3.1.2 PAYMENT INITIATION FOR FUTURE DATED PAYMENTS	17
3.1.2.1 Request	18
3.1.2.2 Response	23
3.1.2.3 Examples	27
3.1.3 PAYMENT INITIATION FOR BULK PAYMENTS	28
3.1.3.1 Request	28
3.1.3.2 Response	34
3.1.3.3 Examples	38
3.1.4 INITIATION FOR STANDING ORDERS FOR RECURRING/PERIODIC PAYMENTS	42
3.1.4.1 Request	43
3.1.4.2 Response	50
3.1.4.3 Examples	53
3.1.5 GET PAYMENT STATUS	54
3.1.5.1 Request	54
3.1.5.2 Response	58
3.1.5.3 Examples	59
3.1.6 GET PAYMENT INITIATION	60
3.1.6.1 Request	60
3.1.6.2 Response	64
3.1.6.3 Examples	65
3.1.7 PAYMENT CANCELLATION	66
3.1.7.1 Request	66
3.1.7.2 Response	70
3.1.7.3 Examples	72
3.1.8 MULTILEVEL SCA FOR PAYMENTS	73
3.2 AIS: ESTABLISH ACCOUNT INFORMATION CONSENT SERVICE	73
3.2.1 CHARACTERISTICS OF THE CONSENT	73
3.2.1.1 Consent model	73

PSD2 - TPP Technical Design

3.2.1.2	Recurring access	75
3.2.1.3	Account owner name delivery	75
3.2.2	ACCOUNT INFORMATION CONSENT	75
3.2.2.1	Request	76
3.2.2.2	Response	82
3.2.2.3	Examples	85
3.2.3	GET CONSENT STATUS	89
3.2.3.1	Request	89
3.2.3.2	Response	92
3.2.3.3	Examples	93
3.2.4	GET CONSENT	94
3.2.4.1	Request	94
3.2.4.2	Response	97
3.2.4.3	Examples	99
3.2.5	REMOVE CONSENT	101
3.2.5.1	Request	101
3.2.5.2	Response	104
3.2.5.3	Examples	105
3.2.6	MULTILEVEL SCA TO ESTABLISH CONSENT	105
3.3	AIS: ACCOUNT DATA READING SERVICE	106
3.3.1	ACCOUNT LIST READING	106
3.3.1.1	Request	107
3.3.1.2	Response	110
3.3.1.3	Examples	111
3.3.2	READING ACCOUNT DETAILS	113
3.3.2.1	Request	114
3.3.2.2	Response	117
3.3.2.3	Examples	118
3.3.3	READING BALANCES	120
3.3.3.1	Request	121
3.3.3.2	Response	124
3.3.3.3	Examples	125
3.3.4	READING OF TRANSACTIONS	126
3.3.4.1	Request	127
3.3.4.2	Response	132
3.3.4.3	Examples	133
3.4	FCS: ESTABLISH CONSENT FOR THE FUND CONFIRMATION SERVICE	137
3.4.1	FUND CONFIRMATION CONSENT	137
3.4.1.1	Request	137
3.4.1.2	Response	143
3.4.1.3	Examples	146
3.4.2	GET CONSENT STATUS	148
3.4.2.1	Request	148
3.4.2.2	Response	152
3.4.2.3	Examples	152

PSD2 - TPP Technical Design

3.4.3	GET CONSENT	153
3.4.3.1	Request	153
3.4.3.2	Response	157
3.4.3.3	Examples	158
3.4.4	REVOKE CONSENT	159
3.4.4.1	Request	159
3.4.4.2	Response	163
3.4.4.3	Examples	163
3.4.5	MULTILEVEL SCA TO ESTABLISH CONSENT	164
3.5	FCS: FUND CONFIRMATION SERVICE	164
3.5.1	CONFIRMATION OF FUNDS	164
3.5.1.1	Request	165
3.5.1.2	Response	167
3.5.1.3	Examples	168
3.6	OAuth2 AS PRE-STEP	169
3.6.1	OBTAIN AUTHORISATION	169
3.6.1.1	Request	169
3.6.1.2	Response OK	171
3.6.1.3	Error response	172
3.6.1.4	Examples	173
3.6.2	OBTAIN ACCESS TOKEN	173
3.6.2.1	Request	173
3.6.2.2	Response OK	175
3.6.2.3	Error response	176
3.6.2.4	Examples	176
3.7	TOKEN RENEWAL REQUEST	177
3.7.1	REQUEST	177
3.7.2	RESPONSE	178
3.7.3	EXAMPLES	179
3.8	SESSIONS: COMBINATION OF AIS AND PIS SERVICES	179
3.9	PROCESSES COMMON TO THE SERVICES.	180
3.9.1	INITIATION OF THE AUTHORISATION PROCESS (EXPLICIT)	180
3.9.1.1	Request	180
3.9.1.2	Response	184
3.9.1.3	Examples	186
3.9.2	UPDATE DATA OF THE PSU (SELECT SCA METHOD)	187
3.9.2.1	Request	187
3.9.2.2	Response	191
3.9.2.3	Examples	193
3.9.3	GET AUTHORISATION SUB-RESOURCES	194
3.9.3.1	Request	194
3.9.3.2	Response	198
3.9.3.3	Examples	198
3.9.4	GET SCA STATUS	199
3.9.4.1	Request	199

PSD2 - TPP Technical Design

3.9.4.2	Response	203
3.9.4.3	Examples	204
4.	DESCRIPTION OF VALUE-ADDED SERVICES	205
4.1	AVAILABLE ASPSPs SERVICE	205
4.1.1	VERSION 1	205
4.1.1.1	Request	205
4.1.1.2	Response	206
4.1.1.3	Examples	206
4.1.2	VERSION 2	207
4.1.2.1	Request	207
4.1.2.2	Response	208
4.1.2.3	Examples	209
4.2	SVA: PAYMENT INITIATION WITH LIST OF AVAILABLE ACCOUNTS FOR PISP	210
4.2.1	PAYMENT INITIATION	210
4.2.1.1	Request	210
4.2.1.2	Response	216
4.2.1.3	Examples	219
5.	DEFINITION OF TYPES OF COMPOSITE DATA	221
5.1	ACCOUNTACCESS	221
5.2	ACCOUNTDETAILS	222
5.3	ACCOUNTREFERENCE	225
5.4	ACCOUNTREPORT	225
5.5	ADDRESS	226
5.6	AMOUNT	226
5.7	AUTHENTICATIONOBJECT	227
5.8	ASPSP	228
5.9	BALANCE	228
5.10	EXCHANGERATE	229
5.11	HREF	229
5.12	LINKS	230
5.13	PAYMENTEXCHANGERATE	231
5.14	REPORTEXCHANGERATE	232
5.15	SINGLEPAYMENT	233
5.16	TPPMESSAGE	234
5.17	TRANSACTIONS	235
6.	ANNEXES	238
6.1	SIGNATURE	238
6.1.1	"DIGEST" HEADER MANDATORY	238
6.1.2	SIGNATURE REQUIREMENTS	238
6.1.3	EXAMPLE	239
6.1.3.1	Generation of the "Digest" header	240

PSD2 - TPP Technical Design

6.1.3.2	Generation of the "Signature" header	241
6.1.3.3	Generation of the "TPP-Signature-Certificate" header	242
6.1.3.4	Definitive headers to send	242
6.2	HTTP RESPONSE CODES	242
6.3	RETURN CODES	244
6.4	TRANSACTION STATUS	250
6.5	CONSENT STATUS	251
6.6	TYPES OF AUTHENTICATION	252
6.7	BALANCE TYPE	252
6.8	CHARGE BEARER	253
6.9	GOOD PRACTICE GUIDE	254
6.9.1	REMITTANCEINFORMATIONUNSTRUCTURED FIELD	254
6.9.2	LIFE OF THE SCAREDIRECT LINK	254

1. INTRODUCTION

1.1 Scope

This document describes the technical design of the interface between third-party (payment service) providers (TPPs) and the HUB to ensure compliance with the PSD2 Directive.

1.2 Context

It is the final joint document between Redsys and the financial institutions associated with the HUB.

1.3 Glossary

The table below lists the acronyms/abbreviations and their definitions used in the document.

Acronym	Definition
ASPSP	Account Servicing Payment Services Provider
	Provides and maintains customer accounts from which payments can be made.
PISP	Payment Initiation Services Provider
	Initiates a payment order at the request of the user, from a payment account held at another payment services provider
AISP	Account Information Service Provider
	Provides account information services to customers for payment accounts held with other providers.
TPP	Third Party Provider
	Executes the services defined by PSD2 on behalf of a PSU. If it is necessary for the service, it accesses the account(s) of the PSU administered by an ASPSP using the XS2A interface of this ASPSP. It sends request messages to the XS2A interface of the ASPSP

PSD2 - TPP Technical Design

	and receives response messages corresponding to this ASPSP.
PIISP	Payment Issuer Instrument Services Provider
	Provides users with a payment instrument with which to initiate and process payment transactions.
PSU	Payment Services User
	May be a natural or legal person under PSD2 legislation. Implicitly or explicitly instructs the TPP to perform any PSD2 service for its ASPSP.

2. GENERAL DESCRIPTION OF THE SYSTEM

The following table lists the services available:

Service	Functionality	Status	
CORE	PIS	Initiate simple single signature payment	Available
		Initiate recurring payments	Available
		Initiate recurring multiple/bulk payments	Available
		Initiate future payments	Available
		Check payment status	Available
		Recover payment initiation information	Available
		Cancel payment	Available
	AIS	Establish consent	Available
		Recover consent information	Available
		Check consent status	Available
		Remove consent	Available
		Read list of accounts available with/without balances	Available
		Read list of accounts accessible with/without balances	Available
		Read account details with/without balances	Available
		Read balances	Available
		Read transactions with/without balances	Available
		Read transaction details	Not supported
	FCS	Establish consent	Available
		Recover consent information	Available
		Check consent status	Available
		Remove consent	Available
		Fund confirmation	Available
	SCA	SCA by redirected flow	Available
		SCA by decoupled flow	Available
		Embedded SCA	Not supported
	Common processes	Initiate explicit authorisation	Available
		SCA status query	Available
		Obtain authorisation sub-resources	Available
		Update authorisation data	Available

PSD2 - TPP Technical Design

	OAUTH	Obtain access token	Available
		Renew access token	Available

Table 1: CORE services

Service		Functionality	Status
SVA	ASPSP DIR.	List of available ASPSPs (v1 and v2)	Available
	PIS	Payment initiation with list of accounts available for PISP	Available
	AIS	Alert of data available in PUSH mode	Pending

Table 2: Value-added services

3. DESCRIPTION OF CORE SERVICES

3.1 PIS: Payment initiation service

3.1.1 Payment initiation

Message sent by the TPP to the ASPSP through Hub to initiate payment.

3.1.1.1 Request

Endpoint

POST {provider}/{aspsp}/v1/payments/{payment-product}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none"> • sepa-credit-transfers • instant-sepa-credit-transfers • target-2-payments • cross-border-credit-transfers 	String	MAN	E.g. {provider}/{aspsp}/v1/payments/sepa-credit-transfers/

Query parameters

No additional parameters are specified for this request.

Header

Field	Description	Type	Man.	Format
Content-Type	Value: application/json	String	MAN	Content-Type: application/json
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
Consent-ID	This data element may be contained, if the payment initiation transaction is part of a session, i.e. combined AIS/PIS service. This then contains the "consentId" of the related AIS consent, which was performed prior to this payment initiation.	String	OPT	^{1,36}\$ E.g. Consent-ID: 7890-asdf-4321
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	MAN	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5

PSD2 - TPP Technical Design

PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^.{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: POST
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by	String	OPT	UUID ^[0-9a-fA-F]{8}-

PSD2 - TPP Technical Design

	<p>the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>			<p>[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$</p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	OPT	<p>RFC 2426</p> <p>^GEO:[\\d]*.[\\d]*[;][\\d]*.[\\d]*\$</p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
TPP-Redirect-Preferred	<p>If it equals "true", the TPP prefers a redirect over an embedded SCA approach.</p> <p>If it equals "false", the TPP prefers not to be redirected for SCA. The ASPSP will then choose between the Embedded or the Decoupled SCA approach, depending on the choice of the SCA procedure by the TPP/PSU.</p> <p>If the parameter is not used, the ASPSP will choose the SCA approach to be applied depending on the SCA method chosen by the TPP/PSU.</p> <p>EMBEDDED NOT SUPPORTED IN THIS VERSION</p>	Boolean	OPT	<p>E.g. TPP-Redirect-Preferred: true</p>
TPP-Redirect-URI	<p>URI of the TPP, where the transaction flow shall be redirected to</p>	String	COND	<p>^.{1,250}\$</p> <p>E.g. TPP-Redirect-URI:"https://tpp.e</p>

PSD2 - TPP Technical Design

	<p>after a Redirect. Mandated for the Redirect SCA Approach, specifically when TPP-Redirect-Preferred equals "true".</p> <p>It is recommended to always use this header field.</p> <p>Remark for Future: This field might be changed to mandatory in the next version of the specification.</p>			xample.es/cb"
TPP-Nok-Redirect-URI	<p>If this URI is contained, the TPP is asking to redirect the transaction flow to this address instead of the TPP-Redirect-URI in case of a negative result of the redirect SCA method. This might be ignored by the ASPSP.</p>	String	OPT	<p>^.{1,250}\$ E.g. TPP-Nok-Redirect-URI:"https://tpp.example.es/cb/nok"</p>
TPP-Explicit-Authorisation-Preferred	<p>If it equals "true", the TPP prefers to start the authorisation process separately. This preference might be ignored by the ASPSP, if a signing basket is not supported as functionality.</p> <p>If it equals "false" or if the parameter is not used, there is no preference of the TPP. This especially indicates that the TPP assumes a direct authorisation of the transaction in the next step.</p> <p>Note: the ASPSP may not take it into account if it does not support it.</p>	Boolean	OPT	E.g. TPP-Explicit-Authorisation-Preferred: false

PSD2 - TPP Technical Design

Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgzCCBmugAwIBAgIIZzZvBQlt0UcwDQYJ.....KoZiHvcNAQELBQA wSTELMAkGA1UEBhMCVVMxEzARBgNVBA

Body

The content of the Body is that defined in 5.15 SinglePayment.

3.1.1.2 Response

Header

Field	Description	Type	Man.	Format
Location	Location of the created resource (if created)	String	MAN	^.{1,512}\$ E.g. Location: /v1/payments/{payment-product}/{payment-id}
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

PSD2 - TPP Technical Design

				E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2- 946e-d75958b172e7
ASPSP-SCA-Approach	This data element must be contained, if the SCA Approach is already fixed. Possible values are: <ul style="list-style-type: none"> EMBEDDED DECOUPLED REDIRECT <p>The OAuth SCA approach will be subsumed by REDIRECT.</p>	String	COND	E.g. ASPSP-SCA-Approach: REDIRECT

Body

Field	Description	Type	Man.	Format
transactionStatus	Status of the transaction. Values defined in annexes in 6.4 Transaction status	String	MAN	ISO 20022 E.g. "transactionStatus": "RCVD"
paymentId	Resource identification of the generated payment initiation resource.	String	MAN	^.{1,36}\$ E.g. "paymentId": "1b3ab8e8-0fd5-43d2-946e-d75958b172e7"
transactionFees	Can be used by the ASPSP to transport transaction fees relevant for the underlying payments.	Amount	OPT	E.g. "transactionFees": {...}
transactionFeeIndicator	If equals true, the transaction will involve specific transaction cost as shown by the ASPSP in their public price list or as agreed between ASPSP and	Boolean	OPT	E.g. "transactionFeeIndicator": true

PSD2 - TPP Technical Design

	<p>PSU.</p> <p>If equals false, the transaction will not involve additional specific transaction costs to the PSU.</p>			
scaMethods	<p>This data element might be contained, if SCA is required and if the PSU has a choice between different authentication methods.</p> <p>If this data element is contained, then there is also a hyperlink of type "startAuthorisationWithAuthenticationMethodSelection" contained in the response body.</p> <p>These methods shall be presented towards the PSU for selection by the TPP.</p> <p>Note: Only if ASPSP supports selection of the SCA method</p>	List<AuthenticationObject>	COND	E.g. "scaMethods": [...]
_links	<p>A list of hyperlinks to be recognised by the TPP.</p> <p>Type of links admitted in this response:</p> <ul style="list-style-type: none"> • scaRedirect: In case of an SCA Redirect Approach, the ASPSP is transmitting the link to which to redirect the PSU browser. • startAuthorisation: In case, where an explicit start of the 	Links	MAN	E.g. "_links": {...}

PSD2 - TPP Technical Design

	<p>transaction authorisation is needed, but no more data needs to be updated (no authentication method to be selected, no PSU identification nor PSU authentication data to be uploaded).</p> <ul style="list-style-type: none">• startAuthorisation WithAuthentication MethodSelection: The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while selecting the authentication method. This link is contained under exactly the same conditions as the data element "scaMethods"• self: link to the resource created by this request.• status: The link to retrieve the transaction status• scaStatus: The link to retrieve the scaStatus of the corresponding authorisation sub-resource. This link is only contained, if an authorisation			
--	--	--	--	--

PSD2 - TPP Technical Design

	sub-resource has been already created.			
psuMessage	Text to be displayed to the PSU	String	OPT	^.{1,512}\$ E.g. "psuMessage": "Information for the PSU"
tppMessages	Message to the TPP	List<Tpp Message >	OPT	E.g. "tppMessages": [...]

3.1.1.3 Examples

Example of request for SCA via redirection

POST <https://www.hub.com/aspsp-name/v1/payments/sepa-credit-transfers>

Content-Encoding: gzip

Content-Type: application/json

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSU-Http-Method: POST

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSU-GEO-Location: GEO:12.526347;54.649862

TPP-Redirect-Preferred: true

TPP-Redirect-URI: https://www.tpp.com/cb

TPP-Nok-Redirect-URI: https://www.tpp.com/cb/nok

Date: Sun, 26 Sep 2017 15:02:37 GMT

```
{
  "instructedAmount": {
```

PSD2 - TPP Technical Design

```
        "currency": "EUR",
        "amount": "153.50"
    },
    "debtorAccount": {
        "iban": "ES1111111111111111111111"
    },
    "creditorAccount": {
        "iban": "ES2222222222222222222222"
    },
    "creditorName": "Name123",
    "remittanceInformationUnstructured": "Additional information"
}
```

Example of response in case of a redirect with an implicitly created authorisation sub-resource

HTTP/1.1 201 Created

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

ASPSP-SCA-Approach: REDIRECT

Date: Sun, 26 Sep 2017 15:02:43 GMT

Location: </v1/payments/sepa-credit-transfers/123-qwe-456>

Content-Type: application/json

```
{
  "transactionStatus": "RCVD",
  "paymentId": "123-qwe-456",
  "_links": {
    "scaRedirect": {
      "href": "https://hub.example.es/authorize "
    },
    "self": {
      "href": "/v1/payments/sepa-credit-transfers/123-qwe-456",
      "status": {
        "href": "/v1/payments/sepa-credit-transfers/123-qwe-456/status"
      }
    },
    "scaStatus": {
```

PSD2 - TPP Technical Design

```
        "href": "/v1/payments/sepa-credit-transfers/123-qwe-456/authorisations/123auth456"
      }
    }
  }
}
```

Example of request for decoupled SCA

POST <https://hub.example.es/asp-name/v1/payments/sepa-credit-transfers>

```
Content-Encoding: gzip
Content-Type: application/json
X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA
PSU-IP-Address: 192.168.8.16
PSU-IP-Port: 443
PSU-Accept: application/json
PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0
PSU-Http-Method: POST
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
TPP-Redirect-Preferred: false
Date: Sun, 26 Sep 2017 15:02:37 GMT
{
  "instructedAmount": {
    "currency": "EUR",
    "amount": "153.50"
  },
  "debtorAccount": {
    "iban": "ES1111111111111111111111"
  },
  "creditorAccount": {
    "iban": "ES2222222222222222222222"
  },
}
```

PSD2 - TPP Technical Design

```
"creditorName": "Name123",
"remittanceInformationUnstructured": "Additional information"
}
```

Example of response in case of an decoupled SCA approach with implicitly creating an authorisation sub-resource

HTTP/1.1 201 Created

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

ASPSP-SCA-Approach: DECOUPLED

Date: Sun, 26 Sep 2017 15:02:43 GMT

Location: </v1/payments/sepa-credit-transfers/123-qwe-456>

Content-Type: application/json

```
{
  "transactionStatus": "RCVD",
  "paymentId": "123-qwe-456",
  "_links": {
    "self": {
      "href": "/v1/payments/sepa-credit-transfers/123-qwe-456"
    },
    "status": {
      "href": "/v1/payments/sepa-credit-transfers/123-qwe-456/status"
    },
    "scaStatus": {
      "href": "/v1/payments/sepa-credit-transfers/123-qwe-456/authorisations/123auth456"
    }
  },
  "psuMessage": "Please use your XXX Bank app to authorise the payment"
}
```

3.1.2 Payment initiation for future dated payments

Message sent by the TPP to the ASPSP through the Hub to initiate a future dated payment.

3.1.2.1 Request

Endpoint

POST {provider}/{aspsp}/v1/payments/{payment-product}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. hub.example.es
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none"> • sepa-credit-transfers • instant-sepa-credit-transfers • target-2-payments • cross-border-credit-transfers 	String	MAN	E.g. {provider}/{aspsp}/v1/payments/sepa-credit-transfers/

Query parameters

No additional parameters are specified for this request.

Header

Field	Description	Type	Man.	Format
Content-Type	Value: application/json	String	MAN	Content-Type: application/json
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-

PSD2 - TPP Technical Design

				43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsic MWpAA
Consent-ID	This data element may be contained, if the payment initiation transaction is part of a session, i.e. combined AIS/PIS service. This then contains the "consentId" of the related AIS consent, which was performed prior to this payment initiation.	String	OPT	^.{1,36}\$ E.g. Consent-ID: 7890-asdf-4321
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	MAN	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^.{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8

PSD2 - TPP Technical Design

PSU-Accept-Encoding	See above	String	OPT	$\wedge.\{1,50\}\$$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	$\wedge.\{1,50\}\$$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: POST
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.	String	OPT	UUID $\wedge[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 $\wedge\text{GEO}:[\wedge d]^*.[\wedge d]^*[:,;][\wedge d]^*.[\wedge d]^*\$$ E.g.

PSD2 - TPP Technical Design

				PSU-Geo-Location: GEO:90.023856;25 .345963
TPP-Redirect-Preferred	<p>If it equals "true", the TPP prefers a redirect over an embedded SCA approach.</p> <p>If it equals "false", the TPP prefers not to be redirected for SCA. The ASPSP will then choose between the Embedded or the Decoupled SCA approach, depending on the choice of the SCA procedure by the TPP/PSU.</p> <p>If the parameter is not used, the ASPSP will choose the SCA approach to be applied depending on the SCA method chosen by the TPP/PSU.</p> <p>EMBEDDED NOT SUPPORTED IN THIS VERSION</p>	Boolean	OPT	E.g. TPP-Redirect-Preferred: true
TPP-Redirect-URI	<p>URI of the TPP, where the transaction flow shall be redirected to after a Redirect. Mandated for the Redirect SCA Approach, specifically when TPP-Redirect-Preferred equals "true".</p> <p>It is recommended to always use this header field.</p> <p>Remark for Future: This field might be changed to mandatory in the next version of the specification.</p>	String	COND	<p>^.{1,250}\$</p> <p>E.g. TPP-Redirect-URI:"https://tpp.example.es/cb"</p>
TPP-Nok-	If this URI is contained,	String	OPT	^.{1,250}\$

PSD2 - TPP Technical Design

Redirect-URI	the TPP is asking to redirect the transaction flow to this address instead of the TPP-Redirect-URI in case of a negative result of the redirect SCA method. This might be ignored by the ASPSP.			E.g. TPP-Nok-Redirect-URI:"https://tpp.example.es/cb/nok"
TPP-Explicit-Authorisation-Preferred	<p>If it equals "true", the TPP prefers to start the authorisation process separately. This preference might be ignored by the ASPSP, if a signing basket is not supported as functionality.</p> <p>If it equals "false" or if the parameter is not used, there is no preference of the TPP. This especially indicates that the TPP assumes a direct authorisation of the transaction in the next step.</p> <p>Note: the ASPSP may not take it into account if it does not support it.</p>	Boolean	OPT	E.g. TPP-Explicit-Authorisation-Preferred: false
Digest	<p>Is contained if and only if the "Signature" element is contained in the header of the request.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	$\wedge.\{1,100\}\$$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	<p>A signature of the request by the TPP on application level.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	See annexes
TPP-	The certificate used for	String	MAN	$\wedge.\{1,5000\}\$$

PSD2 - TPP Technical Design

Signature-Certificate	signing the request, in base64 encoding.			E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIzZzZvBQlt0UcwDQYJ.....KoZIHvcNAQELBQAwSTE LMAkGA1UEBhMCMCV VMxEzARBgNVBA
------------------------------	--	--	--	---

Body

The content of the Body is defined in 5.15 SinglePayment and the following parameter must also be entered:

Field	Description	Type	Man.	Format
requestedExecutionDate	The payment will be executed on the reported date. Note: this field must be entered.	String	OPT	ISODate E.g. "requestedExecutionDate": "2019-01-12"

3.1.2.2 Response

Header

Field	Description	Type	Man.	Format
Location	Location of the created resource (if created)	String	MAN	Max512Text E.g. Location: /v1/payments/{payment-product}/{payment-id}
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
ASPSP-SCA-Approach	This data element must be contained, if the SCA Approach is	String	COND	E.g. ASPSP-SCA-Approach: REDIRECT

PSD2 - TPP Technical Design

	<p>already fixed. Possible values are:</p> <ul style="list-style-type: none"> • EMBEDDED • DECOUPLED • REDIRECT <p>The OAuth SCA approach will be subsumed by REDIRECT.</p>			
--	--	--	--	--

Body

Field	Description	Type	Man.	Format
transactionStatus	<p>Status of the transaction.</p> <p>Values defined in annexes in 6.4 Transaction status</p>	String	MAN	<p>ISO 20022</p> <p>E.g. "transactionStatus": "RCVD"</p>
paymentId	<p>Resource identification of the generated payment initiation resource.</p>	String	MAN	<p>^.{1,36}\$</p> <p>E.g. "paymentId": "1b3ab8e8-0fd5-43d2-946e-d75958b172e7"</p>
transactionFees	<p>Can be used by the ASPSP to transport transaction fees relevant for the underlying payments.</p>	Amount	OPT	<p>E.g. "transactionFees": {...}</p>
transactionFeeIndicator	<p>If equals true, the transaction will involve specific transaction cost as shown by the ASPSP in their public price list or as agreed between ASPSP and PSU.</p> <p>If equals false, the transaction will not involve additional specific transaction costs to the PSU.</p>	Boolean	OPT	<p>E.g. "transactionFeeIndicator": true</p>
scaMethod	<p>This data element might be contained, if</p>	List<Authentication	COND	<p>E.g. "scaMethods": [...]</p>

PSD2 - TPP Technical Design

<p>s</p>	<p>SCA is required and if the PSU has a choice between different authentication methods.</p> <p>If this data element is contained, then there is also a hyperlink of type "startAuthorisationWithAuthenticationMethodSelection" contained in the response body.</p> <p>These methods shall be presented towards the PSU for selection by the TPP.</p> <p>Note: Only if ASPSP supports selection of the SCA method</p>	<p>onObject ></p>		
<p>_links</p>	<p>A list of hyperlinks to be recognised by the TPP.</p> <p>Type of links admitted in this response:</p> <ul style="list-style-type: none"> • scaRedirect: In case of an SCA Redirect Approach, the ASPSP is transmitting the link to which to redirect the PSU browser. • startAuthorisation: In case, where an explicit start of the transaction authorisation is needed, but no more data needs to be updated (no authentication method to be selected, no PSU 	<p>Links</p>	<p>MAN</p>	<p>E.g. "_links": {...}</p>

PSD2 - TPP Technical Design

	<p>identification nor PSU authentication data to be uploaded).</p> <ul style="list-style-type: none"> • startAuthorisationWithAuthenticationMethodSelection: The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while selecting the authentication method. This link is contained under exactly the same conditions as the data element "scaMethods" • self: link to the resource created by this request. • status: The link to retrieve the transaction status • scaStatus: The link to retrieve the scaStatus of the corresponding authorisation sub-resource. This link is only contained, if an authorisation sub-resource has been already created. 			
psuMessage	Text to be displayed to the PSU	String	OPT	$\wedge.\{1,512\}\$$ E.g. "psuMessage": "Information for the PSU"

PSD2 - TPP Technical Design

tppMessages	Message to the TPP	List<TppMessage>	OPT	E.g. "tppMessages": [...]
--------------------	--------------------	------------------	-----	---------------------------

3.1.2.3 Examples

Example of request for SCA via redirection

POST <https://hub.example.es/aspsp-name/v1/payments/sepa-credit-transfers>

```
Content-Encoding: gzip
Content-Type: application/json
X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA
PSU-IP-Address: 192.168.8.16
PSU-IP-Port: 443
PSU-Accept: application/json
PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: POST
PSU-Device-ID: f8b3fedaf6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
TPP-Redirect-Preferred: true
TPP-Redirect-URI: https://tpp.example.es/cb
TPP-Nok-Redirect-URI: https://tpp.example.es/cb/nok
Date: Sun, 26 Sep 2017 15:02:37 GMT
{
  "instructedAmount": {
    "currency": "EUR",
    "amount": "153.50"
  },
  "debtorAccount": {
    "iban": "ES1111111111111111111111"
  },
}
```

PSD2 - TPP Technical Design

```
"creditorAccount": {  
    "iban": "ES222222222222222222222222"  
},  
"creditorName": "Name123",  
"remittanceInformationUnstructured": "Additional information",  
"requestedExecutionDate": "2019-01-12"  
}
```

3.1.3 Payment initiation for bulk payments

Message sent by the TPP to the ASPSP through the Hub to create a bulk payment initiation.

3.1.3.1 Request

Endpoint

POST {provider}/{aspsp}/v1/bulk-payments/{payment-product}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. hub.example.es
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none">• sepa-credit-transfers• instant-sepa-credit-transfers• target-2-payments• cross-border-credit-transfers	String	MAN	E.g. {provider}/{aspsp-name}/v1/bulk-payments/sepa-credit-transfers/

Query parameters

No additional parameters are specified for this request.

Header

Field	Description	Type	Man.	Format
Content-Type	Value: application/json	String	MAN	Content-Type: application/json
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
Consent-ID	This data element may be contained, if the payment initiation transaction is part of a session, i.e. combined AIS/PIS service. This then contains the "consentId" of the related AIS consent, which was performed prior to this payment initiation.	String	OPT	^.{1,36}\$ E.g. Consent-ID: 7890-asdf-4321
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	MAT	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5

PSD2 - TPP Technical Design

PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^.{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: POST
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by	String	OPT	UUID ^[0-9a-fA-F]{8}-

PSD2 - TPP Technical Design

	<p>the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>			<p>[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$</p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	OPT	<p>RFC 2426</p> <p>^GEO:[\\d]*.[\\d]*[;][\\d]*.[\\d]*\$</p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
TPP-Redirect-Preferred	<p>If it equals "true", the TPP prefers a redirect over an embedded SCA approach.</p> <p>If it equals "false", the TPP prefers not to be redirected for SCA. The ASPSP will then choose between the Embedded or the Decoupled SCA approach, depending on the choice of the SCA procedure by the TPP/PSU.</p> <p>If the parameter is not used, the ASPSP will choose the SCA approach to be applied depending on the SCA method chosen by the TPP/PSU.</p> <p>EMBEDDED NOT SUPPORTED IN THIS VERSION</p>	Boolean	OPT	<p>E.g. TPP-Redirect-Preferred: true</p>
TPP-Redirect-URI	<p>URI of the TPP, where the transaction flow shall be redirected to</p>	String	COND	<p>^.{1,250}\$</p> <p>E.g. TPP-Redirect-URI:"https://tpp.e</p>

PSD2 - TPP Technical Design

	<p>after a Redirect. Mandated for the Redirect SCA Approach, specifically when TPP-Redirect-Preferred equals "true".</p> <p>It is recommended to always use this header field.</p> <p>Remark for Future: This field might be changed to mandatory in the next version of the specification.</p>			xample.es/cb"
TPP-Nok-Redirect-URI	<p>If this URI is contained, the TPP is asking to redirect the transaction flow to this address instead of the TPP-Redirect-URI in case of a negative result of the redirect SCA method. This might be ignored by the ASPSP.</p>	String	OPT	<p>^.{1,250}\$</p> <p>E.g. TPP-Nok-Redirect-URI:"https://tpp.example.es/cb/nok"</p>
TPP-Explicit-Authorisation-Preferred	<p>If it equals "true", the TPP prefers to start the authorisation process separately. This preference might be ignored by the ASPSP, if a signing basket is not supported as functionality.</p> <p>If it equals "false" or if the parameter is not used, there is no preference of the TPP. This especially indicates that the TPP assumes a direct authorisation of the transaction in the next step.</p> <p>Note: the ASPSP may not take it into account if it does not support it.</p>	Boolean	OPT	E.g. TPP-Explicit-Authorisation-Preferred: false

PSD2 - TPP Technical Design

Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYtZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgzCCBmugAwIBAgIIZzZvBQIt0UcwDQYJ.....KoZIHvcNAQELBQAwSTEMAkgA1UEBhMCMVVMxEzARBgNVBA

Body

Field	Description	Type	Man.	Format
batchBookingPreferred	If this element equals true, the PSU prefers only one booking entry. If this element equals false, the PSU prefers individual booking of all contained individual transactions. The ASPSP will follow this preference according to contracts agreed on with the PSU.	Boolean	OPT	E.g. "batchBookingPreferred":true
debtorAccount	The debtor's account.	Account Reference	MAN	E.g. "debtorAccount": {"iban": "ES11111111111111111111111111111111"}
requestedExecution	If contained, the payments contained in	String	OPT	ISODate

PSD2 - TPP Technical Design

Date	this bulk will be executed at the addressed date. This field may not be used together with the field requestedExecutionTime.			E.g. "requestedExecutionDate": "2018-05-17"
requestedExecutionTime	If contained, the payments contained in this bulk will be executed at the addressed Date/Time. This field may not be used together with the field requestedExecutionDate.	String	OPT	ISODateTime
payments	The Bulk Entry Type is a type which follows the JSON formats for the supported products for single payments. <ul style="list-style-type: none"> debtorAccount requestedExecutionDate requestedExecutionTime <p>These three data elements may not be contained in any bulk entry.</p>	Array<SinglePayment>	MAN	E.g. "payments": [...]

3.1.3.2 Response

Header

Field	Description	Type	Man.	Format
Location	Location of the created resource (if created)	String	MAN	^.{1,512}\$ E.g. Location: /v1/bulk-payments/{payment-product}/{payment-id}
X-Request-ID	ID of the request, unique to the call, as determined by the	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-

PSD2 - TPP Technical Design

	initiating party.			fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
ASPSP-SCA-Approach	This data element must be contained, if the SCA Approach is already fixed. Possible values are: <ul style="list-style-type: none"> • EMBEDDED • DECOUPLED • REDIRECT The OAuth SCA approach will be subsumed by REDIRECT.	String	COND	E.g. ASPSP-SCA-Approach: REDIRECT

Body

Field	Description	Type	Man.	Format
transactionStatus	Status of the transaction. Values defined in annexes in 6.4 Transaction status	String	MAN	ISO 20022 E.g. "transactionStatus": "RCVD"
paymentId	Resource identification of the generated payment initiation resource.	String	MAN	^.{1,36}\$ E.g. "paymentId": "1b3ab8e8-0fd5-43d2-946e-d75958b172e7"
transactionFees	Can be used by the ASPSP to transport transaction fees relevant for the underlying payments.	Amount	OPT	E.g. "transactionFees": {...}
transactionFeeIndicator	If equals true, the transaction will involve specific transaction cost as shown by the	Boolean	OPT	E.g. "transactionFeeIndicator": true

PSD2 - TPP Technical Design

	<p>ASPSP in their public price list or as agreed between ASPSP and PSU.</p> <p>If equals false, the transaction will not involve additional specific transaction costs to the PSU.</p>			
scaMethods	<p>This data element might be contained, if SCA is required and if the PSU has a choice between different authentication methods.</p> <p>If this data element is contained, then there is also a hyperlink of type "startAuthorisationWithAuthenticationMethodSelection" contained in the response body.</p> <p>These methods shall be presented towards the PSU for selection by the TPP.</p> <p>Note: Only if ASPSP supports selection of the SCA method</p>	List<AuthenticationObject>	COND	E.g. "scaMethods": [...]
_links	<p>A list of hyperlinks to be recognised by the TPP.</p> <p>Type of links admitted in this response:</p> <ul style="list-style-type: none"> • scaRedirect: In case of an SCA Redirect Approach, the ASPSP is transmitting the link to which to redirect the PSU browser. 	Links	MAN	E.g. "_links": {...}

PSD2 - TPP Technical Design

	<ul style="list-style-type: none"> • startAuthorisation: In case, where an explicit start of the transaction authorisation is needed, but no more data needs to be updated (no authentication method to be selected, no PSU identification nor PSU authentication data to be uploaded). • startAuthorisationWithAuthenticationMethodSelection: The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while selecting the authentication method. This link is contained under exactly the same conditions as the data element "scaMethods" • self: link to the resource created by this request. • status: The link to retrieve the transaction status • scaStatus: The link to retrieve the scaStatus of the corresponding authorisation sub- 			
--	--	--	--	--

PSD2 - TPP Technical Design

	resource. This link is only contained, if an authorisation sub-resource has been already created.			
psuMessage	Text to be displayed to the PSU	String	OPT	^.{1,512}\$ E.g. "psuMessage": "Information for the PSU"
tppMessages	Message to the TPP	List<TppMessage>	OPT	E.g. "tppMessages": [...]

3.1.3.3 Examples

Example of request for SCA via redirect

POST <https://hub.example.es/aspsp-name/v1/bulk-payments/sepa-credit-transfers>

```
Content-Encoding: gzip
Content-Type: application/json
X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA
PSU-IP-Address: 192.168.8.16
TPP-Redirect-Preferred: true
TPP-Redirect-URI: https://tpp.example.es/cb
TPP-Nok-Redirect-URI: https://tpp.example.es/cb/nok
Date: Sun, 26 Sep 2017 15:02:37 GMT
```

```
{
  "batchBookingPreferred": true,
  "debtorAccount": {
    "iban": "ES11111111111111111111111111111111"
  },
  "requestedExecutionDate": "2018-12-21",
  "payments":
  [
    {
```

PSD2 - TPP Technical Design

```
    "instructedAmount": {
      "currency": "EUR",
      "amount": "153.50"
    },
    "creditorAccount": {
      "iban": "ES222222222222222222222222"
    },
    "creditorName": "Name123",
    "remittanceInformationUnstructured": "Additional
information"
  },
  {
    "instructedAmount": {
      "currency": "EUR",
      "amount": "20.30"
    },
    "creditorAccount": {
      "iban": "ES333333333333333333333333"
    },
    "creditorName": "Name123",
    "remittanceInformationUnstructured": "Additional
information"
  }
]
```

Example of response in case of a redirect with an implicitly created authorisation sub-resource

```
HTTP/1.1 201 Created
X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541
ASPSP-SCA-Approach: REDIRECT
Date: Sun, 26 Sep 2017 15:02:43 GMT
Location: /v1/bulk-payments/sepa-credit-transfers/123-qwe-456
Content-Type: application/json
{
```

```
  "transactionStatus": "RCVD",
```

PSD2 - TPP Technical Design

```
"paymentId": "123-qwe-456",
"_links": {
  "scaRedirect": {
    "href": "https://hub.example.es/authorize "
  },
  "self": {
    "href": "/v1/bulk-payments/sepa-credit-transfers/123-qwe-456",
    "status": {
      "href": "/v1/bulk-payments/sepa-credit-transfers/123-qwe-456/status"
    },
    "scaStatus": {
      "href": "/v1/bulk-payments/sepa-credit-transfers/123-qwe-456/authorisations/123auth456"
    }
  }
}
}
```

Example of request for decoupled SCA

POST <https://hub.example.es/asp-name/v1/bulk-payments/sepa-credit-transfers>

Content-Encoding: gzip

Content-Type: application/json

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

Authorization: Bearer 2YotnFZFjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

TPP-Redirect-Preferred: false

Date: Sun, 26 Sep 2017 15:02:37 GMT

```
{
  "batchBookingPreferred": true,
  "debtorAccount": {
    "iban": "ES1111111111111111111111"
  },
  "requestedExecutionDate": "2018-12-21",
  "payments":
```

PSD2 - TPP Technical Design

```
[
  {
    "instructedAmount": {
      "currency": "EUR",
      "amount": "153.50"
    },
    "creditorAccount": {
      "iban": "ES22222222222222222222222222222222"
    },
    "creditorName": "Name123",
    "remittanceInformationUnstructured": "Additional
information"
  },
  {
    "instructedAmount": {
      "currency": "EUR",
      "amount": "20.30"
    },
    "creditorAccount": {
      "iban": "ES33333333333333333333333333333333"
    },
    "creditorName": "Name123",
    "remittanceInformationUnstructured": "Additional
information"
  }
]
```

Example of response in case of an decoupled SCA approach with implicitly creating an authorisation sub-resource

HTTP/1.1 201 Created
X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541
ASPSP-SCA-Approach: DECOUPLED
Date: Sun, 26 Sep 2017 15:02:43 GMT
Location: </v1/bulk-payments/sepa-credit-transfers/123-qwe-456>
Content-Type: application/json

PSD2 - TPP Technical Design

```
{
  "transactionStatus": "RCVD",
  "paymentId": "123-qwe-456",
  "_links": {
    "self": {
      "href": "/v1/bulk-payments/sepa-credit-transfers/123-qwe-456"
    },
    "status": {
      "href": "/v1/bulk-payments/sepa-credit-transfers/123-qwe-456/status"
    },
    "scaStatus": {
      "href": "/v1/bulk-payments/sepa-credit-transfers/123-qwe-456/authorisations/123auth456"
    }
  },
  "psuMessage": "Please use your XXX Bank app to authorise the payment"
}
```

3.1.4 Initiation for standing orders for recurring/periodic payments

Message sent by the TPP to the ASPSP through the Hub to create a future recurring/periodic payment initiation.

The functionality of recurring payment initiations is covered by the Berlin Group specification as a specific standing order initiation.

The TPP can submit a recurring payment initiation where the starting date, frequency and conditionally an end date is provided. Once authorised by the PSU, the payment then will be executed by the ASPSP, if possible, following this "standing order" as submitted by the TPP. No further TPP action is needed. This payment is called a periodic payment in this context to differentiate the payment from recurring payment types, where third parties are initiating the same amount of money e.g. payees for using credit card transactions or direct debits for recurring payments of goods or services. These latter types of payment initiations are not part of this interface.

Note: for the permanent payment initiation orders, the ASPSP will always request SCA with Dynamic linking. No exceptions are allowed.

dayOfExecution field rules

- **Daily payments:** the "dayOfExecution" field is not required. The first payment is the "startDate", and from then on, the payment is made every day.
- **Weekly payments:** if "dayOfExecution" is required, the possible values are from 01=Monday to 07=Sunday. If "dayOfExecution" is not required, the "startDate" used is that of the day of the week on which the payment was made. (If the "startDate" is Thursday, the payment will be made every Thursday)
- **Twice-monthly payments:** the same rule as for weekly payments applies.
- **Monthly or less frequent payments:** the possible values range from 01 to 31, using 31 as the last day of the month.

3.1.4.1 Request

Endpoint

POST {provider}/{aspsp}/v1/periodic-payments/{payment-product}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. hub.example.es
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none"> • sepa-credit-transfers • instant-sepa-credit-transfers • target-2-payments • cross-border-credit-transfers 	String	MAN	E.g. {provider}/{aspsp-name}/v1/periodic-payments/sepa-credit-transfers/

Query parameters

No additional parameters are specified for this request.

Header

Field	Description	Type	Man.	Format
Content-Type	Value: application/json	String	MAN	Content-Type: application/json
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
Consent-ID	This data element may be contained, if the payment initiation transaction is part of a session, i.e. combined AIS/PIS service. This then contains the "consentId" of the related AIS consent, which was performed prior to this payment initiation.	String	OPT	^.{1,36}\$ E.g. Consent-ID: 7890-asdf-4321
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	MAN	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5

PSD2 - TPP Technical Design

PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^.{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: POST

PSD2 - TPP Technical Design

<p>PSU-Device-ID</p>	<p>UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>	<p>String</p>	<p>OPT</p>	<p>UUID</p> <p><code>^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$</code></p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
<p>PSU-Geo-Location</p>	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	<p>String</p>	<p>OPT</p>	<p>RFC 2426</p> <p><code>^GEO:[\\d]*.[\\d]*[;][\\d]*.[\\d]*\$</code></p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
<p>TPP-Redirect-Preferred</p>	<p>If it equals "true", the TPP prefers a redirect over an embedded SCA approach.</p> <p>If it equals "false", the TPP prefers not to be redirected for SCA. The ASPSP will then choose between the Embedded or the Decoupled SCA approach, depending on the choice of the SCA procedure by the TPP/PSU.</p> <p>If the parameter is not used, the ASPSP will choose the SCA approach to be applied depending on the SCA method chosen by the TPP/PSU.</p> <p>EMBEDDED NOT SUPPORTED IN THIS VERSION</p>	<p>Boolean</p>	<p>OPT</p>	<p>E.g. TPP-Redirect-Preferred: true</p>

PSD2 - TPP Technical Design

<p>TPP-Redirect-URI</p>	<p>URI of the TPP, where the transaction flow shall be redirected to after a Redirect. Mandated for the Redirect SCA Approach, specifically when TPP-Redirect-Preferred equals "true".</p> <p>It is recommended to always use this header field.</p> <p>Remark for Future: This field might be changed to mandatory in the next version of the specification.</p>	<p>String</p>	<p>COND</p>	<p>^.{1,250}\$</p> <p>E.g. TPP-Redirect-URI:"https://tpp.example.es/cb"</p>
<p>TPP-Nok-Redirect-URI</p>	<p>If this URI is contained, the TPP is asking to redirect the transaction flow to this address instead of the TPP-Redirect-URI in case of a negative result of the redirect SCA method. This might be ignored by the ASPSP.</p>	<p>String</p>	<p>OPT</p>	<p>^.{1,250}\$</p> <p>E.g. TPP-Nok-Redirect-URI:"https://tpp.example.es/cb/nok"</p>
<p>TPP-Explicit-Authorisation-Preferred</p>	<p>If it equals "true", the TPP prefers to start the authorisation process separately. This preference might be ignored by the ASPSP, if a signing basket is not supported as functionality.</p> <p>If it equals "false" or if the parameter is not used, there is no preference of the TPP. This especially indicates that the TPP assumes a direct authorisation of the transaction in the next step.</p> <p>Note: the ASPSP may not take it into account</p>	<p>Boolean</p>	<p>OPT</p>	<p>E.g. TPP-Explicit-Authorisation-Preferred: false</p>

PSD2 - TPP Technical Design

	if it does not support it.			
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	OPT	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYtZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ= =
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQlt0UcwDQYJ.....KoZIHvcNAQELBQAwSTELMAkGA1UEBhMCMVVMxEzARBgNVBA

Body

The content of the body is defined in 5.15 SinglePayment together with the following definitions:

Field	Description	Type	Man.	Format
startDate	The first applicable day of execution starting from this date is the first payment.	String	MAN	ISODate E.g. "startDate":"2018-12-20"
executionRule	Supported values: <ul style="list-style-type: none"> following preceding This data attribute	String	OPT	E.g. "executionRule":"following"

PSD2 - TPP Technical Design

	<p>defines the behavior when recurring payment dates falls on a weekend or bank holiday. The payment is then executed either the "preceding" or "following" working day.</p> <p>ASPSP might reject the request due to the communicated value, if rules in Online-Banking are not supporting this execution rule.</p>			
endDate	<p>The last applicable day of execution</p> <p>If not given, it is an infinite standing order.</p>	String	OPT	<p>ISODate</p> <p>E.g. "endDate":"2019-01-20"</p>
frequency	<p>The frequency of the recurring payment resulting from this standing order.</p> <p>Permitted values:</p> <ul style="list-style-type: none"> • Daily • Weekly • EveryTwoWeeks • Monthly • EveryTwoMonths • Quarterly • SemiAnnual • Annual 	String	MAN	<p>ISO 20022 EventFrequency7Code</p> <p>E.g. "frequency":"Monthly"</p>
dayOfExecution	<p>"31" is ultimo.</p> <p>The format is following the regular expression $\backslash d\{1,2\}$. Example: The first day is addressed by "1".</p> <p>The date is referring to the time zone of the ASPSP.</p> <p>Only if supported in the ASPSP Online</p>	String	COND	<p>$\backslash d\{1,2\}$</p> <p>E.g. "dayOfExecution":"01"</p>

	Banking.			
--	----------	--	--	--

3.1.4.2 Response

Header

Field	Description	Type	Man.	Format
Location	Location of the created resource (if created)	String	MAN	$\wedge.\{1,512\}\$$ E.g. Location: /v1/periodic-payments/{payment-product}/{payment-id}
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $\wedge[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
ASPSP-SCA-Approach	This data element must be contained, if the SCA Approach is already fixed. Possible values are: <ul style="list-style-type: none"> EMBEDDED DECOUPLED REDIRECT The OAuth SCA approach will be subsumed by REDIRECT.	String	COND	E.g. ASPSP-SCA-Approach: REDIRECT

Body

Field	Description	Type	Man.	Format
transactionStatus	Status of the transaction. Values defined in annexes in 6.4	String	MAN	ISO 20022 E.g. "transactionStatus": "RCVD"

PSD2 - TPP Technical Design

	Transaction status			
paymentId	Resource identification of the generated payment initiation resource.	String	MAN	$\wedge.\{1,36\}\$$ E.g. "paymentId": "1b3ab8e8-0fd5-43d2-946e-d75958b172e7"
transactionFees	Can be used by the ASPSP to transport transaction fees relevant for the underlying payments.	Amount	OPT	E.g. "transactionFees": {...}
transactionFeeIndicator	If equals true, the transaction will involve specific transaction cost as shown by the ASPSP in their public price list or as agreed between ASPSP and PSU. If equals false, the transaction will not involve additional specific transaction costs to the PSU.	Boolean	OPT	E.g. "transactionFeeIndicator": true
scaMethods	This data element might be contained, if SCA is required and if the PSU has a choice between different authentication methods. If this data element is contained, then there is also a hyperlink of type "startAuthorisationWithAuthenticationMethodSelection" contained in the response body. These methods shall be presented towards the PSU for selection by the TPP. Note: Only if ASPSP supports selection of	List<AuthenticationObject>	COND	E.g. "scaMethods": [...]

PSD2 - TPP Technical Design

	the SCA method			
_links	<p>A list of hyperlinks to be recognised by the TPP.</p> <p>Type of links admitted in this response:</p> <ul style="list-style-type: none"> • scaRedirect: In case of an SCA Redirect Approach, the ASPSP is transmitting the link to which to redirect the PSU browser. • startAuthorisation: In case, where an explicit start of the transaction authorisation is needed, but no more data needs to be updated (no authentication method to be selected, no PSU identification nor PSU authentication data to be uploaded). • startAuthorisationWithAuthenticationMethodSelection: The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while selecting the authentication method. This link is contained under 	Links	MAN	E.g. "_links": {...}

PSD2 - TPP Technical Design

	<p>exactly the same conditions as the data element "scaMethods"</p> <ul style="list-style-type: none"> • self: link to the resource created by this request. • status: The link to retrieve the transaction status • scaStatus: The link to retrieve the scaStatus of the corresponding authorisation sub-resource. This link is only contained, if an authorisation sub-resource has been already created. 			
psuMessage	Text to be displayed to the PSU	String	OPT	$\wedge.\{1,512\}\$$ E.g. "psuMessage": "Information for the PSU"
tppMessages	Message to the TPP	List<Tpp Message >	OPT	E.g. "tppMessages": [...]

3.1.4.3 Examples

Example of request for SCA via redirect

POST <https://hub.example.es/{aspsp-name}/v1/periodic-payments/sepa-credit-transfers>

Content-Encoding: gzip

Content-Type: application/json

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

TPP-Redirect-Preferred: true

PSD2 - TPP Technical Design

TPP-Redirect-URI: https://tpp.example.es/cb

TPP-Nok-Redirect-URI: https://tpp.example.es/cb/nok

Date: Sun, 26 Sep 2017 15:02:37 GMT

```
{
  "instructedAmount": {
    "currency": "EUR",
    "amount": "153.50"
  },
  "creditorAccount": {
    "iban": "ES22222222222222222222222222222222"
  },
  "creditorName": "Name123",
  "remittanceInformationUnstructured": "Additional information",
  "startDate": "2018-03-01",
  "executionRule": "preceeding",
  "frequency": "Monthly",
  "dayOfExecution": "01"
}
```

3.1.5 Get payment status

This message is sent by the TPP to the HUB to request information on the status of the payment initiation requested by the TPP.

3.1.5.1 Request

Endpoint

GET {provider}/{aspsp}/v1/{payment-service}/{payment-product}/{paymentId}/status

Path

Field	Description	Type	Man.	Format
-------	-------------	------	------	--------

PSD2 - TPP Technical Design

provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-service	Possible values are: <ul style="list-style-type: none"> • payments • bulk-payments • periodic-payments 	String	MAN	E.g. {provider}/{aspsp}/v1/payments
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none"> • sepa-credit-transfers • instant-sepa-credit-transfers • target-2-payments • cross-border-credit-transfers 	String	MAN	E.g. {provider}/{aspsp}/v1/payments/sepa-credit-transfers/
paymentId	Resource Identification of the related payment. Sent previously as a response to a message initiating payment by the TPP to the HUB.	String	MAN	^.{1,36}\$ E.g. 1234-qwer-5678

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-

PSD2 - TPP Technical Design

				43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsic MWpAA
Accept	Response format supported. Supported values: <ul style="list-style-type: none"> • application/json 	String	OPT	^.{1,50}\$ E.g. Accept: application/json
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-

PSD2 - TPP Technical Design

				Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: GET
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\d]*.[\d]*[;][\d]*.[\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.345963
Digest	Is contained if and only if the "Signature" element is contained in	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY

PSD2 - TPP Technical Design

	the header of the request. See 6.1 Signature for more information.			5M2M2NDYyMmVjO WFmMGNmYTziNT U3MjVmNDI4NTRIM zJkYzE3ZmNmMDE 3ZGFmMjhhNTc5OT U3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwI BAgIIzZzVbQIt0Uc wDQYJ.....KoZI hvcNAQELBQAwSTE LMAkGA1UEBhMVCV VMxEzARBgNVBA

Body

No additional data are specified.

3.1.5.2 Response

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}- [0-9a-fA-F]{4}-[0- 9a-fA-F]{4}-[0-9a- fA-F]{4}-[0-9a-fA- F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5- 43d2-946e- d75958b172e7

Body

PSD2 - TPP Technical Design

Field	Description	Type	Man.	Format
transactionStatus	Status of the payment transaction. Values defined in 6.4 Transaction status	String	MAN	ISO20022 E.g. "transactionStatus": "ACCP"
fundsAvailable	This data element is contained, if supported by the ASPSP, if a funds check has been performed and if the transactionStatus is: <ul style="list-style-type: none"> • ATCT • ACWC • ACCP 	Boolean	COND	E.g. "fundsAvailable": true
psuMessage	Text to show to the PSU.	String	OPT	^.{1,512}\$ E.g. "psuMessage": "Information for PSU"
tppMessages	Message for the TPP	List<Tp pMessage>	OPT	E.g. "tppMessages": [...]

3.1.5.3 Examples

Example of request

GET <https://www.hub.com/aspsp-name/v1/payments/sepa-credit-transfer/123asdf456/status>

Accept: application/json

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSD2 - TPP Technical Design

PSU-Http-Method: GET
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of response

```
HTTP/1.1 200 Ok
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:50 GMT
Content-Type: application/json
{
  "transactionStatus": "ACCP",
  "fundsAvailable": true
}
```

3.1.6 Get payment initiation

This message is sent by the TPP through the HUB to the ASPSP to obtain the information of a payment initiation.

3.1.6.1 Request

Endpoint

GET {provider}/{aspsp}/v1/{payment-service}/{payment-product}/{paymentId}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-service	Possible values are: <ul style="list-style-type: none">• payments• bulk-payments• periodic-payments	String	MAN	E.g. {provider}/{aspsp}/v1/payments
payment-product	Payment product to be	String	MAN	E.g.

PSD2 - TPP Technical Design

	used. List of supported products: <ul style="list-style-type: none"> • sepa-credit-transfers • instant-sepa-credit-transfers • target-2-payments • cross-border-credit-transfers 			{provider}/{aspssp}/v1/payments/sepa-credit-transfers/
paymentId	Resource Identification of the related payment. Sent previously as a response to a message initiating payment by the TPP to the HUB.	String	MAN	^.{1,36}\$ E.g. 1234-qwer-5678

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field	String	OPT	^[0-9]{1,3}.[0-9]{1,3}.[0-9]{1,3}.[0-9]{1,3}\$

PSD2 - TPP Technical Design

	between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.			E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none">• GET• POST• PUT	String	OPT	E.g. PSU-Http-Method: GET

PSD2 - TPP Technical Design

	<ul style="list-style-type: none"> • PATCH • DELETE 			
PSU-Device-ID	<p>UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>	String	OPT	<p>UUID</p> <p>$^{[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}}\\$</p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	OPT	<p>RFC 2426</p> <p>$^{GEO:[\d]*.[\d]*[;][\d]*.[\d]*}\\$</p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
Digest	<p>Is contained if and only if the "Signature" element is contained in the header of the request.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>$^{\{1,100\}}\\$</p> <p>E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==</p>
Signature	<p>A signature of the request by the TPP on application level.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>See annexes</p>
TPP-Signature-Certificate	<p>The certificate used for signing the request, in base64 encoding.</p>	String	MAN	<p>$^{\{1,5000\}}\\$</p> <p>E.g. TPP-Signature-Certificate: MIIHgzCCBmugAwI</p>

				BAGIIzZzVbQIt0Uc wDQYJ.....KoZI hvcNAQELBQAwSTE LMAkGA1UEBhMCMV VMxEzARBgNVBA
--	--	--	--	---

Body

No additional data are specified.

3.1.6.2 Response

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

The fields to return are those requesting initiation of the original payment:

- 3.1.1 Payment initiation
- 3.1.2 Payment initiation for future dated payments
- 3.1.3 Payment initiation for bulk payments
- 3.1.4 Initiation for standing orders for recurring/periodic payments

Plus the following:

Field	Description	Type	Man.	Format
transactionStatus	Status of the transaction. Values defined in annexes. Short code.	String	MAN	ISO 20022 E.g. "transactionStatus": "ACCP"
psuMessage	Text to show to the	String	OPT	^.{1,512}\$

PSD2 - TPP Technical Design

e	PSU.			E.g. "psuMessage": "Information for the PSU"
tppMessages	Message for the TPP	List<Tpp Message >	OPT	E.g. "tppMessage": [...]

3.1.6.3 Examples

Example of request

GET <https://www.hub.com/aspsp-name/v1/payments/sepa-credit-transfers/123-asdf-456>

Accept: application/json

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSU-Http-Method: GET

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSU-GEO-Location: GEO:12.526347;54.649862

Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of response

HTTP/1.1 200 Ok

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Date: Sun, 26 Sep 2017 15:02:50 GMT

Content-Type: application/json

```
{
  "instructedAmount": {
    "currency": "EUR",
    "amount": "153.50"
  }
}
```


PSD2 - TPP Technical Design

```
    },
    "debtorAccount": {
        "iban": "ES11111111111111111111111111111111"
    },
    "creditorAccount": {
        "iban": "ES22222222222222222222222222222222"
    },
    "creditorName": "Name123",
    "remittanceInformationUnstructured": "Additional information",
    "transactionStatus": "ACCP"
}
```

3.1.7 Payment cancellation

This request is sent by the TPP to the ASPSP through the Hub and allows payment cancellation to be initiated. Depending on the payment-service, the payment-product and the ASPSP's implementation, this TPP call might be sufficient to cancel a payment. If an authorisation of the payment cancellation is mandated by the ASPSP, a corresponding hyperlink will be contained in the response message.

3.1.7.1 Request

Endpoint

DELETE {provider}/{aspsp}/v1/{payment-service}/{payment-product}/{paymentId}

Path

Field	Description	Type	Man.	Format
provider	URL of the ASPSP where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-service	Possible values are: <ul style="list-style-type: none">• payments• bulk-payments• periodic-	String	MAN	E.g. {provider}/v1/payments

PSD2 - TPP Technical Design

	payments			
paymentId	Identifier of the resource that references the payment initiation. Sent previously as a response to a message initiating payment by the HUB to the ASPSP.	String	MAN	^.{1,36}\$ E.g.123-qwe-456

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5

PSD2 - TPP Technical Design

PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: DELETE
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-

PSD2 - TPP Technical Design

	<p>by the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>			<p>9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$</p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	OPT	<p>RFC 2426</p> <p>^GEO:[\\d]*.[\\d]*[;][\\d]*.[\\d]*\$</p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
Digest	<p>Is contained if and only if the "Signature" element is contained in the header of the request.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>^.{1,100}\$</p> <p>E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==</p>
Signature	<p>A signature of the request by the TPP on application level.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>See annexes</p>
TPP-Signature-Certificate	<p>The certificate used for signing the request, in base64 encoding.</p>	String	MAN	<p>^.{1,5000}\$</p> <p>E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQIt0UcwDQYJ...KoZIHvcNAQELBQAwSTELMAkGA1UEBhM CVVMxEzARBgNVBA</p>

Body

No additional data are specified.

3.1.7.2 Response

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $\wedge[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Man.	Format
transactionStatus	Status of the transaction. Values defined in annexes in 6.4 Transaction status	String	MAN	ISO 20022 E.g. "transactionStatus": "CANC"
scaMethods	<p>This data element might be contained, if SCA is required and if the PSU has a choice between different authentication methods.</p> <p>If this data element is contained, then there is also a hyperlink of type "startAuthorisationWithAuthenticationMethodSelection" contained in the response body.</p> <p>These methods shall be presented towards the PSU for selection by the TPP.</p> <p>Note: Only if ASPSP</p>	List<AuthenticationObject>	COND	E.g. "scaMethods": [...]

PSD2 - TPP Technical Design

	supports selection of the SCA method			
_links	<p>A list of hyperlinks to be recognised by the TPP.</p> <p>Type of links admitted in this response:</p> <ul style="list-style-type: none"> • startAuthorisation: In case, where an explicit start of the transaction authorisation is needed, but no more data needs to be updated (no authentication method to be selected, no PSU identification nor PSU authentication data to be uploaded). • startAuthorisationWithAuthenticationMethodSelection: The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while selecting the authentication method. This link is contained under exactly the same conditions as the data element "scaMethods" 	Links	COND	E.g. "_links": {...}
psuMessage	Text to show to the PSU.	String	OPT	$\wedge.\{1,512\}\$$ E.g. "psuMessage": "Information for the

PSD2 - TPP Technical Design

				PSU"
tppMessages	Message for the TPP	List<Tpp Message >	OPT	E.g. "tppMessages": [...]

3.1.7.3 Examples

Example of request

DELETE <https://www.hub.com/aspsp-name/v1/payments/sepa-credit-transfers/123-qwe-456>

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSU-Http-Method: GET

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSU-GEO-Location: GEO:12.526347;54.649862

Content-Type: application/json

Date: Sun, 26 Sep 2017 15:02:48 GMT

Example in case the DELETE process as such is already sufficient for cancelling the payment

HTTP/1.1 204 No Content

X-Request-ID: 0ee25bf4-6ff1-11e8-adc0-fa7ae01bbebc

Date: Sun, 26 Sep 2017 15:02:47 GMT

Example in case an authorisation of the cancellation is needed by the PSU

HTTP/1.1 200 Ok

X-Request-ID: 0ee25bf4-6ff1-11e8-adc0-fa7ae01bbebc

Date: Sun, 26 Sep 2017 15:02:47 GMT

PSD2 - TPP Technical Design

```
{
  "transactionStatus": "ACTC",
  "_links": {
    "startAuthorisation": {
      "href": "/v1/payments/sepa-credit-transfers/123-qwe-456/cancellation-authorisations"
    }
  }
}
```

3.1.8 Multilevel SCA for payments

In the case of the SCA flow by redirection, the TPP may redirect to PSU, which initiates the transaction to the scaRedirect link for applying SCA.

In the case of SCA decoupled flow, the TPP will receive in the psuMessage field the message it must show to the PSU and direct to the PSU's bank app.

In addition, the ASPSP will return a message in the psuMessage field to indicate to the PSU that the transaction requires SCA by more users.

3.2 AIS: Establish account information consent service

3.2.1 Characteristics of the consent

3.2.1.1 Consent model

Model	Description
Detailed consent	Request consent for the accounts indicated Create a consent, which the ASPSP must store, requesting access for the accounts indicated and with the requested access. If there was already consent, this consent will expire and the new agreement will enter into force when authorised by the PSU. The accounts for which consent is requested to access the "balances" and/or "transactions" are also assumed to have the "accounts" access type.

Global consent	<p>Request consent for the list of available accounts This functionality only serves to request consent for the list of available PSU accounts. It does not give consent for "accounts", "balances" and/or "transactions".</p> <p>This request does not indicate the accounts for which access is wanted. It indicates that it is requested for "all available accounts", indicating in the access the "availableAccounts" or "availableAccountsWithBalances" with the value "allAccounts".</p> <p>It is a once-time-only consent to obtain the list of available accounts. It will not give details of the accounts.</p> <p>Request consent to obtain access to all the accounts for all the PSD2 AIS services Request access for all the PSU accounts available on all the PSD2 AIS services.</p> <p>The accounts are not indicated by the TPP.</p> <p>This request does not indicate the accounts for which access is wanted. The request is indicated as being for "all PSD2 accounts", indicating in the access the "allPsd2" attribute with the value "allAccounts".</p> <p>Through the HUB, the TPP may recover this information managed between ASPSP and PSU, making a request to recover consent information.</p>
Bank-offered consent	<p>Request consent without indicating the accounts Request consent to access "accounts", "balances" and/or "transactions" without indicating the accounts. Thus the "accounts", "balances" and "transactions" attributes will include a blank array.</p> <p>To select the accounts that will be provided, access must be obtained bilaterally between ASPSP and PSU through the ASPSP interface in the OAuth redirect flow.</p> <p>In the redirection process, the ASPSP will show the PSU its accounts so that the PSU can choose which to provide consent for to the TPP.</p> <p>Through the HUB, the TPP may recover this information managed between ASPSP and PSU, making a request to recover consent information.</p>

3.2.1.2 Recurring access

Recurring consents

If there is already a prior consent with recurring access (recurringIndicator=true) and a new consent request is sent with recurring access, as soon as the new consent is accepted by the PSU, the prior consent will expire and only the new requested consent will be valid.

A consent with recurring access may have one or more accounts with different types of access ("accounts", "balances", "transactions")

Note: giving access to "balances" and/or "transactions" automatically grants "accounts" access to these accounts.

Non-recurring consents

A consent request for non-recurring access (once-only and with recurringIndicator=false) will be treated as a new consent (new consentId) without affecting previous existing consents.

3.2.1.3 Account owner name delivery

This specification is following the consent models described in NextGentPSD2 XS2A Framework v1.3.6. In particular, this specification follows:

- The ASPSP deliver the account owner name without any extension to the consent model defined below.
- The provision of this service by an ASPSP might depend on the fact that the account owner name is also delivered in online channels of the ASPSP

3.2.2 Account information consent

With this service, a TPP may request consent through the HUB to access the PSU accounts. This request may be for indicated accounts or not.

That is why the consent request has these variants:

- Establish consent for account information on the indicated accounts
- Establish account information consent to obtain a list of all available accounts
- Establish consent for account information without indicating the accounts
- Establish account information consent to obtain access to all accounts for all types of PSD2 AIS access: "accounts", "balances" and/or "transactions"

Note: each consent information will generate a new resource, i.e. a new consentId.

3.2.2.1 Request

Endpoint

POST {provider}/{aspsp}/v1/consents

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $^{[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpA A
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and	String	OPT	$^{[0-9]\{1,3\}.[0-9]\{1,3\}.[0-9]\{1,3\}.[0-9]\{1,3\}}\$$ E.g. PSU-IP-Address: 192.168.16.5

PSD2 - TPP Technical Design

	<p>TPP.</p> <p>If not available, the TPP shall use the IP Address used by the TPP when submitting this request.</p>			
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	$\wedge \\d{1,5}\$$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	$\wedge .\{1,50}\$$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	$\wedge .\{1,50}\$$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	$\wedge .\{1,50}\$$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	$\wedge .\{1,50}\$$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST 	String	OPT	E.g. PSU-Http-Method: POST

PSD2 - TPP Technical Design

	<ul style="list-style-type: none"> • PUT • PATCH • DELETE 			
PSU-Device-ID	<p>UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>	String	OPT	<p>UUID</p> <p><code>^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$</code></p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	OPT	<p>RFC 2426</p> <p><code>^GEO:[\\d]*.[\\d]*[;][\\d]*.[\\d]*\$</code></p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
TPP-Redirect-Preferred	<p>If it equals "true", the TPP prefers a redirect over an embedded SCA approach.</p> <p>If it equals "false", the TPP prefers not to be redirected for SCA. The ASPSP will then choose between the Embedded or the Decoupled SCA approach, depending on the choice of the SCA procedure by the TPP/PSU.</p> <p>If the parameter is not used, the ASPSP will choose the SCA approach to be applied depending on</p>	Boolean	OPT	<p>E.g. TPP-Redirect-Preferred: true</p>

PSD2 - TPP Technical Design

	<p>the SCA method chosen by the TPP/PSU.</p> <p>EMBEDDED NOT SUPPORTED IN THIS VERSION</p>			
TPP-Redirect-URI	<p>URI of the TPP, where the transaction flow shall be redirected to after a Redirect. Mandated for the Redirect SCA Approach, specifically when TPP-Redirect-Preferred equals "true".</p> <p>It is recommended to always use this header field.</p> <p>Remark for Future: This field might be changed to mandatory in the next version of the specification.</p>	String	COND	<p>^.{1,250}\$</p> <p>E.g. TPP-Redirect-URI:"https://tpp.example.es/cb"</p>
TPP-Nok-Redirect-URI	<p>If this URI is contained, the TPP is asking to redirect the transaction flow to this address instead of the TPP-Redirect-URI in case of a negative result of the redirect SCA method. This might be ignored by the ASPSP.</p>	String	OPT	<p>^.{12,50}\$</p> <p>E.g. TPP-Nok-Redirect-URI:"https://tpp.example.es/cb/nok"</p>
TPP-Explicit-Authorisation-Preferred	<p>If it equals "true", the TPP prefers to start the authorisation process separately. This preference might be ignored by the ASPSP, if a signing basket is not supported as functionality.</p>	Boolean	OPT	<p>E.g. TPP-Explicit-Authorisation-Preferred: false</p>

PSD2 - TPP Technical Design

	<p>If it equals "false" or if the parameter is not used, there is no preference of the TPP. This especially indicates that the TPP assumes a direct authorisation of the transaction in the next step.</p> <p>Note: the ASPSP may not take it into account if it does not support it.</p>			
Digest	<p>Is contained if and only if the "Signature" element is contained in the header of the request.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>^.{1,100}\$</p> <p>E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRI MzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==</p>
Signature	<p>A signature of the request by the TPP on application level.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	See annexes
TPP-Signature-Certificate	<p>The certificate used for signing the request, in base64 encoding.</p>	String	MAN	<p>^.{1,5000}\$</p> <p>E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgII ZzZvBQlt0UcwDQYJ.....KoZIHvcNAQELBQAWS TELMakGA1UEBhMCVVM xEzARBgNVBA</p>

Body

Field	Description	Type	Man.	Format
access	<p>Accesses requested to the services. Only the sub-attributes with "accounts", "balances"</p>	Account Access	MAN	E.g. "access": {...}

PSD2 - TPP Technical Design

	and "transactions" tags are accepted. In addition, the ASPSP may support the attributes "availableAccounts", "availableAccountsWithBalances" or "allPsd2" with the value "allAccounts".			
recurringIndicator	<p>Possible values:</p> <ul style="list-style-type: none"> • true: recurring access to the account. • false: once-only access. 	Boolean	MAN	E.g. "recurringIndicator": true
validUntil	<p>Date until which the consent requests access.</p> <p>The following value should be used to create consent with the maximum possible access time: 9999-12-31</p> <p>When consent is recovered, the maximum possible date will be adjusted.</p>	String	MAN	ISODate E.g. "validUntil": "2018-05-17"
frequencyPerDay	This field indicates the requested maximum frequency for an access without PSU involvement per day. For a one-off access, this attribute is set to "1".	Integer	MAN	E.g. "frequencyPerDay": 4
combinedServiceIndicator	If true indicates that a payment initiation service will be addressed in the same "session"	Boolean	MAN	E.g. "combinedServiceIndicator": false

3.2.2.2 Response

Header

Field	Description	Type	Man.	Format
Location	Location of the created resource (if created)	String	MAN	Max512Text E.g. Location: /v1/consents/{consentId}
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
ASPSP-SCA-Approach	This data element must be contained, if the SCA Approach is already fixed. Possible values are: <ul style="list-style-type: none"> EMBEDDED DECOUPLED REDIRECT <p>The OAuth SCA approach will be subsumed by REDIRECT.</p>	String	COND	E.g. ASPSP-SCA-Approach: REDIRECT

Body

Field	Description	Type	Man.	Format
consentStatus	Consent authentication status. See values defined in 6.5 Consent status	String	MAN	E.g. "consentStatus": "received"
consentId	Identifier of the resource that references the consent. It must be contained if a consent	String	MAN	^.{1,36}\$ E.g. "consentId": "123-QWE-456"

PSD2 - TPP Technical Design

	was generated.			
scaMethods	<p>This data element might be contained, if SCA is required and if the PSU has a choice between different authentication methods.</p> <p>If this data element is contained, then there is also a hyperlink of type "startAuthorisationWithAuthenticationMethodSelection" contained in the response body.</p> <p>These methods shall be presented towards the PSU for selection by the TPP.</p> <p>Note: Only if ASPSP supports selection of the SCA method</p>	List<AuthenticationObject>	COND	E.g. "scaMethods": [...]
_links	<p>A list of hyperlinks to be recognised by the TPP.</p> <p>Type of links admitted in this response:</p> <ul style="list-style-type: none"> • scaRedirect: In case of an SCA Redirect Approach, the ASPSP is transmitting the link to which to redirect the PSU browser. • startAuthorisation: In case, where an explicit start of the transaction authorisation is needed, but no more data needs to be updated (no authentication method to be selected, no PSU 	Links	MAN	E.g. "_links": {...}

PSD2 - TPP Technical Design

	<p>identification nor PSU authentication data to be uploaded).</p> <ul style="list-style-type: none"> • startAuthorisationWithAuthenticationMethodSelection: The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while selecting the authentication method. This link is contained under exactly the same conditions as the data element "scaMethods" • self: link to the resource created by this request. • status: The link to retrieve the transaction status • scaStatus: The link to retrieve the scaStatus of the corresponding authorisation sub-resource. This link is only contained, if an authorisation sub-resource has been already created. 			
psuMessage	Text to be displayed to the PSU	String	OPT	$\wedge.\{1,512\}\$$ E.g. "psuMessage": "Information for the PSU"
tppMessage	Message to the TPP	List<Tp	OPT	E.g. "tppMessages":

PSD2 - TPP Technical Design

```
    }
    ],
    "transactions": [
      {
        "iban": "ES11111111111111111111111111111111"
      }
    ]
  },
  "recurringIndicator": true,
  "validUntil": "2018-05-17",
  "frequencyPerDay": 4
}
```

Example of consent request for the list of available accounts with SCA via redirect

POST <https://www.hub.com/aspsp-name/v1/consents>

Content-Encoding: gzip

Content-Type: application/json

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSU-Http-Method: POST

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSU-GEO-Location: GEO:12.526347;54.649862

TPP-Redirect-Preferred: true

TPP-Redirect-URI: https://www.tpp.com/cb

TPP-Nok-Redirect-URI: https://www.tpp.com/cb/nok

Date: Sun, 26 Sep 2017 15:02:37 GMT

```
{
```

```
  "access": {
```

```
    "availableAccounts": "allAccounts"
```

PSD2 - TPP Technical Design

```
    },  
    "recurringIndicator": false,  
    "validUntil": "2018-05-17",  
    "frequencyPerDay": 1  
}
```

Example of consent request without indicating the accounts and decoupled SCA

POST <https://www.hub.com/aspsp-name/v1/consents>

```
Content-Encoding: gzip  
Content-Type: application/json  
X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541  
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA  
PSU-IP-Address: 192.168.8.16  
PSU-IP-Port: 443  
PSU-Accept: application/json  
PSU-Accept-Charset: utf-8  
PSU-Accept-Encoding: gzip  
PSU-Accept-Language: es-ES  
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)  
Gecko/20100101 Firefox/54.0  
PSU-Http-Method: POST  
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc  
PSU-GEO-Location: GEO:12.526347;54.649862  
TPP-Redirect-Preferred: false  
Date: Sun, 26 Sep 2017 15:02:37 GMT  
{  
  "access": {  
    "balances": [],  
    "transactions": []  
  },  
  "recurringIndicator": true,  
  "validUntil": "2018-05-17",  
  "frequencyPerDay": 4  
}
```

Example of the response in the case of SCA via redirect with an implicitly generated sub-resource authorisation

HTTP/1.1 201 Created

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

ASPSP-SCA-Approach: REDIRECT

Date: Sun, 26 Sep 2017 15:02:43 GMT

Location: </v1/consents/123-asdf-456>

Content-Type: application/json

```
{
  "consentStatus": "received",
  "consentId": "123-asdf-456",
  "_links": {
    "scaRedirect": {
      "href": "https://hub.example.es/authorize "
    },
    "self": {
      "href": "/v1/consents/123-asdf-456",
    },
    "status": {
      "href": "/v1/consents/123-asdf-456/status"
    },
    "scaStatus": {
      "href": "/v1/consents/123-asdf-456/authorisations/123auth456"
    }
  }
}
```

Example of response in the case of decoupled SCA

HTTP/1.1 201 Created

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

ASPSP-SCA-Approach: DECOUPLED

Date: Sun, 26 Sep 2017 15:02:43 GMT

Location: </v1/consents/123-asdf-456>

Content-Type: application/json

```
{
```

PSD2 - TPP Technical Design

```
"consentStatus": "received",
"consentId": "123-asdf-456",
"_links": {
  "self": {
    "href": "/v1/consents/123-asdf-456",
    "status": {
      "href": "/v1/consents/123-asdf-456/status"
    }
  },
  "psuMessage": "Please use your XXX Bank app to authorise consent"
}
```

3.2.3 Get consent status

This service allows TPP to know the status of a consent request initiated previously.

3.2.3.1 Request

Endpoint

GET {provider}/{aspsp}/v1/consents/{consent-id}/status

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
consentId	Identifier of the resource that references the consent. Sent previously as a response to a request message for consent from the TPP to the HUB.	String	MAN	^.{1,36}\$ E.g.123-qwerty-456

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $^{[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	$^{[0-9]\{1,3\}.[0-9]\{1,3\}.[0-9]\{1,3\}.[0-9]\{1,3\}}\$$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	$^{\\d\{1,5\}}\$$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and	String	OPT	$^{.\{1,50\}}\$$ E.g. PSU-Accept: application/json

PSD2 - TPP Technical Design

	TPP, if available.			
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: GET
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7

PSD2 - TPP Technical Design

PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\\d]*.[\\d]* [;][\\d]*.[\\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25 .345963
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA- 256=NzdmZjA4YjY 5M2M2NDYyMmVjO WFmMGNmYTziNT U3MjVmNDI4NTRIM zJkYzE3ZmNmMDE 3ZGFmMjhhNTc5OT U3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwI BAGIIzZzZvBQlt0Uc wDQYJ.....KoZI hvcNAQELBQAwSTE LMAkGA1UEBhMCMV VMxEzARBgNVBA

Body

No additional data are sent.

3.2.3.2 Response

This message is returned by the HUB to the TPP as a response to the request message for the consent status.

Header

PSD2 - TPP Technical Design

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Man.	Format
consentStatus	Consent authentication status. See values defined in 6.5 Consent status	String	MAN	E.g. "consentStatus": "valid"
psuMessage	Text to show to the PSU	String	OPT	$^{\{1,512\}}\$$ E.g. "psuMessage": "Information for PSU"
tppMessages	Message for the TPP	List<TppMessage>	OPT	E.g. "tppMessages": [...]

3.2.3.3 Examples

Example of request

GET <https://www.hub.com/aspsp-name/v1/consents/123asdf456/status>

Accept: application/json

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSD2 - TPP Technical Design

```
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: GET
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
Date: Sun, 26 Sep 2017 15:02:48 GMT
```

Example of response

```
HTTP/1.1 200 Ok
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:50 GMT
Content-Type: application/json
{
  "consentStatus": "valid"
}
```

3.2.4 Get consent

3.2.4.1 Request

This message is sent by the TPP to the HUB as a request to recover the information of a previously created consent.

Endpoint

GET {provider}/{aspsp}/v1/consents/{consentId}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
consentId	Identifier of the resource that references the consent. Sent previously as a response to a request message for consent from	String	MAN	^.{1,36}\$ E.g. 7890-asdf-4321

PSD2 - TPP Technical Design

	the TPP to the HUB.			
--	---------------------	--	--	--

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $^{[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicM WpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	$^{[0-9]\{1,3\}.[0-9]\{1,3\}.[0-9]\{1,3\}.[0-9]\{1,3\}}\$$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	$^{\\d\{1,5\}}\$$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP	String	OPT	$^{.\{1,50\}}\$$ E.g. PSU-Accept:

PSD2 - TPP Technical Design

	request Accept header fields between PSU and TPP, if available.			application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: GET
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-

PSD2 - TPP Technical Design

	device.			d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\\d]*.[\\d]*[;][\\d]*.[\\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.345963
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQlt0UcwDQYJ.....KoZIHvcNAQELBQAwwSTELMAKGA1UEBhMCMVVMxEzARBgNVBA

Body

No additional data are sent.

3.2.4.2 Response

This message is returned by the HUB to the TPP as a response to the message requesting recovery of the consent information.

Header

PSD2 - TPP Technical Design

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $^{\wedge}[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Man.	Format
access	Accesses requested to the services. Only the sub-attributes with "accounts", "balances" and "transactions" tags are accepted. In addition, the ASPSP may support the attributes "availableAccounts", "availableAccountsWithBalances" or "allPsd2" with the value "allAccounts"	AccountAccess	MAN	E.g. "access": {...}
recurringIndicator	Possible values: <ul style="list-style-type: none"> • true: recurring access to the account. • false: once-only access. 	Boolean	MAN	E.g. "recurringIndicator": true
validUntil	Date until which the consent requests access. The following value should be used to create consent with the maximum possible access time: 9999-12-31 When consent is recovered, the	String	MAN	ISODate E.g. "validUntil": "2018-05-17"

PSD2 - TPP Technical Design

	maximum possible date will be adjusted.			
frequencyPerDay	Indicates the frequency of access to the account every day. 1 if it is one-time-only access.	Integer	MAN	E.g. "frequencyPerDay":4
lastActionDate	Date of the last modification made to the consent.	String	MAN	ISODate E.g. "lastActionDate":"2018-01-01"
consentStatus	Consent authentication status. Values defined in annexes.	String	MAN	E.g. "consentStatus":"valid"
psuMessage	Text to show to the PSU	String	OPT	^.{1,512}\$ E.g. "psuMessage":"Information for PSU"
tppMessages	Message for the TPP	List<TppMessage>	OPT	E.g. "tppMessages":[...]

3.2.4.3 Examples

Example of request

```
GET https://www.hub.com/aspsp-name/v1/consents/7890-asdf-4321/
Accept: application/json
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA
PSU-IP-Address: 192.168.8.16
PSU-IP-Port: 443
PSU-Accept: application/json
PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: GET
```

PSD2 - TPP Technical Design

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSU-GEO-Location: GEO:12.526347;54.649862

Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of response to consent with dedicated accounts

HTTP/1.1 200 Ok

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Date: Sun, 26 Sep 2017 15:02:50 GMT

Content-Type: application/json

```
{
  "access": {
    "balances": [
      {
        "iban": "ES11111111111111111111111111111111"
      },
      {
        "iban": "ES22222222222222222222222222222222",
        "currency": "USD"
      },
      {
        "iban": "ES33333333333333333333333333333333"
      }
    ],
    "transactions": [
      {
        "iban": "ES11111111111111111111111111111111"
      }
    ]
  },
  "recurringIndicator": true,
  "validUntil": "2018-05-17",
  "frequencyPerDay": 4,
  "lastActionDate": "2018-01-17",
  "consentStatus": "valid"
}
```

Example of response to consent with global availableAccounts

HTTP/1.1 200 Ok

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

PSD2 - TPP Technical Design

Date: Sun, 26 Sep 2017 15:02:50 GMT

Content-Type: application/json

```
{
  "access": {
    "availableAccounts": "allAccounts"
  },
  "recurringIndicator": true,
  "validUntil": "2018-05-17",
  "frequencyPerDay": 4,
  "lastActionDate": "2018-01-17",
  "consentStatus": "valid"
}
```

3.2.5 Remove consent

3.2.5.1 Request

This request may be sent by a TPP to the HUB to request the removal of a previously created consent.

Endpoint

DELETE {provider}/{aspsp}/v1/consents/{consentId}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
consentId	Identifier of the resource that references the consent. Sent previously as a response to a request message for consent from the TPP to the HUB.	String	MAN	^.{1,36}\$ E.g. 7890-asdf-4321

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $^{\wedge}[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicM WpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	$^{\wedge}[0-9]\{1,3\}.\{0-9\}\{1,3\}.\{0-9\}\{1,3\}.\{0-9\}\{1,3\}\$$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	$^{\wedge}\{1,5\}\$$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	$^{\wedge}.\{1,50\}\$$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	$^{\wedge}.\{1,50\}\$$ E.g. PSU-Accept-Charset: utf-8

PSD2 - TPP Technical Design

PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: DELETE
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\\d]*.[\\d]*[;][\\d]*.[\\d]*\$ E.g.

PSD2 - TPP Technical Design

				PSU-Geo-Location: GEO:90.023856;25.3 45963
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQlt0UcwDQYJ.....KoZIhvcNAQELBQAwSTELMAkGA1UEBhMCVVMxEzARBgNVBA

Body

No additional data are sent.

3.2.5.2 Response

This message is sent by the HUB to TPP as a response to the request to remove the consent.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

PSD2 - TPP Technical Design

	by the initiating party.			E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
--	--------------------------	--	--	--

Body

No additional fields are specified.

3.2.5.3 Examples

Example of request

```
DELETE https://www.hub.com/aspsp-name/v1/consents/7890-asdf-4321
Accept: application/json
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA
PSU-IP-Address: 192.168.8.16
PSU-IP-Port: 443
PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: DELETE
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
Date: Sun, 26 Sep 2017 15:02:48 GMT
```

Example of response

```
HTTP/1.1 204 Ok
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:50 GMT
```

3.2.6 Multilevel SCA to establish consent

In the case of the SCA flow by redirection, the TPP may redirect to PSU, which initiates the transaction to the scaRedirect link for applying SCA.

In the case of SCA decoupled flow, the TPP will receive in the psuMessage field the message it must show to the PSU and direct to the PSU's bank app.

In addition, the ASPSP will return a message in the `psuMessage` field to indicate to the PSU that the transaction requires SCA by more users.

3.3 AIS: Account data reading service

3.3.1 Account list reading

This service allows a list of PSU accounts to be obtained, including the account balances if requested and the consent includes it.

This request is used both for the list of available accounts and the list of account details, depending on the consent used in the request.

As a requirement, it is assumed that the PSU has given its consent for this access and it has been stored by the ASPSP.

Operation of the service according to the type of access indicated in the consent:

Type of access	Description
availableAccounts	<p>This type of access is associated with once-only consents. If the consent associated with the request has this type of access, it will be a once-only consent and may be obtained:</p> <ul style="list-style-type: none"> List of all the available PSU accounts. <p>The following may not be obtained:</p> <ul style="list-style-type: none"> Account balances (unless supported by the ASPSP) Links to the endpoint of balances or transactions
availableAccountsWithBalances	<p>This type of access is associated with once-only consents. If the consent associated with the request has this type of access, it will be a once-only consent and may be obtained:</p> <ul style="list-style-type: none"> List of all the available PSU accounts. Account balances (unless supported by the ASPSP) <p>The following may not be obtained:</p> <ul style="list-style-type: none"> Links to the endpoint of balances or transactions
account	<p>If the consent associated with the request has this type of access, the accounts included in the consent with the "account" type of access may be listed.</p>
balances	<p>If the consent associated with the request has this type of access, the accounts included in the consent with the "balances" type of access may be listed and their balances may be obtained if supported by the ASPSP.</p>
transactions	<p>If the consent has accounts with this type of access, these</p>

PSD2 - TPP Technical Design

	accounts may be listed with the "account" access type. This type of access does not imply a "balances" type of access.
allPsd2	If the consent associated with the request has this type of access, the accounts included in the consent may be listed and their balances may be obtained. Note: allPsd2 grants the three types of access.

3.3.1.1 Request

Endpoint

GET {provider}/{aspsp}/v1/accounts{query-parameters}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name

Query parameters

Field	Description	Type	Man.	Format
withBalance	If it is included, this function includes the balances. This request will be rejected if access to balances does not include consent or the ASPSP does not support this parameter.	Boolean	OPT	E.g. true

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

PSD2 - TPP Technical Design

				E.g. X-Request-ID: 1b3ab8e8-0fd5- 43d2-946e- d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsic MWpAA
Consent-ID	Identification of the consent resource	String	MAN	^.{1,36}\$ E.g. Consent-ID: 7890-asdf-4321
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	COND	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip

PSD2 - TPP Technical Design

PSU-Accept-Language	See above	String	OPT	$\wedge.\{1,50\}\$$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: GET
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.	String	OPT	UUID $\wedge[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 $\wedge\text{GEO}:[\backslash\text{d}]*.[\backslash\text{d}]*[;][\backslash\text{d}]*.[\backslash\text{d}]*\$$ E.g. PSU-Geo-Location: GEO:90.023856;25.345963

PSD2 - TPP Technical Design

Digest	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	MAN	$\wedge.\{1,100\}\$$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	$\wedge.\{1,5000\}\$$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQIt0UcwDQYJ.....KoZIHvcNAQELBQAwSTE LMAkGA1UEBhMCMCVVMxEzARBgNVBA

Body

Data are not sent in the body in this request.

3.3.1.2 Response

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined	String	MAN	UUID $\wedge[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$

PSD2 - TPP Technical Design

	by the initiating party.			E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
--	--------------------------	--	--	--

Body

Field	Description	Type	Mand.	Format
accounts	List of available accounts.	List<AccountDetails>	MAN	E.g. "accounts": []
psuMessage	Text to show to the PSU.	String	OPT	^.{1,512}\$ E.g. "psuMessage": "Information for PSU"
tppMessages	Message for the TPP.	List<TppMessage>	OPT	E.g. "tppMessages": [...]

3.3.1.3 Examples

Example of request to obtain list of accessible PSU accounts

```
GET https://www.hub.com/aspsp-name/v1/accounts
Content-Encoding: gzip
Content-Type: application/json
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA
Consent-ID: 7890-asdf-4321
PSU-IP-Address: 192.168.8.16
PSU-IP-Port: 443
PSU-Accept: application/json
PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: GET
```

PSD2 - TPP Technical Design

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of the response obtaining list of accessible PSU accounts

Response where the consent has been given for two different IBAN numbers.

```
HTTP/1.1 200 Ok
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:50 GMT
Content-Type: application/json
{
  "accounts": [
    {
      "resourceId": "3dc3d5b3-7023-4848-9853-f5400a64e80f",
      "iban": "ES11111111111111111111111111111111",
      "currency": "EUR",
      "product": "Girokonto",
      "cashAccountType": "CACC",
      "name": "Main Account",
      "_links": {
        "balances": {
          "href": "/v1/accounts/3dc3d5b3-7023-4848-9853-f5400a64e80f/balances"
        },
        "transactions": {
          "href": "/v1/accounts/3dc3d5b3-7023-4848-9853-f5400a64e80f/transactions"
        }
      }
    },
    {
      "resourceId": "3dc3d5b3-7023-4848-9853-f5400a64e81g",
      "iban": "ES22222222222222222222222222222222",
      "currency": "USD",
      "cashAccountType": "CACC",
```

PSD2 - TPP Technical Design

```
"name": "US Dollar Account",
"_links": {
  "balances": {
    "href": "/v1/accounts/3dc3d5b3-7023-4848-9853-
f5400a64e81g/balances"
  }
}
]
```

3.3.2 Reading account details

This service allows the account details to be read with the balances if required.

As a requirement, it is assumed that the PSU has given its consent for this access and it has been stored by the ASPSP.

Operation of the service according to the type of access indicated in the consent:

Type of access	Description
availableAccounts	This type of access does not allow consumption of this service.
availableAccountsWithBalances	This type of access does not allow consumption of this service.
account	If the consent associated with the request has this type of access, the account may be queried.
balances	If the consent associated with the request has this type of access, the account may be queried and its balances may be obtained if the ASPSP supports it.
transactions	If the consent has accounts with this type of access, this account may be queried with the "account" access type. This type of access does not imply a "balances" type of access.
allPsd2	If the consent associated with the request has this type of access, the account may be queried and its balances may be obtained. Note: allPsd2 grants the three types of access.

3.3.2.1 Request

Endpoint

GET {provider}/{aspsp}/v1/accounts/{account-id}{query-parameters}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
account-id	Identifier of the account assigned by the ASPSP	String	MAN	^.{1,100}\$ E.g. account-id=a1q5w

Query parameters

Field	Description	Type	Man.	Format
withBalance	If it is included, this function includes the balances. This request will be rejected if access to balances does not include consent or the ASPSP does not support this parameter.	Boolean	OPT	E.g. true

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained	String	MAN	E.g.

PSD2 - TPP Technical Design

	in a prior authentication on OAuth2.			Authorisation: Bearer 2YotnFZFEjr1zCsic MWpAA
Consent-ID	Identification of the consent resource	String	MAN	^.{1,36}\$ E.g. Consent-ID: 7890-asdf-4321
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	COND	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U;

PSD2 - TPP Technical Design

				Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none">• GET• POST• PUT• PATCH• DELETE	String	OPT	E.g. PSU-Http-Method: GET
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\d]*.[\d]*[;][\d]*.[\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.345963
Digest	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OT

PSD2 - TPP Technical Design

				U3OQ==
Signature	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwI BAgIIzZvBQIt0Uc wDQYJ.....KoZI hvcNAQELBQAwSTE LMAkGA1UEBhMCMV VMxEzARBgNVBA

Body

Data are not sent in the body in this request.

3.3.2.2 Response

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Mand.	Format
account	Detailed information on the account	Account Details	MAN	E.g. "account": {...}
psuMessage	Text to show to the	String	OPT	^.{1,512}\$

PSD2 - TPP Technical Design

	PSU			E.g. "psuMessage": "Information for PSU"
tppMessages	Message for the TPP	List<Tpp Message >	OPT	E.g. "tppMessages": [...]

3.3.2.3 Examples

Example of request

GET <https://www.hub.com/aspsp-name/v1/accounts/3dc3d5b3-7023-4848-9853-f5400a64e80f>

Content-Encoding: gzip

Content-Type: application/json

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

Consent-ID: 7890-asdf-4321

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSU-Http-Method: GET

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSU-GEO-Location: GEO:12.526347;54.649862

Date: Sun, 26 Sep 2017 15:02:48 GMT

Example when the account only has one currency

HTTP/1.1 200 Ok

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Date: Sun, 26 Sep 2017 15:02:50 GMT

Content-Type: application/json

{

PSD2 - TPP Technical Design

```
"account": {
  "resourceId": "3dc3d5b3-7023-4848-9853-f5400a64e80f",
  "iban": "ES111111111111111111111111",
  "currency": "EUR",
  "ownerName": "Heike Mustermann",
  "product": "Girokonto",
  "cashAccountType": "CACC",
  "name": "Main Account",
  "_links": {
    "balances": {
      "href": "/v1/accounts/3dc3d5b3-7023-4848-9853-f5400a64e80f/balances"
    },
    "transactions": {
      "href": "/v1/accounts/3dc3d5b3-7023-4848-9853-f5400a64e80f/transactions"
    }
  }
}
}
```

Example of multi-currency account response

```
HTTP/1.1 200 Ok
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:50 GMT
Content-Type: application/json
{
```

```
  "account": {
    "resourceId": "3dc3d5b3-7023-4848-9853-f5400a64e81g",
    "iban": "ES222222222222222222222222",
    "currency": "XXX",
    "ownerName": "Heike Mustermann",
    "product": "Multicurrency Account",
    "cashAccountType": "CACC",
    "name": "Aggregation Account",
    "_links": {
```

PSD2 - TPP Technical Design

```
    "balances": {
      "href": "/v1/accounts/3dc3d5b3-7023-4848-9853-
f5400a64e81g/balances"
    },
    "transactions": {
      "href": "/v1/accounts/3dc3d5b3-7023-4848-9853-
f5400a64e81g/transactions"
    }
  }
}
```

3.3.3 Reading balances

This service allows balances of an account determined by its identifier to be obtained.

As a requirement, it is assumed that the PSU has given its consent for this access and it has been stored by the ASPSP.

Operation of the service according to the type of access indicated in the consent:

Type of access	Description
availableAccounts	This type of access does not allow consumption of this service.
availableAccountsWithBalances	This type of access does not allow consumption of this service.
account	This type of access does not allow consumption of this service.
balances	If the consent associated with the request has this type of access, the account balances may be queried.
transactions	This type of access does not allow consumption of this service.
allPsd2	If the consent associated with the request has this type of access, the account balances may be queried. Note: allPsd2 grants the three types of access.

3.3.3.1 Request

Endpoint

GET {provider}/{aspsp}/v1/accounts/{account-id}/balances

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
account-id	Identifier of the account that will be used in the data reading. Obtained previously in the reading of the account list. Must be valid at least while the consent lasts. This id may be tokenised.	String	MAN	^{1,100}\$ E.g. account-id=a1q5w

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer

PSD2 - TPP Technical Design

				2YotnFZFEjr1zCsic MWpAA
Consent-ID	Identification of the consent resource	String	MAN	^.{1,36}\$ E.g. Consent-ID: 7890-asdf-4321
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	COND	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5)

PSD2 - TPP Technical Design

				Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: GET
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\\d]*.[\\d]*[;][\\d]*.[\\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.345963
Digest	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYtZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	Is contained if and only	String	MAN	See annexes

PSD2 - TPP Technical Design

	if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.			
TPP-Signature-Certificate	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwI BAgIIzZzZvBQIt0Uc wDQYJ.....KoZI hvcNAQELBQAwSTE LMAkGA1UEBhMVCV VMxEzARBgNVBA

Body

The data are not sent in the body in this request.

3.3.3.2 Response

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Mand.	Format
account	Identifier of the addressed account. Remark for Future: It is recommended to use this data element. The	AccountReference	OPT	E.g. "account": {...}

PSD2 - TPP Technical Design

	condition might change to "mandatory" in a next version of the specification.			
balances	A list of balances regarding this account, e.g. the current balance, the last booked balance.	List<Balance >	MAN	E.g. "balances": {...}
psuMessage	Text to show to the PSU.	String	OPT	^.{1,512}\$ E.g. "psuMessage": "Information for PSU"
tppMessages	Message for the TPP.	List<TppMessage>	OPT	E.g. "tppMessages": [...]

3.3.3.3 Examples

Example of request

GET <https://www.hub.com/aspsp-name/accounts/3dc3d5b3-7023-4848-9853-f5400a64e81g/balances>

Accept: application/json

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

Consent-ID: 7890-asdf-4321

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSU-Http-Method: GET

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSU-GEO-Location: GEO:12.526347;54.649862

PSD2 - TPP Technical Design

Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of response

HTTP/1.1 200 Ok

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Date: Sun, 26 Sep 2017 15:02:50 GMT

Content-Type: application/json

```
{
  "account": {
    "iban": "ES1111111111111111111111"
  },
  "balances": [
    {
      "balanceType": "closingBooked",
      "balanceAmount": {
        "currency": "EUR",
        "amount": "500.00"
      },
      "referenceDate": "2017-10-25"
    },
    {
      "balanceType": "expected",
      "balanceAmount": {
        "currency": "EUR",
        "amount": "900.00"
      },
      "lastChangeDateTime": "2017-10-25T15:30:35.035Z"
    }
  ]
}
```

3.3.4 Reading of transactions

This service allows transactions to be obtained of an account determined by its identifier.

PSD2 - TPP Technical Design

As a requirement, it is assumed that the PSU has given its consent for this access and it has been stored by the ASPSP.

Operation of the service according to the type of access indicated in the consent:

Type of access	Description
availableAccounts	This type of access does not allow consumption of this service.
availableAccountsWithBalances	This type of access does not allow consumption of this service.
account	This type of access does not allow consumption of this service.
balances	If the consent associated with the request has this type of access, the balances may be requested if the ASPSP supports it.
transactions	If the consent associated with the request has this type of access, the account activity may be queried.
allPsd2	If the consent associated with the request has this type of access, the account balances may be queried. Note: allPsd2 grants the three types of access.

3.3.4.1 Request

Endpoint

GET {provider}/{aspsp}/v1/accounts/{account-id}/transactions{query-parameters}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
account-id	Identifier of the account that will be used in the	String	MAN	^.{1,100}\$ E.g. account-id=a1q5w

PSD2 - TPP Technical Design

	<p>data reading. Obtained previously in the reading of the account list. Must be valid at least while the consent lasts. This id may be tokenised.</p>			
--	--	--	--	--

Query parameters

Field	Description	Type	Man.	Format
dateFrom	Start date of query. It is included if the "deltaList" is not included.	String	COND	ISODate E.g. dateFrom=2017-10-25
dateTo	End date of query. Its default value is the current date, unless otherwise indicated.	String	OPT	ISODate E.g. dateTo=2017-11-05
entryReferenceFrom	If it is indicated, it will give us the results from the time of the call with entryReferenceFrom before that given. If it is contained, the dateFrom and dateTo attributes are ignored.	String	OPT	E.g. entryReferenceFrom=1234-asdf-567
bookingStatus	Status of the returned transactions. The status codes permitted are "booked", "pending" and "both". Those mandatory for the ASPSPs are "booked".	String	MAN	E.g. bookingStatus=booked
deltaList	Indicates that the AISP is in favour of obtaining all the transactions after the last access to the report for this PSU and account. This indicator could be rejected by the ASPSP if this function is not compatible.	Boolean	OPT	E.g. deltaList=false

PSD2 - TPP Technical Design

withBalance	<p>If it is included, this function includes the balances.</p> <p>This request will be rejected if access to balances does not include consent or the ASPSP does not support this parameter.</p>	Boolean	OPT	E.g. true
--------------------	--	---------	-----	-----------

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	<p>UUID</p> <p>^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$</p> <p>E.g.</p> <p>X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	<p>E.g.</p> <p>Authorisation: Bearer 2YotnFZFEjr1zCsic MWpAA</p>
Consent-ID	Identification of the consent resource	String	MAN	<p>^.{1,36}\$</p> <p>E.g. Consent-ID: 7890-asdf-4321</p>
Accept	Response format supported. Supported values: application/json	String	OPT	<p>^.{1,50}\$</p> <p>E.g. Accept: application/json</p>
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP.	String	COND	<p>^[0-9]{1,3}.[0-9]{1,3}.[0-9]{1,3}.[0-9]{1,3}\$</p> <p>E.g.</p> <p>PSU-IP-Address:</p>

PSD2 - TPP Technical Design

	If not available, the TPP shall use the IP Address used by the TPP when submitting this request.			192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH 	String	OPT	E.g. PSU-Http-Method: GET

PSD2 - TPP Technical Design

	<ul style="list-style-type: none"> DELETE 			
PSU-Device-ID	<p>UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>	String	OPT	<p>UUID</p> <p>$^{\wedge}[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\\$</p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	OPT	<p>RFC 2426</p> <p>$^{\wedge}\text{GEO}:[\backslash\text{d}]*\.[\backslash\text{d}]*[;][\backslash\text{d}]*\.[\backslash\text{d}]*\\$</p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
Digest	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	MAN	<p>$^{\wedge}\{1,100\}\\$</p> <p>E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==</p>
Signature	<p>Is contained if and only if the "Signature" element is contained in the header of the request.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>See annexes</p>
TPP-Signature-Certificate	<p>A signature of the request by the TPP on application level.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>$^{\wedge}\{1,5000\}\\$</p> <p>E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQltOUcwDQYJ.....KoZI</p>

				hvcNAQELBQAwSTE LMAkGA1UEBhMCMCV VMxEzARBgNVBA
--	--	--	--	--

Body

Data are not sent in the body in this request.

3.3.4.2 Response

Header

Field	Description	Type	Man.	Format
Content-Type	Possible values: application/json	String	MAN	E.g. Content-Type: application/json
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Man.	Format
account	Identifier of the addressed account. Remark for Future: It is recommended to use this data element. The condition might change to "mandatory" in a next version of the specification.	AccountReference	OPT	E.g. "account": {...}
transactions	JSON based account report. This account report contains transactions	AccountReport	OPT	E.g. "transactions": {...}

PSD2 - TPP Technical Design

	resulting from the query parameters.			
balances	A list of balances regarding this account, which might be restricted to the current balance.	List<Balance >	OPT	E.g. "balances": [...]
_links	List of hyperlinks to be recognised by the TPP. Types supported in this response: " download ": Download link for the query data when the data returned are of a substantial weight. Only for camt-data.	Links	OPT	E.g. "_links": {...}
psuMessage	Text to show to the PSU	String	OPT	^.{1,512}\$ E.g. "psuMessage": "Information for the PSU"
tppMessages	Message for the TPP	List<TppMessage>	OPT	E.g. "tppMessages": [...]

3.3.4.3 Examples

Example of a search request sending search criteria by dateTo and dateFrom

GET

<https://www.hub.com/aspsp-name/v1/accounts/qwer3456tzui7890/transactions?dateFrom=2017-10-25&dateTo=2017-11-05&bookingStatus=both>

Accept: application/json

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMwPAA

Consent-ID: 7890-asdf-4321

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSD2 - TPP Technical Design

PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: GET
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of a search request sending entryReferenceFrom search criteria

GET <https://www.hub.com/aspsp-name/v1/accounts/qwer3456tzui7890/transactions?entryReferenceFrom=1234-asd-4564700&bookingStatus=both>
Accept: application/json
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA
Consent-ID: 7890-asdf-4321
PSU-IP-Address: 192.168.8.16
PSU-IP-Port: 443
PSU-Accept: application/json
PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: GET
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of response with pagination

HTTP/1.1 200 Ok
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:50 GMT
Content-Type: application/json

PSD2 - TPP Technical Design

```
{
  "account": {
    "iban": "ES1111111111111111111111"
  },
  "transactions": {
    "booked": [
      {
        "transactionId": "1234567",
        "creditorName": "John Miles",
        "creditorAccount": {
          "iban": "ES1111111111111111111111"
        },
        "transactionAmount": {
          "currency": "EUR",
          "amount": "256.67"
        },
        "bookingDate": "2017-10-25",
        "valueDate": "2017-10-26",
        "remittanceInformationUnstructured": "Example for
Remittance Information"
      },
      {
        "transactionId": "1234568",
        "debtorName": "Paul Simpson",
        "debtorAccount": {
          "iban": "NL354543123456900"
        },
        "transactionAmount": {
          "currency": "EUR",
          "content": "343.01"
        },
        "bookingDate": "2017-10-25",
        "valueDate": "2017-10-26",
        "remittanceInformationUnstructured": "Another example
for Remittance Information"
      }
    ]
  }
}
```

PSD2 - TPP Technical Design

```
],
"pending": [
{
  "transactionId": "123456789",
  "creditorName": "Claude Renault",
  "creditorAccount": {
    "iban": "NL354543123456900"
  },
  "transactionAmount": {
    "currency": "EUR",
    "amount": "-100.03"
  },
  "valueDate": "2017-10-26",
  "remittanceInformationUnstructured": "Another example
for Remittance Information"
}
],
"_links": {
  "account": {
    "href": "/v1/accounts/qwer3456tzui7890"
  },
  "first": {
    "href": "/v1/accounts/
qwer3456tzui7890/transactions?page[number]=1&page[siz
e]=15"
  },
  "previous": {
    "href": "/v1/accounts/
qwer3456tzui7890/transactions?page[number]=2&page[siz
e]=15"
  },
  "next": {
    "href": "/v1/accounts/
qwer3456tzui7890/transactions?page[number]=4&page[siz
e]=15"
  },
  "last": {
```

PSD2 - TPP Technical Design

```
        "href": "/v1/accounts/
qwer3456tzui7890/transactions?page[number]=10&page[si
ze]=15"
    }
}
}
```

Example of response with error

```
{
  "tppMessages": [{
    "category": "ERROR",
    "code": " ACCESS_EXCEEDED "
  }
]
```

3.4 FCS: Establish consent for the fund confirmation service

3.4.1 Fund confirmation consent

Using this service, a TPP can report a confirmation consent for ASPSP funds on the specified account.

Unlike the request to establish information consent on the account, this consent does not have secondary effects on other existing ones.

E.g. does not invalidate prior consent.

3.4.1.1 Request

Endpoint

POST {provider}/{aspsp}/v2/consents/confirmation-of-funds

Path

Field	Description	Type	Man.	Format
-------	-------------	------	------	--------

PSD2 - TPP Technical Design

provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $^{\wedge}[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpA A
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	$^{\wedge}[0-9]\{1,3\}.\{0-9\}\{1,3\}.\{0-9\}\{1,3\}.\{0-9\}\{1,3\}\$$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding	String	OPT	$^{\wedge}\{1,5\}\$$ E.g. PSU-IP-Port: 443

PSD2 - TPP Technical Design

	HTTP request IP Port field between PSU and TPP, if available.			
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	$\wedge.\{1,50\}\$$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	$\wedge.\{1,50\}\$$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	$\wedge.\{1,50\}\$$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	$\wedge.\{1,50\}\$$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: POST
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available.	String	OPT	UUID $\wedge[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$

PSD2 - TPP Technical Design

	<p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>			<p>E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	OPT	<p>RFC 2426 ^GEO:[\d]*.[\d]*[;][\d]*.[\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.345963</p>
TPP-Redirect-Preferred	<p>If it equals "true", the TPP prefers a redirect over an embedded SCA approach.</p> <p>If it equals "false", the TPP prefers not to be redirected for SCA. The ASPSP will then choose between the Embedded or the Decoupled SCA approach, depending on the choice of the SCA procedure by the TPP/PSU.</p> <p>If the parameter is not used, the ASPSP will choose the SCA approach to be applied depending on the SCA method chosen by the TPP/PSU.</p> <p>EMBEDDED NOT SUPPORTED IN THIS VERSION</p>	Boolean	OPT	<p>E.g. TPP-Redirect-Preferred: true</p>
TPP-Redirect-	<p>URI of the TPP, where the transaction flow shall be redirected to</p>	String	COND	<p>^.{1,250}\$ E.g. TPP-Redirect-</p>

PSD2 - TPP Technical Design

<p>URI</p>	<p>after a Redirect. Mandated for the Redirect SCA Approach, specifically when TPP-Redirect-Preferred equals "true".</p> <p>It is recommended to always use this header field.</p> <p>Remark for Future: This field might be changed to mandatory in the next version of the specification.</p>			<p>URI:"https://tpp.example.es/cb"</p>
<p>TPP-Nok-Redirect-URI</p>	<p>If this URI is contained, the TPP is asking to redirect the transaction flow to this address instead of the TPP-Redirect-URI in case of a negative result of the redirect SCA method. This might be ignored by the ASPSP.</p>	<p>String</p>	<p>OPT</p>	<p>^.{12,50}\$</p> <p>E.g. TPP-Nok-Redirect-URI:"https://tpp.example.es/cb/nok"</p>
<p>TPP-Explicit-Authorisation-Preferred</p>	<p>If it equals "true", the TPP prefers to start the authorisation process separately. This preference might be ignored by the ASPSP, if a signing basket is not supported as functionality.</p> <p>If it equals "false" or if the parameter is not used, there is no preference of the TPP. This especially indicates that the TPP assumes a direct authorisation of the transaction in the next step.</p>	<p>Boolean</p>	<p>OPT</p>	<p>E.g. TPP-Explicit-Authorisation-Preferred: false</p>

PSD2 - TPP Technical Design

	Note: the ASPSP may not take it into account if it does not support it.			
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRI MzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgzCCBmugAwIBAgIIZzZvBQlt0UcwDQYJ.....KoZIhvcNAQELBQAwS TELMakGA1UEBhMCVVM xEzARBgNVBA

Body

Field	Description	Type	Man.	Format
account	Account, where the confirmation of funds service is aimed to be submitted to.	Account Reference	MAN	E.g. "access": {...}
cardNumber	Card Number of the card issued by the PIISP. Should be delivered if available.	String	OPT	^.{1,35}\$
cardExpiry Date	Expiry date of the card issued by the PIISP	String	OPT	ISODate E.g. "validUntil": "2018-05-17"
cardInformation	Additional explanation for the card product.	String	OPT	^.{1,140}\$

registrationInformation	Additional information about the registration process for the PSU, e.g. a reference to the TPP / PSU contract	String	OPT	^.{1,140}\$
--------------------------------	---	--------	-----	-------------

3.4.1.2 Response

Response code

HTTP 201 response code if the resource is correctly created.

Header

Field	Description	Type	Man.	Format
Location	Contains the link to the resource generated.	String	MAN	Max512Text E.g. Location: /v2/consents/confirmation-of-funds/{consentId}
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
ASPSP-SCA-Approach	Value returned if the SCA method has been fixed. Possible values: <ul style="list-style-type: none"> EMBEDDED DECOUPLED REDIRECT <p>The SCA based on OAuth will be taken as REDIRECT.</p>	String	COND	E.g. ASPSP-SCA-Approach: REDIRECT

Body

Field	Description	Type	Man.	Format
-------	-------------	------	------	--------

PSD2 - TPP Technical Design

consentStatus	Consent authentication status. See values defined in 6.5 Consent status	String	MAN	E.g. "consentStatus": "received"
consentId	Identifier of the resource that references the consent. It must be contained if a consent was generated.	String	MAN	^{1,36}\$ E.g. "consentId": "123-QWE-456"
scaMethods	<p>This data element might be contained, if SCA is required and if the PSU has a choice between different authentication methods.</p> <p>If this data element is contained, then there is also a hyperlink of type "startAuthorisationWithAuthenticationMethodSelection" contained in the response body.</p> <p>These methods shall be presented towards the PSU for selection by the TPP.</p> <p>Note: Only if ASPSP supports selection of the SCA method</p>	List<AuthenticationObject>	COND	E.g. "scaMethods": [...]
_links	<p>A list of hyperlinks to be recognised by the TPP.</p> <p>Type of links admitted in this response:</p> <ul style="list-style-type: none"> • scaRedirect: In case of an SCA Redirect Approach, the ASPSP is transmitting the link to which to redirect the PSU browser. • startAuthorisation: In case, where an explicit start of the transaction 	Links	MAN	E.g. "_links": {...}

PSD2 - TPP Technical Design

	<p>authorisation is needed, but no more data needs to be updated (no authentication method to be selected, no PSU identification nor PSU authentication data to be uploaded).</p> <ul style="list-style-type: none"> • startAuthorisationWithAuthenticationMethodSelection: The link to the authorisation endpoint, where the authorisation sub-resource has to be generated while selecting the authentication method. This link is contained under exactly the same conditions as the data element "scaMethods" • self: link to the resource created by this request. • status: The link to retrieve the transaction status • scaStatus: The link to retrieve the scaStatus of the corresponding authorisation sub-resource. This link is only contained, if an authorisation sub-resource has been 			
--	---	--	--	--

PSD2 - TPP Technical Design

	already created.			
psuMessage	Text to be displayed to the PSU	String	OPT	^.{1,512}\$ E.g. "psuMessage": "Information for the PSU"
tppMessages	Message to the TPP	List<TppMessage>	OPT	E.g. "tppMessages": [...]

3.4.1.3 Examples

Example of consent request

POST <https://www.hub.com/aspsp-name/v2/consents/confirmation-of-funds>

```
Content-Encoding: gzip
Content-Type: application/json
X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541
Authorization: Bearer 2YotnFZFEjrlzCsicMwPAA
PSU-IP-Address: 192.168.8.16
PSU-IP-Port: 443
PSU-Accept: application/json
PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: POST
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
TPP-Redirect-Preferred: true
TPP-Redirect-URI: https://www.tpp.com/cb
TPP-Nok-Redirect-URI: https://www.tpp.com/cb/nok
Date: Sun, 26 Sep 2017 15:02:37 GMT
{
  "account": {
    "iban": "ES11111111111111111111111111111111"
  },
  "cardNumber": "123456781234",
```

PSD2 - TPP Technical Design

```
    "cardExpiryDate": "2020-12-31",
    "cardInformation": "MyMerchant Loyalty Card",
    "registrationInformation": "Your contrat Number 1234 with
MyMerchant is completed with the registration with your bank."
}
```

Example of the response in the case of SCA via redirect with an implicitly generated sub-resource authorisation

HTTP/1.1 201 Created

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

ASPSP-SCA-Approach: REDIRECT

Date: Sun, 26 Sep 2017 15:02:43 GMT

Location: </v2/consents/confirmation-of-funds/123-asdf-456>

Content-Type: application/json

```
{
  "consentStatus": "received",
  "consentId": "123-asdf-456",
  "_links": {
    "scaRedirect": {
      "href": "https://hub.example.es/authorization "
    },
    "self": {
      "href": "/v2/consents/confirmation-of-funds/123-asdf-456",
    },
    "status": {
      "href": "/v2/consents/confirmation-of-funds/123-asdf-456/status"
    },
    "scaStatus": {
      "href": "/v2/consents/123-asdf-456/authorisations/confirmation-of-funds/123auth456"
    }
  }
}
```

Example of response in the case of decoupled SCA

HTTP/1.1 201 Created

PSD2 - TPP Technical Design

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

ASPSP-SCA-Approach: DECOUPLED

Date: Sun, 26 Sep 2017 15:02:43 GMT

Location: </v2/consents/confirmation-of-funds/123-asdf-456>

Content-Type: application/json

```
{
  "consentStatus": "received",
  "consentId": "123-asdf-456",
  "_links": {
    "self": {
      "href": "/v2/consents/confirmation-of-funds/123-asdf-456",
      "status": {
        "href": "/v2/consents/confirmation-of-funds/123-asdf-456/status"
      }
    }
  },
  "psuMessage": "Please use your XXX Bank app to authorise consent"
}
```

3.4.2 Get consent status

This service allows TPP to know the status of a consent request initiated previously.

3.4.2.1 Request

Endpoint

GET {provider}/{aspsp}/v2/consents/confirmation-of-funds/{consent-id}/status

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name

PSD2 - TPP Technical Design

consentId	Identifier of the resource that references the consent. Sent previously as a response to a request message for consent from the TPP.	String	MAN	^.{1,36}\$ E.g.123-qwerty-456
------------------	---	--------	-----	--------------------------------------

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	^[0-9]{1,3}.[0-9]{1,3}.[0-9]{1,3}.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of	String	OPT	^\d{1,5}\$

PSD2 - TPP Technical Design

	the corresponding HTTP request IP Port field between PSU and TPP, if available.			E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: GET
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available.	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-

PSD2 - TPP Technical Design

	UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.			fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\\d]*.[\\d]*[;][\\d]*.[\\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.345963
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYtZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIzZzVbQlt0UcwDQYJ.....KoZIHvcNAQELBQAwSTE LMAkGA1UEBhMCMCV VMxEzARBgNVBA

Body

No additional data are sent.

3.4.2.2 Response

This message is returned to the TPP as a response to the request message for the consent status.

Response code

HTTP 200 response code.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $^{\wedge}[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Man.	Format
consentStatus	Consent authentication status. See values defined in 6.5 Consent status	String	MAN	E.g. "consentStatus": "valid"
psuMessage	Text to show to the PSU	String	OPT	$^{\wedge}.\{1,512\}\$$ E.g. "psuMessage": "Information for PSU"
tppMessages	Message for the TPP	List<Tp pMessage>	OPT	E.g. "tppMessages": [...]

3.4.2.3 Examples

Example of request

PSD2 - TPP Technical Design

```
GET https://www.hub.com/aspsp-name/v2/consents/confirmation-of-funds/123asdf456/status
Accept: application/json
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA
PSU-IP-Address: 192.168.8.16
PSU-IP-Port: 443
PSU-Accept: application/json
PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: GET
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
Date: Sun, 26 Sep 2017 15:02:48 GMT
```

Example of response

```
HTTP/1.1 200 Ok
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:50 GMT
Content-Type: application/json
{
  "consentStatus": "valid"
}
```

3.4.3 Get consent

3.4.3.1 Request

This message is sent by the TPP as a request to recover the information on previously created consent for fund confirmation. Particularly useful for the TPP in cases where the consent was managed directly between the ASPSP and the PSU.

Endpoint

GET {provider}/{aspsp}/v2/consents/confirmation-of-funds/{consentId}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
consentId	Identifier of the resource that references the consent. Sent previously as a response to a request message for consent from the TPP.	String	MAN	^.{1,36}\$ E.g. 7890-asdf-4321

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP	String	OPT	^[0-9]{1,3}.[0-9]{1,3}.[0-9]{1,3}.[0-9]{1,3}\$

PSD2 - TPP Technical Design

	request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.			E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none">• GET• POST	String	OPT	E.g. PSU-Http-Method: GET

PSD2 - TPP Technical Design

	<ul style="list-style-type: none"> • PUT • PATCH • DELETE 			
PSU-Device-ID	<p>UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>	String	OPT	<p>UUID</p> <p>$^{\wedge}[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\\$</p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	OPT	<p>RFC 2426</p> <p>$^{\wedge}\text{GEO}:[\backslash\text{d}]*\text{.}[\backslash\text{d}]*[;][\backslash\text{d}]*\text{.}[\backslash\text{d}]*\text{\\$}$</p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
Digest	<p>Is contained if and only if the "Signature" element is contained in the header of the request.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>$^{\wedge}\text{.}\{1,100\}\text{\\$}$</p> <p>E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==</p>
Signature	<p>A signature of the request by the TPP on application level.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>See annexes</p>
TPP-Signature-Certificate	<p>The certificate used for signing the request, in base64 encoding.</p>	String	MAN	<p>$^{\wedge}\text{.}\{1,5000\}\text{\\$}$</p> <p>E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQlt0UcwDQYJ.....KoZI</p>

PSD2 - TPP Technical Design

				hvcNAQELBQAwSTE LMAkGA1UEBhMCMCV VMxEzARBgNVBA
--	--	--	--	--

Body

No additional data are sent.

3.4.3.2 Response

This message is returned to the TPP as a response to the message requesting recovery of the consent information.

Response code

HTTP 200 response code.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Man.	Format
account	Account, where the confirmation of funds service is aimed to be submitted to.	Account Reference	MAN	E.g. "access": {...}
cardNumber	Card Number of the card issued by the PIISP. Should be delivered if available.	String	OPT	^.{1,35}\$

PSD2 - TPP Technical Design

cardExpiry Date	Expiry date of the card issued by the PIISP	String	OPT	ISODate E.g. "validUntil":"2018-05-17"
cardInformation	Additional explanation for the card product.	String	OPT	^.{1,140}\$
registrationInformation	Additional registration information.	String	OPT	^.{1,140}\$
consentStatus	The status of the consent resource.	String	MAN	E.g. "consentStatus":"valid"
psuMessage	Text sent to TPP to be shown to the PSU.	String	OPT	^.{1,512}\$ E.g. "psuMessage":"Information for PSU"
tppMessages	Message for the TPP.	List<Tpp Message >	OPT	E.g. "tppMessages":[...]

3.4.3.3 Examples

Example of request

GET <https://www.hub.com/aspsp-name/v2/consents/confirmation-of-funds/7890-asdf-4321/>

Accept: application/json

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSU-Http-Method: GET

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSD2 - TPP Technical Design

PSU-GEO-Location: GEO:12.526347;54.649862

Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of response

HTTP/1.1 200 Ok

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Date: Sun, 26 Sep 2017 15:02:50 GMT

Content-Type: application/json

```
{
  "account": {
    "iban": "ES1111111111111111111111"
  },
  "cardNumber": "123456781234",
  "cardExpiryDate": "2020-12-31",
  "cardInformation": "MyMerchant Loyalty Card",
  "registrationInformation": "Your contrat Number 1234 with
MyMerchant is completed with the registration with your bank."
  "consentStatus": "valid"
}
```

3.4.4 Revoke consent

3.4.4.1 Request

This service allows a request for the removal of consent previously created in the ASPSP.

Endpoint

DELETE {provider}/{aspsp}/v2/consents/confirmation-of-funds/{consentId}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name

PSD2 - TPP Technical Design

consentId	Identifier of the resource that references the consent. Sent previously as a response to a request message for consent from the TPP.	String	MAN	^.{1,36}\$ E.g. 7890-asdf-4321
------------------	---	--------	-----	---------------------------------------

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port:

PSD2 - TPP Technical Design

	request IP Port field between PSU and TPP, if available.			443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: DELETE
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-

PSD2 - TPP Technical Design

	device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.			F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\d]*.[\d]* [;][\d]*.[\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.345963
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYtZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIzZzVbQlt0UcwDQYJ.....KoZIHvcNAQELBQAwSTE LMAkGA1UEBhMCMCV VMxEzARBgNVBA

Body

No additional data are sent.

3.4.4.2 Response

This message is sent to the TPP as a response to the request to remove the consent.

Response code

HTTP 204 response code for correct cancellation.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

No additional fields are specified.

3.4.4.3 Examples

Example of request

DELETE <https://www.hub.com/aspsp-name/v2/consents/confirmation-of-funds/7890-asdf-4321>

Accept: application/json

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSD2 - TPP Technical Design

```
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: DELETE
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
Date: Sun, 26 Sep 2017 15:02:48 GMT
```

Example of response

```
HTTP/1.1 204 Ok
X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:50 GMT
```

3.4.5 Multilevel SCA to establish consent

In the case of the SCA flow by redirection, the TPP may redirect to PSU, which initiates the transaction to the scaRedirect link for applying SCA.

In the case of SCA decoupled flow, the TPP will receive in the psuMessage field the message it must show to the PSU and direct to the PSU's bank app.

In addition, the ASPSP will return a message in the psuMessage field to indicate to the PSU that the transaction requires SCA by more users.

3.5 FCS: Fund Confirmation Service

3.5.1 Confirmation of funds

This type of message is used in the fund query service. The TPP sends a request to the HUB to query the funds for a given amount.

The HUB communicates with the ASPSP to ask whether it has funds or not, and after the query, returns the response to the TPP.

Rules that are applied to confirm funds in multi-currency accounts

- If no card number, but the PSU account identifier is contained: check on default account registered by customer.
- If no card number but the PSU and the account identifier with currency is contained: check the availability of funds on the corresponding sub-account.

PSD2 - TPP Technical Design

- If card number and the PSU account identifier is contained: check on sub-account addressed by card, if the addressed card is registered with one of the sub-accounts.
- If the card number is not registered for any of the sub-accounts, or if the card number is registered for a different sub-account the card number might be ignored.

3.5.1.1 Request

Endpoint

POST {provider}/{aspsp}/v1/funds-confirmations

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2. Only if the consent management has been carried out	String	COND	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA

PSD2 - TPP Technical Design

	through the API.			
Consent-ID	Identifier of the consent obtained in the transaction requesting consent. Only if the consent management has been carried out through the API.	String	COND	^.{1,36}\$ E.g. Consent-ID: 7890-asdf-4321
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,512}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQlt0UcwDQYJ.....KoZIHvcNAQELBQAwSTELMAkGA1UEBhMCVVMxEzARBgNVBA

Body

PSD2 - TPP Technical Design

Field	Description	Type	Mand.	Format
cardNumber	Card Number of the card issued by the PIISP. Should be delivered if available.	String	OPT	E.g. "cardNumber": "1111-1111-1111-1111"
account	PSU's account number.	AccountReference	MAN	E.g. "account": { "iban": "ES11111111111111111111111111111111" }
payee	The merchant where the card is accepted as an information to the PSU.	String	OPT	^.{1,70}\$ E.g. "payee": "Merchant name"
instructedAmount	Transaction amount to be checked within the funds check mechanism.	Amount	MAN	E.g. "instructedAmount": { ... }

3.5.1.2 Response

This message is returned by the HUB to the TPP as a response to the fund confirmation message.

Header

Field	Description	Type	Man.	Format
Location	Contains the link to the resource generated.	String	MAN	
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-

				946e-d75958b172e7
--	--	--	--	-------------------

Body

Field	Description	Type	Man.	Format
fundsAvailable	Equals true if sufficient funds are available at the time of the request, false otherwise.	Boolean	MAN	E.g. "fundsAvailable": true
tppMessages	Message for the TPP.	List<TppMessage>	OPT	E.g. "tppMessages": [...]

3.5.1.3 Examples

Example of request

POST <https://www.hub.com/aspsp-name/v1/funds-confirmations>

Content-Encoding: gzip

Content-Type: application/json

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

Consent-ID: 7890-asdf-4321

Date: Sun, 17 Oct 2017 13:15:17 GMT

```
{
  "cardNumber": "87432569872156",
  "account": {
    "iban": "ES1111111111111111111111"
  },
  "payee": "Name123",
  "instructedAmount": {
    "currency": "EUR",
    "amount": "153.50"
  }
}
```

Example of response with available funds

```
HTTP/1.1 200 Ok
X-Request-ID: 0ee25bf4-6ff1-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:47 GMT
Content-Type: application/json
{
  "fundsAvailable": true
}
```

3.6 OAuth2 as pre-step

3.6.1 Obtain authorisation

3.6.1.1 Request

The TPP redirects the PSU's browser so that it carries out the following request (redirection) to the HUB:

Endpoint

```
GET
/{aspsp}/authorize?response_type={response_type}&client_id={client_id}&scope
={scope}&state={state}&redirect_uri={redirect_uri}&code_challenge={code_chall
enge}&code_challenge_method={code_challenge_method}
```

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name

Query parameters

Field	Description	Type	Man.	Format
-------	-------------	------	------	--------

PSD2 - TPP Technical Design

response_type	Its value must be established at "code".	String	MAN	E.g. response_type=code
client_id	organizationIdentifier" provided in the eIDAS certificate formed as: <ul style="list-style-type: none"> - PSD - 2 characters from the NCA country code (according to ISO 3166) - Carácter "-" - 2-8 characters for the NCA identifier (A-Z in upper case) - Carácter "-" - PSP identifier 	String	MAN	^.{1,70}\$ E.g. client_id=PSDES-BDE-3DFD246
scope	Possible scope: <ul style="list-style-type: none"> • PIS • AIS • FCS • SVA <p>May indicate more than one, separated by a +</p>	String	MAN	^.{1,64}\$ E.g. scope=PIS+AIS+SVA
state	Opaque value generated by the TPP. Used to prevent "cross-site request forgery" XSRF attacks.	String	MAN	^.{1,64}\$ E.g. state=XYZ
redirect_uri	URL returned to the HUB where it will report the authorisation "code" that will be used subsequently to obtain the access token.	String	MAN	^.{1,250}\$ E.g. redirect_uri=https%3A%2F%2Fwww%2Etp%2Ecom%2Fcb
code_challenge	PKCE challenge used to prevent code injection attacks.	String	MAN	^.{1,128}\$ E.g. code_challenge=E9Melh

PSD2 - TPP Technical Design

	According to RFC 7636.			oa2OwvFrEMTJguCHaoeK1t8URWbuGJSstw-cM
code_challenge_method	Method to verify the code that may be "plain" or "S256". S256 (SHA 256) preferred	String	OPT	^.{1,120}\$ E.g. code_challenge_method=S256

Header

No additional fields are specified.

Body

The data are not sent in the body in this response.

3.6.1.2 Response OK

Response if the request has been processed correctly. The result is the redirection initiated by the HUB from the PSU navigator to the URL of the environment provided by the TPP.

Path

No additional fields are specified.

Query Parameters

Field	Description	Type	Man.	Format
Location	Contains the URL where the redirection is carried out to the TPP.	String	MAN	E.g. Location: https://www.tpp.com/cb
code	One-time-only authorisation generated by the HUB. A life of not more than 10 minutes is recommended.	String	MAN	^.{1,64}\$ E.g. code=SpIxlIOBeZQQYbYS6WxSbIA
state	Opaque value generated by the TPP. Used to maintain the status between request and response. The HUB will include it when it	String	MAN	^.{1,64}\$ E.g. state=XYZ

PSD2 - TPP Technical Design

	redirects the PSU's browser back to the TPP. Used to prevent "cross-site request forgery" attacks.			
--	--	--	--	--

Body

Data are not sent in the body in this request.

3.6.1.3 Error response

Response if there has been any error in the request. The result is the redirection initiated by the HUB from the PSU navigator to the URL of the environment provided by the TPP.

Path

No additional fields are specified.

Query Parameters

Field	Description	Type	Man.	Format
Location	Contains the URL that is redirected to the TPP.	String	MAN	E.g. Location: https://www.tpp.com/cb
error	Code that indicates the error that has occurred.	String	MAN	E.g. error=invalid_request
state	Value generated by the TPP. Used to maintain the status between request and response. The HUB will return it in the response.	String	MAN	E.g. state=XYZ

Body

Data are not sent in the body in this request.

3.6.1.4 Examples

Example of request

GET https://www.hub.com/aspsp-name/authorize?response_type=code&client_id=PSDES-BDE-3DFD246&scope=PIS%20AIS%20SVA&state=xyz&redirect_uri=https%3A%2F%2Fwww%2Ehub%2Ecom%2Fcb&code_challenge=E9Melhoa2OwvFrEMTJguCHaoeK1t8URWbuGJSstw-cM&code_challenge_method=S256

Example of OK response

HTTP/1.1 302 Found

Location: <https://www.tpp.com/cb?code=Sp1xl0BeZQQYbYS6WxSbIA&state=xyz>

Example of NOK response

HTTP/1.1 302 Found

Location: https://www.tpp.com/cb?error=access_denied&state=xyz

3.6.2 Obtain access token

This message is sent by the HUB to ASPSP to exchange the authorisation code obtained in the prior step and obtain an access token and refresh token.

3.6.2.1 Request

Endpoint

POST {provider}/{aspsp}/token

Path

Field	Description	Type	Mand.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is	String	MAN	E.g. aspsp-name

PSD2 - TPP Technical Design

	made.			
--	-------	--	--	--

Request Parameters

Field	Description	Type	Mand.	Format
grant_type	Must take the value of "authorisation_code"	String	MAN	E.g. grant_type=authorization_code
client_id	"organizationIdentifier" provided in the eIDAS certificate formed as: <ul style="list-style-type: none"> - PSD - 2 characters from the NCA country code (according to ISO 3166) - Carácter "-" - 2-8 characters for the NCA identifier (A-Z in upper case) - Carácter "-" - PSP identifier 	String	MAN	^.{1,70}\$ E.g. client_id=PSDES-BDE-3DFD246
code	Authorisation code returned by the ASPSP in the previous application requesting an authorisation code	String	MAN	^.{1,64}\$ E.g. code=SplxIOBeZQ QY bYS6WxSbIA
redirect_uri	URL is returned to the TPP where the authorisation "code" is entered. It must be the same as that entered in the authorisation code request.	String	MAN	^.{1,250}\$ E.g. redirect_uri=https%3A%2F%2Fwww%2Eetpp%2Ecom%2Fcb

PSD2 - TPP Technical Design

code_verifier	PKCE verification code used to prevent code injection attacks. Based on RFC 7636.	String	MAN	E.g. code_verifier=dBjftJeZ4CVP-mB92K27uhbUJU1p1r_wW1gFWFOEjXk
----------------------	---	--------	-----	---

Header

No additional fields are specified.

Body

Fields are not sent in the body.

3.6.2.2 Response OK

Response if the request has been processed correctly. The result of the request is an access token sent by the HUB to the PSU.

Body

Field	Description	Type	Man.	Format
access_token	Access token issued by the HUB and joined to the scope that was requested in the request and confirmed by the PSU.	String	MAN	^.{1,64}\$ E.g. "access_token":"2YotnFZFEjr1zCsicMWpAA"
token_type	Type of token issued. Will take the value "Bearer".	String	MAN	E.g. "token_type":"Bearer"
expires_in	Life of the access token in seconds.	Integer	OPT	E.g. "expires_in":300
refresh_token	Refresh token. May be used to obtain a new access token if	String	OPT	^.{1,64}\$ E.g. "refresh_token":"tGzv3JOkF0X

	it has expired.			G5Qx2TIKWIA"
--	-----------------	--	--	--------------

3.6.2.3 Error response

Response if there has been any error in the request. It is the result of the request for an access token made by the TPP to the HUB.

Body

Field	Description	Type	Man.	Format
error	Code that indicates the error that has occurred. For more return codes see the annexes.	String	MAN	E.g. "error": "invalid_request"

3.6.2.4 Examples

Example of request

POST /token HTTP/1.1

Host: <https://www.hub.com/aspsp-name>

Content-Type: application/x-www-form-urlencoded

grant_type=authorization_code&client_id=PSDES-BDE-3DFD246&code=Sp1xl0BeZQQYbYS6WxSbIA&redirect_uri=https%3A%2F%2Fwww%2Etp%2Ecom%2Fcb&code_verifier=dBjftJeZ4CVP-mB92K27uhbUJU1p1r_wW1gFWFOEjXk

Example of OK response

HTTP/1.1 200 OK

Content-Type: application/json; charset=UTF-8

Cache-Control: no-store

Pragma: no-cache

```
{
  "access_token": "2YotnFZFEjr1zCsicMWpAA",
  "token_type": "Bearer",
  "expires_in": 3600,
  "refresh_token": "tGzv3JOkF0XG5Qx2TlKWIA"
```

}

Example of NOK response

```
HTTP/1.1 400 Bad Request
Content-Type: application/json;charset=UTF-8
Cache-Control: no-store
Pragma: no-cache
{
  "error": "invalid_request"
}
```

3.7 Token renewal request

This service is used when the HUB reports that the access_token has expired. Using this request, you can refresh the access_token by sending the refresh_token associated with the expired access_token.

3.7.1 Request

Endpoint

POST {provider}/{aspsp}/token

Path

Field	Description	Type	Mand.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
grant_type	Must take the value of "refresh_token"	String	MAN	E.g. grant_type=refresh_token
client_id	organizationIdentifier" provided in the eIDAS certificate formed as: <ul style="list-style-type: none"> - PSD - 2 characters from the NCA country 	String	MAN	^.{1,70}\$ E.g. client_id=PSDES-BDE-3DFD246

PSD2 - TPP Technical Design

	code (according to ISO 3166) <ul style="list-style-type: none"> - Carácter "-" - 2-8 characters for the NCA identifier (A-Z in upper case) - Carácter "-" - PSP identifier 			
refresh_token	The refresh token necessary to be able to obtain an unexpired access_token.	String	MAN	$\wedge.\{1,64\}\$$ E.g. refresh_token=tGzv3JOkF0XG5Qx2TIKWIA

Header

No additional data are specified.

Body

No additional data are specified.

3.7.2 Response

Field	Description	Type	Man.	Format
access_token	Access token issued by the HUB and joined to the scope that was requested in the request and confirmed by the PSU.	String	MAN	$\wedge.\{1,64\}\$$ E.g. "access_token":"83kdFZFEjr1zCsicMWBB"
token_type	Type of token issued. Will take the value "Bearer".	String	MAN	E.g. "token_type":"Bearer"
expires_in	Life of the access token in	Integer	OPT	E.g. "expires_in":300

PSD2 - TPP Technical Design

	seconds.			
refresh_token	Refresh token. May be used to obtain a new access token if it has expired.	String	OPT	^.{1,64}\$ E.g. "refresh_token": "28JD3JOkF0NM5Qx2TlCCC"

3.7.3 Examples

POST /token HTTP/1.1

Host: <https://www.hub.com>

Content-Type: application/x-www-form-urlencoded

grant_type=refresh_token&client_id=PSDES-BDE-3DFD246&refresh_token=tGzv3JOkF0XG5Qx2TlKWIA

Example of OK response

HTTP/1.1 200 OK

Content-Type: application/json; charset=UTF-8

Cache-Control: no-store

Pragma: no-cache

```
{
  "access_token": "83kdFzFEjrlzCsicMWBB",
  "token_type": "Bearer",
  "expires_in": 300,
  "refresh_token": "28JD3JOkF0NM5Qx2TlCCC"
}
```

3.8 Sessions: combination of AIS and PIS services

The session support allows you to combine the AIS and PIS services in the same session.

The session support is determined by the access token obtained after carrying out the OAuth2 (pre-step) protocol.

To ensure the session is supported, the access token must have been obtained for the PIS, AIS and TPP scope, and have the roles of PISP and AISP available in its eIDAS certificate.

3.9 Processes common to the services.

3.9.1 Initiation of the authorisation process (explicit)

Use

The process of initiating authorisation is a necessary process to create a new authorisation sub-resource (if it has not been created implicitly). Applied in the following scenarios:

- The ASPSP has indicated with a "startAuthorisation" link in the response to a payment initiation request that an explicit initiation of the authorisation process is not necessary because of the TPP.
- The ASPSP has indicated with a "startAuthorisation" link in the response to a payment cancellation request that an explicit initiation of the authorisation process is not necessary because of the TPP.
- The ASPSP has indicated with a "startAuthorisation" link in the response to an account information consent request that an explicit initiation of the authorisation process is not necessary because of the TPP.
- The ASPSP has indicated with a "startAuthorisation" link in the response to a fund confirmation consent request that an explicit initiation of the authorisation process is not necessary because of the TPP.

3.9.1.1 Request

Endpoint in the case of Fund Confirmation Consent

POST {provider}/{aspsp}/v2/consents/confirmation-of-funds/{consentId}/authorisations

Endpoint in the case of Payment Cancellation

POST {provider}/{aspsp}/v1/{payment-service}/{payment-product}/{paymentId}/cancellation-authorisations

Path

PSD2 - TPP Technical Design

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. hub.example.es
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-service	Possible values are: <ul style="list-style-type: none"> • payments • bulk-payments • periodic-payments 	String	COND	E.g. {provider}/v1/payments
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none"> • sepa-credit-transfers • instant-sepa-credit-transfers • target-2-payments • cross-border-credit-transfers 	String	COND	E.g. {provider}/v1/payments/sepa-credit-transfers/
paymentI, consentId	Identifier of the resource that references the payment initiation or consent.	String	MAN	^. {1,36}\$ E.g.123-qwe-456

Query parameters

No additional parameters are specified for this request.

Header

Field	Description	Type	Man.	Format
Content-Type	Value: application/json	String	MAN	Content-Type: application/json
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisati	Bearer Token.	String	MAN	E.g.

PSD2 - TPP Technical Design

on	Obtained in a prior authentication on OAuth2.			Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102

PSD2 - TPP Technical Design

				Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	<p>HTTP method used at the PSU – TPP interface, if available.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: POST
PSU-Device-ID	<p>UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>	String	OPT	<p>UUID</p> <p>$^{\wedge}[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\\$</p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	<p>RFC 2426</p> <p>$^{\wedge}\text{GEO}:[\backslash\text{d}]*.[\backslash\text{d}]*[\text{;},][\backslash\text{d}]*.[\backslash\text{d}]*\\$</p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
Digest	<p>Is contained if and only if the "Signature" element is contained in the header of the request.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	<p>$^{\wedge}.\{1,100\}\\$</p> <p>E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==</p>
Signature	A signature of the request by the TPP on	String	MAN	See annexes

PSD2 - TPP Technical Design

	application level. See 6.1 Signature for more information.			
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAg IIZzZvBQlt0UcwDQYJ...KoZIhvcNAQELBQ AwSTELMAkGA1UEBhM CVVMxEzARBgNVBA

Body

No additional fields are specified.

3.9.1.2 Response

Header

Field	Description	Type	Man.	Format
Location	Contains the link related to the resource generated.	String	MAN	E.g. Location: /v1/payments/{payment-product}/{paymentId}/authorisations/123qwert/456
X-Request-ID	Unique identifier of the transaction assigned by the TPP and submitted through the HUB to the ASPSP	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
ASPSP-SCA-Approach	Value returned if the SCA method has been fixed. Possible values: <ul style="list-style-type: none"> EMBEDDED DECOUPLED REDIRECT 	String	COND	E.g. ASPSP-SCA-Approach: REDIRECT

PSD2 - TPP Technical Design

	The SCA based on OAuth2 will be taken as REDIRECT.			
--	--	--	--	--

Body

Field	Description	Type	Man.	Format
scaStatus	SCA status	String	MAN	E.g. "scaStatus": "received"
authorisationId	Identifier of the resource that references the authorisation of sub-resource created.	String	MAN	^.{1,36}\$ E.g. "authorisationId": "1b3ab8e8-0fd5-43d2-946e-d75958b172e7"
scaMethods	This element is contained if SCA is required and if PSU can choose between the different methods of authentication. If this data is contained the link "selectAuthenticationMethod" will also be reported. These methods must be presented to the PSU. Note: Only if ASPSP supports selection of the SCA method	List<AuthenticationObject>	COND	E.g. "scaMethods": [...]
_links	List of hyperlinks to be recognised by the TPP. Types supported in this response: <ul style="list-style-type: none"> scaRedirect: in case of SCA by redirection. Link where the PSU navigator must be redirected by the TPP. selectAuthenticationMethod 	Links	MAN	E.g. "_links": {...}

PSD2 - TPP Technical Design

	<p>nMethod: link to the authorisation sub-resource or the cancellation authorisation where the SCA method selected will be reported.</p> <ul style="list-style-type: none"> scaStatus: link to query the SCA status corresponding to the authorisation sub-resource. 			
psuMessage	Text sent to TPP through the HUB to be shown to PSU.	String	OPT	^.{1,512}\$ E.g. "psuMessage": "Information for the PSU"
tppMessages	Message for the TPP sent through the HUB.	List<Tpp Message >	OPT	E.g. "tppMessages": [...]

3.9.1.3 Examples

Example of request on a Payment Cancellation

POST <https://hub.example.es/aspsp-name/v1/payments/sepa-credit-transfers/qwert1234tzui7890/cancellation-authorisations>

Content-Encoding: gzip

Content-Type: application/json

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSD2 - TPP Technical Design

PSU-Http-Method: POST
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
Date: Sun, 26 Sep 2017 15:02:37 GMT

Example of response in the case of SCA via redirect

```
HTTP/1.1 201 Created
X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541
ASPSP-SCA-Approach: REDIRECT
Date: Sun, 26 Sep 2017 15:02:43 GMT
Location: /v1/payments/sepa-credit-transfers/123-qwe-456/cancellation-authorisations/123auth456
Content-Type: application/json
{
  "scaStatus": "received",
  "authorisationId": "123auth456",
  "_links": {
    "scaRedirect": {
      "href": "https://hub.example.es/authorize "
    },
    "scaStatus": {
      "href": "/v1/payments/sepa-credit-transfers/123-qwe-456/cancellation-authorisations/123auth456"
    }
  }
}
```

3.9.2 Update data of the PSU (select SCA method)

This message is sent by TPP to the ASPSP through the HUB to indicate the SCA method selected by the PSU.

The SCA-Approach may depend on the SCA method selected.

3.9.2.1 Request

Endpoint in the case of Fund Confirmation Consent

PUT {provider}/{aspsp}/v2/consents/confirmation-of-funds/{consentId}/authorisations/{authorisationId}

Endpoint in the case of Payment Cancellation

PUT {provider}/{aspsp}/v1/{payment-service}/{payment-product}/{paymentId}/cancellation-authorisations/{cancellationId}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. hub.example.es
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-service	Possible values are: <ul style="list-style-type: none"> • payments • bulk-payments • periodic-payments 	String	COND	E.g. {provider}/{aspsp}/v1/payments
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none"> • sepa-credit-transfers • instant-sepa-credit-transfers • target-2-payments • cross-border-credit-transfers 	String	COND	E.g. {provider}/v1/payments/sepa-credit-transfers/
paymentId, consentId	Identifier of the resource that references the payment initiation.	String	MAN	^.{1,36}\$ E.g.123-qwe-456
authorisationId	Identifier of the sub-resource associated with the consent.	String	COND	^.{1,36}\$
cancellationId	Identifier of the sub-resource associated with the payment cancellation.	String	COND	^.{1,36}\$

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $^{\wedge}[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	$^{\wedge}[0-9]\{1,3\}.\{0-9\}\{1,3\}.\{0-9\}\{1,3\}.\{0-9\}\{1,3\}\$$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	$^{\wedge}\backslash\{d\}\{1,5\}\$$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	$^{\wedge}.\{1,50\}\$$ E.g. PSU-Accept: application/json
PSU-Accept-	See above	String	OPT	$^{\wedge}.\{1,50\}\$$

PSD2 - TPP Technical Design

Charset				E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: GET
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP	String	OPT	RFC 2426 ^GEO:[\\d]*.[\\d]*[;,]

PSD2 - TPP Technical Design

	request between PSU and TPP if available.			[[\d]*.[\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.34 5963
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQIt0UcwDQYJ...KoZIHvcNAQELBQAwSTELMAkGA1UEBhM CVVMxEzARBgNVBA

Body

Field	Description	Type	Man.	Format
authenticationMethodId	Identifier of the authentication method.	String	MAN	^.{1,35}\$ E.g. "authenticationMethodId": "123"

3.9.2.2 Response

Header

Field	Description	Type	Man.	Format
X-Request-ID	Unique identifier of the transaction assigned	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-

PSD2 - TPP Technical Design

	by the TPP and submitted through the HUB to the ASPSP			9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
ASPSP-SCA-Approach	Value returned if the SCA method has been fixed. Possible values: <ul style="list-style-type: none"> EMBEDDED DECOUPLED REDIRECT <p>The SCA based on OAuth2 will be taken as REDIRECT.</p>	String	OPT	E.g. ASPSP-SCA-Approach: REDIRECT

Body

Field	Description	Type	Man.	Format
_links	List of hyperlinks to be recognised by the HUB. Types supported in this response: <ul style="list-style-type: none"> scaRedirect: in case of SCA by redirection. Link where the PSU navigator must be redirected by the TPP. scaStatus: link to query the SCA status corresponding to the authorisation sub-resource. This link is only contained if an authorisation sub-resource has been 	Links	MAN	E.g. "_links": {...}

PSD2 - TPP Technical Design

	created.			
scaStatus	SCA status	String	MAN	E.g. "scaStatus": "received"
psuMessage	Text sent to TPP through the HUB to be shown to PSU.	String	OPT	^.{1,512}\$ E.g. "psuMessage": "Information for the PSU"
tppMessages	Message for the TPP sent through the HUB.	List<TppMessage>	OPT	E.g. "tppMessage": [...]

3.9.2.3 Examples

Example of request on a payment cancellation

PUT <https://hub.example.es/v1/payments/sepa-credit-transfers/123-qwe-456/cancellation-authorisations/123asd456>

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSU-Http-Method: GET

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSU-GEO-Location: GEO:12.526347;54.649862

Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of response

HTTP/1.1 200 Ok

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

ASPSP-SCA-Approach: REDIRECT

Date: Sun, 26 Sep 2017 15:02:50 GMT

Content-Type: application/json

PSD2 - TPP Technical Design

```
{
  "scaStatus": "scaMethodSelected",
  "scaRedirect": {
    "href": "https://hub.example.es/authorize "
  },
  "scaStatus": {
    "href": "/v1/payments/sepa-credit-transfers/123-qwe-456/cancellation-authorisations/123auth456"
  }
}
```

3.9.3 Get authorisation sub-resources

Will provide an array of resource identifiers for all the sub-resources of authorisation generated.

3.9.3.1 Request

Endpoint in the case of Payment Cancellation

GET {provider}/{aspsp}/v1/{payment-service}/{payment-product}/{paymentId}/cancellation-authorisations

Path

Field	Description	Type	Man.	Format
provider	URL of the ASPSP where the service is published.	String	MAN	E.g. hub.example.es
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-service	Possible values are: <ul style="list-style-type: none">paymentsbulk-paymentsperiodic-payments	String	COND	E.g. {provider}/v1/payments
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none">sepa-credit-	String	COND	E.g. {provider}/v1/payments/sepa-credit-transfers/

PSD2 - TPP Technical Design

	<p>transfers</p> <ul style="list-style-type: none"> instant-sepa-credit-transfers target-2-payments cross-border-credit-transfers 			
paymentId	Identifier of the resource that references the payment initiation.	String	MAN	$\wedge.\{1,36\}\$$ E.g.123-qwe-456

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID $\wedge[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	$\wedge[0-9]\{1,3\}.\{0-9\}\{1,3\}.\{0-9\}\{1,3\}.\{0-9\}\{1,3\}\$$ E.g. PSU-IP-Address: 192.168.16.5

PSD2 - TPP Technical Design

PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: DELETE
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-

PSD2 - TPP Technical Design

	by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.			9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\\d]*.[\\d]*[;,:] [\\d]*.[\\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.345963
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQlt0UcwDQYJ...KoZIHvcNAQELBQAwSTELMAkGA1UEBhM CVVMxEzARBgNVBA

Body

No additional data are specified.

3.9.3.2 Response

Header

Field	Description	Type	Man.	Format
X-Request-ID	Unique identifier of the transaction assigned by the TPP and submitted through the HUB to the ASPSP	String	MAN	UUID $^{\wedge}[0-9a-fA-F]\{8\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{4\}-[0-9a-fA-F]\{12\}\$$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Man.	Format
cancellationIds	Array of cancellationIds connected to the payment resource. Note: mandatory if it is a cancellation	Array<String>	COND	E.g. "cancellationIds": [...]
psuMessage	Text sent to TPP through the HUB to be shown to PSU.	String	OPT	$^{\wedge}\{1,512\}\$$ E.g. "psuMessage": "Information for the PSU"
tppMessages	Message for the TPP sent through the HUB.	List<TppMessage>	OPT	E.g. "tppMessages": [...]

3.9.3.3 Examples

Example of request

GET <https://hub.example.es/asp-name/v1/payments/sepa-credit-transfers/123-qwe-456/cancellation-authorisations>

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFjrlzCsicMWpAA

PSD2 - TPP Technical Design

```
PSU-IP-Address: 192.168.8.16
Content-Type: application/json
Date: Sun, 26 Sep 2017 15:02:48 GMT
```

Example of response

```
HTTP/1.1 200 Ok
X-Request-ID: 0ee25bf4-6ff1-11e8-adc0-fa7ae01bbebc
Date: Sun, 26 Sep 2017 15:02:47 GMT
{
  "cancellationIds": ["123auth456"]
}
```

3.9.4 Get SCA status

Message sent by the TPP to the ASPSP through the Hub to request the SCA status of an authorisation sub-resource.

3.9.4.1 Request

Endpoint in the case of Fund Confirmation Consent

GET {provider}/{aspsp}/v2/consents/confirmation-of-funds/{consentId}/authorisations/{authorisationId}

Endpoint in the case of Payment Cancellation

GET {provider}/{aspsp}/v1/{payment-service}/{payment-product}/{paymentId}/cancellation-authorisations/{cancellationId}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. hub.example.es
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name

PSD2 - TPP Technical Design

payment-service	Possible values are: <ul style="list-style-type: none"> • payments • bulk-payments • periodic-payments 	String	COND	E.g. {provider}/v1/pa yments
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none"> • sepa-credit-transfers • instant-sepa-credit-transfers • target-2-payments • cross-border-credit-transfers 	String	COND	E.g. {provider}/v1/pa yments/sepa- credit-transfers/
paymentId, consentId	Identifier of the resource that references the payment initiation or consent	String	MAN	^.{1,36}\$ E.g.123-qwe-456
authorisationId	Identifier of the sub-resource associated with the consent.	String	COND	^.{1,36}\$
cancellationId	Identifier of the sub-resource associated with the payment cancellation.	String	COND	^.{1,36}\$

Query parameters

No additional fields are specified.

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g.

PSD2 - TPP Technical Design

				X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when submitting this request.	String	OPT	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^.{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^.{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-	The forwarded Agent header field of the	String	OPT	E.g.

PSD2 - TPP Technical Design

Agent	HTTP request between PSU and TPP, if available.			PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none"> • GET • POST • PUT • PATCH • DELETE 	String	OPT	E.g. PSU-Http-Method: GET
PSU-Device-ID	UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available. UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.	String	OPT	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7
PSU-Geo-Location	The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.	String	OPT	RFC 2426 ^GEO:[\\d]*.[\\d]*[;,] [\\d]*.[\\d]*\$ E.g. PSU-Geo-Location: GEO:90.023856;25.34 5963
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for	String	MAN	^.{1,100}\$ E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmM

PSD2 - TPP Technical Design

	more information.			DE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	^.{1,5000}\$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvBQIt0UcwDQYJ...KoZIHvcNAQELBQAwSTELMAkGA1UEBhM CVVMxEzARBgNVBA

Body

No additional data are specified.

3.9.4.2 Response

Header

Field	Description	Type	Man.	Format
X-Request-ID	Unique identifier of the transaction assigned by the TPP and submitted through the HUB to the ASPSP	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7

Body

Field	Description	Type	Man.	Format
scaStatus	SCA status	String	MAN	E.g. "scaStatus": "finalised"
psuMessage	Text sent to TPP through the HUB to	String	OPT	^.{1,512}\$ E.g.

PSD2 - TPP Technical Design

	be shown to PSU.			"psuMessage": "Information for the PSU"
tppMessages	Message for the TPP sent through the HUB.	List<TppMessage>	OPT	E.g. "tppMessages": [...]

3.9.4.3 Examples

Example of request

GET <https://hub.example.es/aspsp-name/v1/payments/sepa-credit-transfers/123-qwe-456/cancellation-authorisations/123asd456>

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA

PSU-IP-Address: 192.168.8.16

PSU-IP-Port: 443

PSU-Accept: application/json

PSU-Accept-Charset: utf-8

PSU-Accept-Encoding: gzip

PSU-Accept-Language: es-ES

PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0) Gecko/20100101 Firefox/54.0

PSU-Http-Method: GET

PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc

PSU-GEO-Location: GEO:12.526347;54.649862

Date: Sun, 26 Sep 2017 15:02:48 GMT

Example of response

HTTP/1.1 200 Ok

X-Request-ID: 96201400-6ff9-11e8-adc0-fa7ae01bbebc

Date: Sun, 26 Sep 2017 15:02:50 GMT

Content-Type: application/json

```
{
  "scaStatus": "finalised"
}
```

4. DESCRIPTION OF VALUE-ADDED SERVICES

4.1 Available ASPSPs service

This message is sent by the TTP to the HUB to receive the information about what ASPSPs are available in the system.

4.1.1 Version 1

4.1.1.1 Request

Endpoint

GET {provider}/v1/sva/aspsps

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of	String	MAN	See annexes

PSD2 - TPP Technical Design

	the request by the TPP on application level. See 6.1 Signature for more information.			
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	eIDAS E.g. TPP-Signature-Certificate: MIIHgZCCBmugAwIBAgIIZzZvB Qlt0UcwDQYJ.....KoZIHvcNA QELBQAwSTELMAkGA1UEBhMC VVMxEzARBgNVBA

Body

No additional fields are specified.

4.1.1.2 Response

Field	Description	Type	Man.	Format
aspsps	List of ASPSPs available in the system. The returned list will be made up of relevant information on the ASPSP.	List<As psp>	MAN	E.g. "aspsps":[]
tppMessages	Contains the type of message and the code associated with it	Tppmessage	MAN	E.g. "tppMessages":{ }

4.1.1.3 Examples

Example of request

```
GET https://www.hub.com/v1/sva/aspsps
Content-Encoding: gzip
Content-Type: application/json
X-Request-ID: 29391c7e-ad88-49ec-a2ad-99ddcb1f7721
Date: Sun, 27 Oct 2017 13:15:17 GMT
```

Example of response

HTTP/1.1 200 Ok

```
{
  "aspsps": [
    {
      "bic": "XXXXESMMXXX",
      "name": "aspsp1"
    },
    {
      "bic": "YYYYESMMXXX",
      "name": "aspsp2"
    }
  ]
}
```

4.1.2 Version 2

This version includes the name of the API for each ASPSP.

4.1.2.1 Request

Endpoint

GET {provider}/v2/sva/aspsps

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com

Header

Field	Description	Type	Man.	Format
X-Request-ID	ID of the request, unique to the call, as	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]

PSD2 - TPP Technical Design

	determined by the initiating party.			F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Digest	Is contained if and only if the "Signature" element is contained in the header of the request. See 6.1 Signature for more information.	String	MAN	E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ==
Signature	A signature of the request by the TPP on application level. See 6.1 Signature for more information.	String	MAN	See annexes
TPP-Signature-Certificate	The certificate used for signing the request, in base64 encoding.	String	MAN	eIDAS E.g. TPP-Signature-Certificate: MIIHgzCCBmugAwIBAgIIZzZvBQlt0UcwDQYJ.....KoZIHvcNAQELBQAwSTELMAkGA1UEBhMCVVMxEzARBgNVBA

Body

No additional fields are specified.

4.1.2.2 Response

Field	Description	Type	Man.	Format
aspsps	List of ASPSPs available in the system. The returned list will be made up of relevant information on	List<As psp>	MAN	E.g. "aspsps":[]

PSD2 - TPP Technical Design

	the ASPSP.			
tppMessages	Contains the type of message and the code associated with it	Tppmessage	MAN	E.g. "tppMessages":{ }

4.1.2.3 Examples

Example of request

GET <https://www.hub.com/v2/sva/aspsps>

Content-Encoding: gzip

Content-Type: application/json

X-Request-ID: 29391c7e-ad88-49ec-a2ad-99ddcb1f7721

Date: Sun, 27 Oct 2017 13:15:17 GMT

Example of response

HTTP/1.1 200 Ok

```
{
  "aspsps": [
    {
      "bic": "XXXXESMMXXX",
      "name": "Bank name",
      "apiName": "nombreBanco1"
    },
    {
      "bic": "YYYYESMMXXX",
      "name": "Bank 2 name",
      "apiName": "nombreBanco2"
    }
  ]
}
```


4.2 SVA: payment initiation with list of available accounts for PISP

This service allows the TPP to initiate a payment without entering information on the debtor's account "debtorAccount" and provides the list of accounts during the SCA flow so that the PSU can select one.

This value service complements the payment API payment and uses the CORE services to:

- Obtain payment status
- Recover payment initiation information
- Cancel payment initiation

4.2.1 Payment initiation

This message is sent by the TPP to the HUB to initiate payment without entering information on the debtor's account.

4.2.1.1 Request

Endpoint

POST {provider}/{aspsp}/v1/sva/payments/{payment-product}

Path

Field	Description	Type	Man.	Format
provider	URL of the HUB where the service is published.	String	MAN	E.g. www.hub.com
aspsp	Name of the ASPSP to which the request is made.	String	MAN	E.g. aspsp-name
payment-product	Payment product to be used. List of supported products: <ul style="list-style-type: none"> • sepa-credit-transfers • instant-sepa-credit-transfers • target-2-payments • cross-border-credit- 	String	MAN	E.g. {provider}/{aspsp}/v1/payments/sepa-credit-transfers/

PSD2 - TPP Technical Design

	transfers			
--	-----------	--	--	--

Header

Field	Description	Type	Man.	Format
Content-Type	Value: application/json	String	MAN	Content-Type: application/json
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
Authorisation	Bearer Token. Obtained in a prior authentication on OAuth2.	String	MAN	E.g. Authorisation: Bearer 2YotnFZFEjr1zCsicMWpAA
Consent-ID	This data element may be contained, if the payment initiation transaction is part of a session, i.e. combined AIS/PIS service. This then contains the "consentId" of the related AIS consent, which was performed prior to this payment initiation.	String	OPT	^.{1,36}\$ E.g. Consent-ID: 7890-asdf-4321
PSU-IP-Address	The forwarded IP Address header field consists of the corresponding HTTP request IP Address field between PSU and TPP. If not available, the TPP shall use the IP Address used by the TPP when	String	MAN	^[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\$ E.g. PSU-IP-Address: 192.168.16.5

PSD2 - TPP Technical Design

	submitting this request.			
PSU-IP-Port	The forwarded IP Port header field consists of the corresponding HTTP request IP Port field between PSU and TPP, if available.	String	OPT	^\d{1,5}\$ E.g. PSU-IP-Port: 443
PSU-Accept	The forwarded Accept header fields consist of the corresponding HTTP request Accept header fields between PSU and TPP, if available.	String	OPT	^{1,50}\$ E.g. PSU-Accept: application/json
PSU-Accept-Charset	See above	String	OPT	^{1,50}\$ E.g. PSU-Accept-Charset: utf-8
PSU-Accept-Encoding	See above	String	OPT	^{1,50}\$ E.g. PSU-Accept-Encoding: gzip
PSU-Accept-Language	See above	String	OPT	^{1,50}\$ E.g. PSU-Accept-Language: es-ES
PSU-User-Agent	The forwarded Agent header field of the HTTP request between PSU and TPP, if available.	String	OPT	E.g. PSU-User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US; rv:1.9.1.5) Gecko/20091102 Firefox/3.5.5 (.NET CLR 3.5.30729)
PSU-Http-Method	HTTP method used at the PSU – TPP interface, if available. Valid values are: <ul style="list-style-type: none">• GET• POST• PUT• PATCH	String	OPT	E.g. PSU-Http-Method: POST

PSD2 - TPP Technical Design

	<ul style="list-style-type: none"> DELETE 			
PSU-Device-ID	<p>UUID (Universally Unique Identifier) for a device, which is used by the PSU, if available.</p> <p>UUID identifies either a device or a device dependant application installation. In case of an installation identification this ID need to be unaltered until removal from device.</p>	String	OPT	<p>UUID</p> <p><code>^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$</code></p> <p>E.g.</p> <p>PSU-Device-ID: 5b3ab8e8-0fd5-43d2-946e-d75958b172e7</p>
PSU-Geo-Location	<p>The forwarded Geo Location of the corresponding HTTP request between PSU and TPP if available.</p>	String	OPT	<p>RFC 2426</p> <p><code>^GEO:[\d]*.[\d]*;[\d]*.[\d]*\$</code></p> <p>E.g.</p> <p>PSU-Geo-Location: GEO:90.023856;25.345963</p>
TPP-Redirect-Preferred	<p>If it equals "true", the TPP prefers a redirect over an embedded SCA approach.</p> <p>If it equals "false", the TPP prefers not to be redirected for SCA. The ASPSP will then choose between the Embedded or the Decoupled SCA approach, depending on the choice of the SCA procedure by the TPP/PSU.</p> <p>If the parameter is not used, the ASPSP will choose the SCA approach to be applied depending on the SCA method chosen by the TPP/PSU.</p> <p>EMBEDDED NOT</p>	Boolean	OPT	<p>E.g. TPP-Redirect-Preferred: true</p>

PSD2 - TPP Technical Design

	SUPPORTED IN THIS VERSION			
TPP-Redirect-URI	<p>URI of the TPP, where the transaction flow shall be redirected to after a Redirect. Mandated for the Redirect SCA Approach, specifically when TPP-Redirect-Preferred equals "true".</p> <p>It is recommended to always use this header field.</p> <p>Remark for Future: This field might be changed to mandatory in the next version of the specification.</p>	String	COND	<p>^.{1,250}\$</p> <p>E.g. TPP-Redirect-URI:"https://tpp.example.es/cb"</p>
TPP-Nok-Redirect-URI	<p>If this URI is contained, the TPP is asking to redirect the transaction flow to this address instead of the TPP-Redirect-URI in case of a negative result of the redirect SCA method. This might be ignored by the ASPSP.</p>	String	OPT	<p>^.{1,250}\$</p> <p>E.g. TPP-Nok-Redirect-URI:"https://tpp.example.es/cb/nok"</p>
Digest	<p>If it equals "true", the TPP prefers to start the authorisation process separately. This preference might be ignored by the ASPSP, if a signing basket is not supported as functionality.</p> <p>If it equals "false" or if the parameter is not used, there is no preference of the TPP. This especially indicates that the TPP assumes a direct authorisation of the transaction in the</p>	String	MAN	<p>^.{1,100}\$</p> <p>E.g. Digest: SHA-256=NzdmZjA4YjY5M2M2NDYyMmVjOWFmMGNmYTZiNTU3MjVmNDI4NTRIMzJkYzE3ZmNmMDE3ZGFmMjhhNTc5OTU3OQ=</p>

PSD2 - TPP Technical Design

	<p>next step.</p> <p>Note: the ASPSP may not take it into account if it does not support it.</p>			
Signature	<p>Is contained if and only if the "Signature" element is contained in the header of the request.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	See annexes
TPP-Signature-Certificate	<p>A signature of the request by the TPP on application level.</p> <p>See 6.1 Signature for more information.</p>	String	MAN	$\wedge.\{1,5000\}\$$ E.g. TPP-Signature-Certificate: MIIHgZCCBmugAw IBAgIIZzZvBQlt0U cwDQYJ.....Ko ZIhvcNAQELBQAw STELMakGA1UEBh MCVVMxEzARBgN VBA

Body

Field	Description	Type	Man.	Format
instructedAmount	Information on the transfer carried out.	Amount	MAN	E.g. "instructedAmount": {...}
creditorAccount	Creditor account	AccountReference	MAN	E.g. "creditorAccount": { "iban": "ES11111111111111111111" }
creditorName	Creditor's name	String	MAN	$\wedge.\{1,70\}\$$ E.g. "creditorName": "Name"
creditorAgent	BIC of the creditor account.	String	OPT	$\wedge.\{1,12\}\$$ E.g. "creditorAgent": "XSXHX SMMXXX"
creditorAddress	Creditor's address	Address	OPT	E.g. "creditorAddress": {...}
remittanceInformation	Additional	String	OPT	$\wedge.\{1,140\}\$$

PSD2 - TPP Technical Design

Information Unstructured	information			E.g. "remittanceInformationUnstructured": "Additional information"
---------------------------------	-------------	--	--	---

4.2.1.2 Response

Header

Field	Description	Type	Man.	Format
Location	Location of the created resource (if created)	String	MAN	E.g. Location: /v1/payments/{payment-product}/{payment-id}
X-Request-ID	ID of the request, unique to the call, as determined by the initiating party.	String	MAN	UUID ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$ E.g. X-Request-ID: 1b3ab8e8-0fd5-43d2-946e-d75958b172e7
ASPSP-SCA-Approach	This data element must be contained, if the SCA Approach is already fixed. Possible values are: <ul style="list-style-type: none">• EMBEDDED• DECOUPLED• REDIRECT The OAuth SCA approach will be subsumed by REDIRECT.	String	COND	E.g. ASPSP-SCA-Approach: REDIRECT

Body

Field	Description	Type	Man.	Format
transactionStatus	Status of the transaction. Values defined in annexes in 6.4 Transaction status	String	MAN	ISO 20022 E.g. "transactionStatus": "RCVD"
paymentId	Identifier of the resource that references the payment initiation.	String	MAN	^.{1,36}\$ E.g. "paymentId": "1b3ab8e8-0fd5-43d2-946e-d75958b172e7"
transactionFees	Fees associated with the payment.	Amount	OPT	E.g. "transactionFees": {...}
transactionFeeIndicator	If equal to "true", the transaction will involve a fee depending on the ASPSP or what has been agreed between the ASPSP and the PSU. If equal to "false", the transaction will not involve any additional fee for the PSU.	Boolean		E.g. "transactionFeeIndicator": true
_links	List of hyperlinks to be recognised by the TPP. Types supported in this response: <ul style="list-style-type: none"> scaRedirect: in case of SCA by redirection. Link where the PSU navigator must be redirected by the TPP. startAuthorisatio 	Links	MAN	E.g. "_links": {...}

PSD2 - TPP Technical Design

	<p>n: if an explicit initiation of the transaction authorisation is necessary (there is no selection of the SCA method)</p> <ul style="list-style-type: none"> • startAuthorisationWithAuthenticationMethodSelection: link to the authorisation endpoint where the authorisation sub-resource has to be generated while the SCA method is selected. This link is contained under the same conditions as the "scaMethods" field • self: link to the resource created by this request. • status: link to recover the transaction status. • scaStatus: link to query the SCA status corresponding to the authorisation sub-resource. This link is only contained if an 			
--	---	--	--	--

PSD2 - TPP Technical Design

	authorisation sub-resource has been created.			
psuMessage	Text to show to the PSU.	String	OPT	^. {1,512}\$ E.g. "psuMessage": "Information for the PSU"
tppMessages	Message for the TPP	List<Tpp Message >	OPT	E.g. "tppMessages": [...]

4.2.1.3 Examples

Example of request

```
POST https://www.hub.com/aspsp-name/v1/sva/payments/sepa-credit-transfers
Content-Encoding: gzip
Content-Type: application/json
X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541
Authorization: Bearer 2YotnFZFEjrlzCsicMWpAA
PSU-IP-Address: 192.168.8.16
PSU-IP-Port: 443
PSU-Accept: application/json
PSU-Accept-Charset: utf-8
PSU-Accept-Encoding: gzip
PSU-Accept-Language: es-ES
PSU-User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:54.0)
Gecko/20100101 Firefox/54.0
PSU-Http-Method: POST
PSU-Device-ID: f8b3feda-6fe3-11e8-adc0-fa7ae01bbebc
PSU-GEO-Location: GEO:12.526347;54.649862
TPP-Redirect-Preferred: true
TPP-Redirect-URI: https://www.tpp.com/cb
TPP-Nok-Redirect-URI: https://www.tpp.com/cb/nok
Date: Sun, 26 Sep 2017 15:02:37 GMT
{
```

PSD2 - TPP Technical Design

```
"instructedAmount": {
  "currency": "EUR",
  "amount": "153.50"
},
"creditorAccount": {
  "iban": "ES222222222222222222222222"
},
"creditorName": "Name123",
"remittanceInformationUnstructured": "Additional information"
}
```

Example of response

HTTP/1.1 201 Created

X-Request-ID: 10391c7e-ad88-49ec-a2ad-00aacb1f6541

AS PSP-SCA-Approach: REDIRECT

Date: Sun, 26 Sep 2017 15:02:43 GMT

Location: </v1/payments/sepa-credit-transfers/1234-qwer-5678>

```
{
  "transactionStatus": "RCVD",
  "paymentId": "123-qwe-456",
  "_links": {
    "scaRedirect": {
      "href": "https://www.hub.com/aspsp-name/authorize"
    },
    "self": {
      "href": "/v1/payments/sepa-credit-transfers/123-qwe-456",
      "status": {
        "href": "/v1/payments/sepa-credit-transfers/123-qwe-456/status"
      }
    }
  }
}
```

5. DEFINITION OF TYPES OF COMPOSITE DATA

The types of composite data used for the requests and responses in the system are defined below.

5.1 AccountAccess

Field	Description	Type	Man.	Format
accounts	Is asking for detailed account information. If the array is empty, the TPP is asking for an accessible account list. This may be restricted in a PSU/ASPSP authorization dialogue. If the array is empty, also the arrays for balances or transactions shall be empty, if used.	List<AccountReference>	OPT	E.g. "accounts": [...]
balances	Is asking for balances of the addressed accounts. If the array is empty, the TPP is asking for the balances of all accessible account lists. This may be restricted in a PSU/ASPSP authorization dialogue. If the array is empty, also the arrays for accounts or transactions shall be empty, if used.	List<AccountReference>	OPT	E.g. "balances": [...]
transactions	Is asking for transactions of the addressed accounts. If the array is empty, the TPP is asking for the transactions of all accessible account	List<AccountReference>	OPT	E.g. "transactions": [...]

PSD2 - TPP Technical Design

	lists. This may be restricted in a PSU/ASPSP authorization dialogue. If the array is empty, also the arrays for accounts or balances shall be empty, if used.			
availableAccounts	Only the value "allAccounts" is admitted.	String	OPT	E.g. "availableAccounts": "allAccounts"
availableAccountsWithBalances	Only the value "allAccounts" is admitted	String	OPT	E.g. "availableAccountsWithBalances": "allAccounts"
allPsd2	Only the value "allAccounts" is admitted	String	OPT	E.g. "allPsd2": "allAccounts"

5.2 AccountDetails

Field	Description	Type	Man.	Format
resourceId	This is the data element to be used in the path when retrieving data from a dedicated account. This shall be filled, if addressable resource are created by the ASPSP on the /accounts endpoint.	String	COND	^.{1,100}\$ E.g. "resourceId": "3dc3d5b3702348489853f5400a64e80f"
iban	IBAN of the account	String	OPT	E.g. "iban": "ES11111111111111111111"
bban	BBAN of the account if it does not have an IBAN.	String	OPT	E.g. "bban": "20385778983000760236"
msisdn	Alias to access a	String	OPT	^.{1,35}\$

PSD2 - TPP Technical Design

	payment account through a registered mobile phone number.			E.g. "msisdn": "..."
currency	Account currency.	String	MAN	ISO 4217 E.g. "currency": "EUR"
name	Name of the account given by the bank or the PSU in Online-Banking	String	OPT	^.{1,35}\$ E.g. "name": "Name"
ownerName	Name of the legal account owner (In this case, the name of the connected PSU). For a corporate account, the corporate name is used for this attribute.	String	OPT	^.{1,140}\$ E.g. "ownerName": "Heike Mustermann"
product	Product Name of the Bank for this account, proprietary definition	String	OPT	^.{1,35}\$ E.g. "product": "Main Account"
cashAccountType	Specifies the nature or use of the account.	String	OPT	ExternalCashAccountType1Code de ISO 20022 E.g. "cashAccountType": "CACC"
status	Account status. The value is one of the following: <ul style="list-style-type: none"> enabled: the account is available deleted: account closed blocked: account blocked 	String	OPT	E.g. "status": "enabled"
bic	BIC of the account.	String	OPT	^.{1,12}\$ E.g.

PSD2 - TPP Technical Design

				"bic": "XSXHXSMXXX"
linkedAccounts	This data attribute is a field, where an ASPSP can name a cash account associated to pending card transactions.	String	OPT	^.{1,70}\$
usage	Specifies the use of the account. Possible values: <ul style="list-style-type: none"> • PRIV: private personal account • ORGA: business account 	String	OPT	^.{1,4}\$ E.g. "usage": "PRIV"
details	Specifications that might be provided by the ASPSP. <ul style="list-style-type: none"> • Account characteristics • Card characteristics 	String	OPT	^.{1,140}\$
balances	Account balances.	List<Balance>	COND	"balances": [...]
_links	Links to the account, which can be directly used for retrieving account information from this dedicated account. Links to "balances" and/or "transactions" These links are only supported, when the corresponding consent has been already granted.	Links	OPT	E.g. "links": {...}

5.3 AccountReference

Field	Description	Type	Man.	Format
iban	IBAN of the account	String	COND	E.g. "iban": "ES11111111111111111111111111111111"
bban	BBAN of the account if it does not have an IBAN.	String	COND	E.g. "bban": "20385778983000760236"
pan	Primary Account Number (PAN) of a card, can be tokenised by the ASPSP due to PCI DSS requirements.	String	COND	^.{1,35}\$ E.g. "pan": "1234567891234567"
maskedPan	Primary Account Number (PAN) of a card in a masked form.	String	COND	^.{1,35}\$ E.g. "maskedPan": "123456*****4567"
msisdn	Alias to access a payment account through a registered mobile phone number.	String	COND	^.{1,35}\$ E.g. "msisdn": "..."
currency	Currency.	String	OPT	ISO 4217 E.g. "currency": "EUR"

5.4 AccountReport

Field	Description	Type	Man.	Format
booked	Latest known transactions (notes) in the account Must be included if the bookingStatus parameter is set to "booked" or "both".	List<Transactions>	COND	E.g. "booked": [{..}]
pending	Transactions pending in the account. Not contained if the	List<Transactions>	OPT	E.g. "pending": [{..}]

PSD2 - TPP Technical Design

	bookingStatus parameter is established as "booked".			
_links	The following links are accepted in this object: <ul style="list-style-type: none"> • account (MAN) • first (OPT) • next (OPT) • previous (OPT) • last (OPT) 	Links	MAN	E.g. "_links":[{}]

5.5 Address

Field	Description	Type	Mand.	Format
street	Street	String	OPT	^.{1,70}\$ E.g. "street": "Example of street"
buildingNumber	Number	String	OPT	E.g. "buildingNumber": "5"
city	City	String	OPT	E.g. "city": "Córdoba"
postalCode	Postcode	String	OPT	E.g. "postalCode": "14100"
country	Country code	String	MAN	ISO 3166 E.g. "country": "ES"

5.6 Amount

Field	Description	Type	Mand.	Format
currency	Currency of amount.	String	MAN	ISO 4217 E.g. "currency": "EUR"
amount	Amount The decimal separator is a point.	String	MAN	ISO 4217 E.g. "amount": "500.00"

5.7 AuthenticationObject

Field	Description	Type	Mand.	Format
authenticationType	Type of authentication method. Possible values: <ul style="list-style-type: none"> • SMS_OTP • CHIP_OTP • PHOTO_OTP • PUSH_OTP See annex 6.6 Types of authentication for more information.	String	MAN	E.g. "authenticationType": "SMS_OTP"
authenticationVersion	Version of the tool associated with the authenticationType.	String	COND	E.g. "authenticationVersion": "1.0"
authenticationMethodId	Id of the authentication method provided by the ASPSP.	String	MAN	^.{1,35}\$
name	Name of the authentication method defined by the PSU in the ASPSP online banking. It may also be a description provided by the ASPSP. If the TPP has it available, it must present it to the PSU.	String	MAN	E.g. "name": "SMS OTP to phone 666777888"
explanation	Detailed information about the SCA method for the PSU	String	OPT	

5.8 Aspsp

Field	Description	Type	Man.	Format
bic	BIC code of the ASPSP.	String	MAN	E.g. "bic": "XXXXXXXXXX"
name	Name of the ASPSP	String	OPT	E.g. "name": "ASPSP Name"
apiName	Name of the ASPSP used in the request PATH. Note: Only available for V2 of the list of available ASPSPs.	String	COND	E.g. "apiName": "nombreBanco"

5.9 Balance

Field	Description	Type	Man.	Format
balanceAmount	Amount and currency of the balance	Amount	MAN	E.g. "balanceAmount": {...}
balanceType	Type of balance. Values supported in the annex 6.7 Balance type	String	MAN	E.g. "balanceType": "closingBooked"
creditLimitIncluded	A flag indicating if the credit limit of the corresponding account is included in the calculation of the balance, where applicable	Boolean	OPT	E.g. "creditLimitIncluded": true
lastChangeDateTime	Date of the last action carried out on the account.	String	OPT	ISODateTime E.g. "lastChangeDateTime": "2017-10-25T15:30:35.035Z"
referenceDate	Reference date of the balance	String	OPT	ISODate E.g. "referenceDate": "2017-10-25"
lastCommittedTransaction	entryReference of the last committed	String	OPT	Max35Text E.g.

PSD2 - TPP Technical Design

ction	transaction to support the TPP in identifying whether all PSU transactions are already known.			"lastCommittedTransaction": "1234-asd-567"
--------------	---	--	--	--

5.10 ExchangeRate

Field	Description	Type	Man.	Format
currencyFrom	Source currency	String	MAN	E.g. "currencyFrom": "USD"
rate	Defines the exchange rate. E.g. currencyFrom=USD, currencyTo=EUR: 1USD =0.8 EUR and 0.8 is the fee.	String	MAN	E.g. "rate": "0.8"
currencyTo	Destination currency	String	MAN	E.g. "currencyTo": "EUR"
rateDate	Date of fee	String	MAN	ISODateTame
rateContract	Reference to the fee contract	String	OPT	

5.11 Href

Field	Description	Type	Man.	Format
href	Contains a link to a resource	String	OPT	E.g. "href": "/v1/payments/sepa-credit-transfers/asd-1234-jkl"

5.12 Links

Field	Description	Type	Man.	Format
scaRedirect	URL used to carry out the SCA, through redirecting the PSU navigator.	Href	OPT	E.g. "scaRedirect": {...}
startAuthorisation	Link to the endpoint where the authorisation of the transaction or the authorisation of the cancellation transaction must be initiated.	Href	OPT	E.g. "startAuthorisation":{...}
startAuthorisationWithAuthenticationMethodSelection	Link to the endpoint where the authorisation of a transaction or cancellation transaction must be initiated, where the SCA method must be informed with the corresponding call.	Href	OPT	E.g. "startAuthorisationWithAuthenticationMethodSelection ": {...}
selectAuthenticationMethod	Link where the TPP may select the 2-factor authentication method applicable for the PSU, if there is more than one.	Href	OPT	E.g. "selectAuthenticationMethod": {...}
self	The link to the resource created for the request. This link may be used subsequently to recover the transaction status.	Href	OPT	E.g. "self": {...}
status	The link to recover the transaction status. For example, payment initiation status.	Href	OPT	E.g. "status": {...}
account	Link to the resource that provides the information on an	Href	OPT	E.g. "account": {...}

PSD2 - TPP Technical Design

	account.			
balances	Link to the resource that provides the account balances.	Href	OPT	E.g. "balances": {...}
transactions	Link to the resource that provides the account activity.	Href	OPT	E.g. "transactions": {...}
first	Navigation link for reports on paginated accounts.	Href	OPT	E.g. "first": {...}
next	Navigation link for reports on paginated accounts.	Href	OPT	E.g. "next": {...}
previous	Navigation link for reports on paginated accounts.	Href	OPT	E.g. "previous": {...}
last	Navigation link for reports on paginated accounts.	Href	OPT	E.g. "last": {...}
download	Download link for large AIS data packages. Only for camt-data.	Href	OPT	E.g. "download": {...}

5.13 PaymentExchangeRate

Field	Description	Type	Man.	Format
unitCurrency	Currency in which the rate of exchange is expressed in a currency exchange. In the example 1EUR = xxxCUR, the unit currency is EUR.	String	OPT	ISO 4217 E.g. "unitCurrency": "EUR"
exchangeRate	Factor used to convert an amount from one currency into another. This reflects the price at which one currency	String	OPT	E.g. "exchangeRate": "1.3"

	was bought with another currency.			
contractIdentification	Unique identification to unambiguously identify the foreign exchange contract.	String	OPT	E.g. "contractIdentification": "1234-geru-23"
rateType	Specifies the type used to complete the currency exchange. Permitted values: <ul style="list-style-type: none"> • SPOT • SALE • AGRD 	String	OPT	E.g. "rateType": "SPOT"

5.14 ReportExchangeRate

Field	Description	Type	Man.	Format
sourceCurrency	Currency from which an amount is to be converted in a currency conversion.	String	MAN	ISO 4217 E.g. "sourceCurrency": "EUR"
exchangeRate	Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency.	String	MAN	E.g. "exchangeRate": "1.3"
unitCurrency	Currency in which the rate of exchange is expressed in a currency exchange. In the example 1EUR = xxxCUR, the unit currency is EUR.	String	MAN	ISO 4217 E.g. "unitCurrency": "EUR"
targetCurrency	Currency into which an amount is to be	String	MAN	ISO 4217 E.g. "targetCurrency":

PSD2 - TPP Technical Design

	converted in a currency conversion.			"USD"
quotationDate	Date at which an exchange rate is quoted.	String	MAN	ISODate E.g. "quotationDate": "2019-01-24"
contractIdentification	Unique identification to unambiguously identify the foreign exchange contract.	String	OPT	E.g. "contractIdentification": "1234-geru-23"

5.15 SinglePayment

Field	Description	Type	Man.	Format
instructedAmount	Information on the transfer carried out.	Amount	MAN	E.g. "instructedAmount": {...}
debtorAccount	The debtor's account. Note: this field may be optional in some services such as bulk payments	Account Reference	MAN	E.g. "debtorAccount": {"iban": "ES11111111111111111111111111111111"}
creditorAccount	Creditor account	Account Reference	MAN	E.g. "creditorAccount": {"iban": "ES11111111111111111111111111111111"}
creditorName	Creditor's name	String	MAN	^.{1,70}\$ E.g. "creditorName": "Name"
creditorAgent	BIC of the creditor account.	String	OPT	E.g. "creditorAgent": "X SXH X SMMXXX"
creditorAddress	Creditor's address	Address	OPT	E.g. "creditorAddress": {...}
chargeBearer	Only for payment-product: <ul style="list-style-type: none"> target-2-payments cross-border-credit-transfers Permitted values:	String	OPT	ChargeBearerType1Code of ISO 20022 E.g. "chargeBearer": "SLEV"

PSD2 - TPP Technical Design

	<ul style="list-style-type: none"> • DEBT • CRED • SHAR • SLEV 			
remittance InformationUnstructured	<p>Additional information. See annex 6.9 Good practice guide</p> <p>remittanceInformationUnstructured field for recommendations on use.</p>	String	OPT	$\wedge.\{1,140\}\$$ E.g. "remittanceInformationUnstructured": "Additional information"
requested Execution Date	<p>Execution date requested for future payments.</p> <p>Note: only if supported by the ASPSP</p>	String	COND	ISODate
requested Execution Time	<p>Requested time of execution.</p> <p>Note: only if supported by the ASPSP</p>	String	COND	ISODateTime

5.16 TppMessage

Field	Description	Type	Man.	Format
category	Category of type of message received. Possible values: ERROR or WARNING	String	MAN	E.g. "category": "ERROR"
code	Response code. All the return codes for the service are listed in annex 6.3 Return codes.	String	MAN	E.g. "code": "CONSENT_INVALID"
path	Path to the field with a reference to the error.	String	COND	E.g. "path": "..."
text	Additional explanatory	String	OPT	E.g. "text": "Example of

	text.			text"
--	-------	--	--	-------

5.17 Transactions

Field	Description	Type	Man.	Format
transactionId	Can be used as access-ID in the API, where more details on a transaction is offered.	String	OPT	E.g. "transactionId":"123-asdf-456"
entryReference	Is the identification of the transaction as used e.g. for reference for deltafunction on application level.	String	OPT	^.{1,35}\$ E.g. "entryReference":"1234-asdf-456"
endToEndId	Unique end-to-end identifier.	String	OPT	^.{1,35}\$ E.g. "endToEnd":"..."
mandateId	Identification of Mandates, e.g. a SEPA Mandate ID	String	OPT	^.{1,35}\$ E.g. "mandateId":"..."
checkId	Cheque identifier	String	OPT	^.{1,35}\$ E.g. "checkId":"..."
creditorId	Identification of the beneficiary. For example, an ID of a SEPA beneficiary.	String	OPT	^.{1,35}\$ E.g. "creditorId":"..."
bookingDate	The Date when an entry is posted to an account on the ASPSPs books.	String	OPT	ISODate "bookingDate":"2017-10-23"
valueDate	The Date at which assets become available to the account owner in case of a credit	String	OPT	ISODate E.g. "valueDate":"2017-10-23"
transactionAmount	The amount of the transaction as billed to the account.	Amount	MAN	E.g. "transactionAmount": [{}]
currencyExchange	Exchange rate	List<Repo rtExchang	OPT	E.g. "currencyExchange":

PSD2 - TPP Technical Design

		eRate>		[{...}]
creditorName	Name of the creditor if a "Debited" transaction	String	OPT	^.{1,70}\$ E.g. "creditor": "Nombre"
creditorAccount	Creditor's account.	AccountReference	COND	E.g. "creditorAccount": {...}
ultimateCreditor	Ultimate creditor.	String	OPT	^.{1,70}\$ E.g. "ultimateCreditor": "Nombre"
debtorName	Name of the debtor if a "Credited" transaction	String	OPT	^.{1,70}\$ E.g. "debtor": "Nombre"
debtorAccount	The debtor's account.	AccountReference	COND	E.g. "debtorAccount": {...}
ultimateDebtor	Name of ultimate debtor.	String	OPT	^.{1,70}\$ E.g. "ultimateDebtor": "Nombre"
remittanceInformationUnstructured	Field to include additional information on the remittance.	String	OPT	^.{1,140}\$ E.g. "remittanceInformationUnstructured": "Additional information"
remittanceInformationStructured	Reference as contained in the structured remittance reference structure	String	OPT	^.{1,140}\$ E.g. "remittanceInformationStructured": "Ref. 12344567"
purposeCode	ExternalPurpose1Code ISO 20022	String	OPT	ExternalPurpose1Code ISO 20022
bankTransactionCode	Bank transaction code as used by the ASPSP and using the sub elements of this structured code defined by ISO20022	String	OPT	ExternalBankTransactionDomain1Code
proprietaryBankTransactionCode	Proprietary bank transaction code	String	OPT	^.{1,35}\$
_links	Possible values:	Links	OPT	E.g. "_links": {...}

PSD2 - TPP Technical Design

	• transactionDetails			
--	----------------------	--	--	--

6. ANNEXES

6.1 Signature

6.1.1 "Digest" header mandatory

The Digest field is mandatory in all requests.

This field contains a hash of the message body. If the message does not contain a body, the "Digest" field must contain a hash of an empty "bytelist". The hash algorithms that may be used to calculate the "Digest" in the context of this specification are SHA-256 and SHA-512.

6.1.2 Signature requirements

The structure of the "Signature" field of the request header must be presented with the following structure.

Element	Type	Man.	Requirements	Additional requirements
keyId	String	MAN	It is a chain that can be used by the HUB to find a component needed to validate the signature.	Serial number of the TPP certificate included in "TPP-Signature-Certificate". Must be formatted as follows: KeyId="SN=XXX,CA=YYYYYYYYYYYYYYYY" Where "XXX" is the serial number of the certificate in hexadecimal code and "YYYYYYYYYYYYYYYY" is the full "Distinguished Name" of the certification authority.
Algorithm-ID	String	MAN	It is used to specify the algorithm used to generate the signature.	The algorithm must identify the same algorithm for the signature as that presented in the request certificate. Must identify SHA-256 or SHA-512.
Headers	String	OPT	Is used to specify the list of HTTP headers included when the signature is generated	The required fields to be signed are: <ul style="list-style-type: none"> digest

PSD2 - TPP Technical Design

			<p>for the message. If specified, it must be a list between inverted commas and in lower case, separated by a blank space. If not specified, it must be understood that only one value has been specified. This specified value is the "Date" attribute of the request header.</p> <p>The order of the attributes is important and must be the same as the order specified on the list of HTTP headers specified in this field.</p>	<ul style="list-style-type: none"> • x-request-id <p>Conditionally, if they travel and are supported, they must include:</p> <ul style="list-style-type: none"> • psu-id • psu-corporate-id • tpp-redirect-uri
Signature	String	MAN	<p>The "signature" parameter must be in Base64 according to RFC 4648.</p> <p>The TPP uses the algorithm and the parameters of the header to form the chain to be signed. The chain to sign is signed with the keyId and the corresponding algorithm. The content must be in Base64.</p>	There are no additional requirements.

6.1.3 Example

You want to make a host-to-host request with the following text:

```
{
  "instructedAmount" : {
    "currency" : "EUR",
    "amount" : "16.00"
  },
  "debtorAccount" : {
    "iban" : "ES5140000001050000000001",
```

PSD2 - TPP Technical Design

```
    "currency" : "EUR"
  },
  "creditorName" : "Cred. Name",
  "creditorAccount" : {
    "iban" : "ES6621000418401234567891",
    "currency" : "EUR"
  },
  "creditorAddress" : {
    "street" : "Example of street",
    "buildingNumber" : "15",
    "city" : "Cordoba",
    "postalCode" : "14100",
    "country" : "ES"
  },
  "remittanceInformationUnstructured" : "Payment",
  "chargeBearer" : "CRED"
}
```

And you must also add the following headers

- X-Request-ID=a13cbf11-b053-4908-bd06-517dfa3a1861

You must make the following transactions.

6.1.3.1 Generation of the "Digest" header

To do so you must perform the hash of the message body that will be sent. It is vital to do so on the final content once serialised, as the following serialisation processes may introduce changes in the body of the message finally sent, making the signature invalid.

It is possible to use the SHA-256 and SHA-512 algorithms following the RFC 5843. In our example you will use SHA-256 on the body of the message, obtaining the following result:

- Hexadecimal:
A5F1CF405B28E44ED29507E0F64495859BA877893D2A714512D16CE3BD8
BE562
- Base64: pfHPQFso5E7SIQfg9kSVhZuod4k9KnFFEtFs472L5WI=

Thus, the value of the "Digest" header to generate will be:

SHA256=pfHPQFso5E7SIQfg9kSVhZuod4k9KnFFEtFs472L5WI=

The headers you have so far are:

X-Request-ID=a13cbf11-b053-4908-bd06-517dfa3a1861f]

Digest=SHA256=pfHPQFso5E7SIQfg9kSVhZuod4k9KnFFEtFs472L5WI=

6.1.3.2 Generation of the "Signature" header

The "Signature" header is the multi-value type, i.e. it contains within it various pairs of sub-headers of the attribute-value type

Establishment of the "keyId" value

This field is obtained based on a serial number of the certificate in hexadecimal and the DN of the certification authority that generates the certificate.

In our example you obtain the following result:

keyId="SN=-5d803f65,CA=CN=REDSYS-AC-EIDASt-C1,OU=PKI,O=REDSYS,C=ES"

Establishment of the "headers" attribute

You should note that this attribute and some others are shown in the Berlin Group document with the first character in upper case, but in the RFC used by the entity its content is always established in lower case, so we assume that it is an error.

This establishes the fields that will be taken into account signing.

headers="digest x-request-id"

Establishment of the "algorithm" attribute

algorithm="SHA-256"

Construction of the chain to be signed

The chain to be signed according to point 2.2.3 is as follows:

Digest: SHA256=pfHPQFso5E7SIQfg9kSVhZuod4k9KnFFEtFs472L5WI=

X-Request-ID: a13cbf11-b053-4908-bd06-517dfa3a1861f

Generation of the signature

We sign the chain obtained in the above point with the private key of our certificate and pass the result to Base64, obtaining in our specific case the following result:

PSD2 - TPP Technical Design

```
la8LV3Fny2so4c40OkYFtZvr1mOkOVY1n87iKfIggEkXQjZNcyjp9fFkNtQc+5ZVNESdiq
KG8xrawYa5gAm46CvcKChNTPaakiEJHcXM5RZPWN0Ns5HjV5mUY2QzD+g5mwqcW
vXtBr1vg0bZKN8Zt3+uJMN37NQg9tJNE2yKIJIEPIAYOjC2PA/yzGSLOdADnXQut9yRvx
w8gMCjDtRaKdYWmwG6/crX293hGvBUeff1xvTluWhQzyfx4J6WG0v1ZmpnWdZ1LF6
8sToeDGTdu65aVKV2q6qcZzcm5aPV6+mVHX+21Vr6acxiLZdeYUHYJHrzErUN3KJrmt
3w2AL7Dw==
```

6.1.3.3 Generation of the "TPP-Signature-Certificate" header

This header contains the certificate we have used in Base64. For reasons of space only a part is established in the example:

```
TPP-Signature-Certificate="MIIEWTCCA0GgAwIBAgI....
```

6.1.3.4 Definitive headers to send

As seen in the above points the headers that must be sent in the request are:

```
X-Request-ID=a13cbf11-b053-4908-bd06-517dfa3a1861f
```

```
Digest=SHA256=pfHPQFso5E7SIQfg9kSVhZuod4k9KnFFEtFs472L5WI=
```

```
Signature=keyId="SN=-5d803f65,CA=CN=REDSYS-AC-EIDAST-
C1,OU=PKI,O=REDSYS,C=ES",algorithm="SHA-256",headers="digest x-request-
id",signature="
```

```
la8LV3Fny2so4c40OkYFtZvr1mOkOVY1n87iKfIggEkXQjZNcyjp9fFkNtQc+5ZVNESdiq
KG8xrawYa5gAm46CvcKChNTPaakiEJHcXM5RZPWN0Ns5HjV5mUY2QzD+g5mwqcW
vXtBr1vg0bZKN8Zt3+uJMN37NQg9tJNE2yKIJIEPIAYOjC2PA/yzGSLOdADnXQut9yRvx
w8gMCjDtRaKdYWmwG6/crX293hGvBUeff1xvTluWhQzyfx4J6WG0v1ZmpnWdZ1LF6
8sToeDGTdu65aVKV2q6qcZzcm5aPV6+mVHX+21Vr6acxiLZdeYUHYJHrzErUN3KJrmt
3w2AL7Dw=="
```

```
TPP-Signature-Certificate=MIIEWTCCA0GgAwIBAgIEon/...
```

6.2 HTTP response codes

The HTTP codes followed by this specification and their uses are the following:

HTTP code	Description
200 OK	<p>PUT, GET Response Codes</p> <p>This return code is permitted if a request was repeated due to a time-out. The response in that might be either a 200 or 201 code depending on the ASPSP implementation.</p> <p>The POST for a Funds request will also return 200 since it does not create a new resource.</p>

PSD2 - TPP Technical Design

	DELETE Response Code where a payment resource has been cancelled successfully and no further cancellation authorisation is required.
201 Created	POST response code where Payment Initiation or Consent Request was correctly performed.
202 Accepted	DELETE response code, where a payment resource can be cancelled in general, but where a cancellation authorisation is needed in addition.
204 No Content	DELETE response code where a consent resource was successfully deleted. The code indicates that the request was performed, but no content was returned. Also used in DELETE requests of a payment initiation where authentication is not needed.
400 Bad Request	Validation error occurred. This code will cover malformed syntax in request or incorrect data in payload.
401 Unauthorised	The TPP or the PSU is not correctly authorized to perform the request. Retry the request with correct authentication information.
403 Forbidden	Returned if the resource that was referenced in the path exists but cannot be accessed by the TPP or the PSU. This code should only be used for non-sensitive id references as it will reveal that the resource exists even though it cannot be accessed.
404 Not found	Returned if the resource or endpoint that was referenced in the path does not exist or cannot be referenced by the TPP or the PSU. When in doubt if a specific id in the path is sensitive or not, use the HTTP response code 404 instead of the HTTP response code 403.
405 Method Not Allowed	This code is only sent when the HTTP method (PUT, POST, DELETE, GET etc.) is not supported on a specific endpoint. It has nothing to do with the consent, payment or account information data model. DELETE Response code in case of cancellation of a payment initiation, where the payment initiation cannot be cancelled due to legal or other operational reasons.

406 Not Acceptable	The ASPSP cannot generate the content that the TPP specified in the Accept header.
408 Request Timeout	The server is still working correctly, but an individual request has timed out.
409 Conflict	The request could not be completed due to a conflict with the current state of the target resource.
415 Unsupported Media Type	The TPP has supplied a media type which the ASPSP does not support.
429 Too Many Requests	The TPP has exceeded the number of requests allowed by the consent or by the RTS.
500 Internal Server Error	Internal server error occurred.
503 Service Unavailable	The ASPSP server is currently unavailable. Generally, this is a temporary state.

6.3 Return codes

Permitted return codes and associated HTTP response codes.

	HTTP code	Code	Description
SIGNATURE CERTIFICATE	401	CERTIFICATE_INVALID	The contents of the signature/corporate seal certificate are not matching PSD2 general PSD2 or attribute requirements.
	401	CERTIFICATE_EXPIRED	Signature/corporate seal certificate is expired.
	401	CERTIFICATE_BLOCKED	Signature/corporate seal certificate has been blocked by the ASPSP or the related NCA.
	401	CERTIFICATE_REVOKED	Signature/corporate seal certificate has been revoked by QSTP.
	401	CERTIFICATE_MISSING	Signature/corporate seal certificate was not available in the request but is mandated for the corresponding.
SIGNATURE	401	SIGNATURE_INVALID	Application layer eIDAS

PSD2 - TPP Technical Design

E		D	Signature for TPP authentication is not correct.
	401	SIGNATURE_MISSING	Application layer eIDAS Signature for TPP authentication is mandated by the ASPSP but is missing.
GENERAL	400	FORMAT_ERROR	<p>Format of certain request fields are not matching the XS2A requirements. An explicit path to the corresponding field might be added in the return message.</p> <p>This applies to headers and body entries. It also applies in cases where these entries are referring to erroneous or not existing data instances, e.g. a malformed IBAN.</p>
	400	PARAMETER_NOT_CONSISTENT	Parameters submitted by TPP are not consistent. This applies only for query parameters.
	400	PARAMETER_NOT_SUPPORTED	The parameter is not supported by the API provider. This code should only be used for parameters that are described as "optional if supported by API provider."
	401	PSU_CREDENTIALS_INVALID	The PSU-ID cannot be matched by the addressed ASPSP or is blocked, or a password resp. OTP was not correct. Additional information might be added.
	400 (payload) 405 (HTTP method)	SERVICE_INVALID	The addressed service is not valid for the addressed resources or the submitted data.

PSD2 - TPP Technical Design

	403	SERVICE_BLOCKED	This service is not reachable for the addressed PSU due to a channel independent blocking by the ASPSP. Additional information might be given by the ASPSP.
	401	CORPORATE_ID_INVALID	The PSU-Corporate-ID cannot be matched by the addressed ASPSP.
	403 (if resource on path) 400 (if resource in payload)	CONSENT_UNKNOWN	The Consent-ID cannot be matched by the ASPSP relative to the TPP.
	401	CONSENT_INVALID	The consent was created by this TPP but is not valid for the addressed service/resource. Or, the definition of the consent is not complete, or is invalid.
	401	CONSENT_EXPIRED	The consent was created by this TPP but has expired and needs to be renewed.
	401	TOKEN_UNKNOWN	The OAuth2 token cannot be matched by the ASPSP relative to the TPP.
	401	TOKEN_INVALID	The OAuth2 token is associated to the TPP but is not valid for the addressed service/resource.
	401	TOKEN_EXPIRED	The OAuth2 token is associated to the TPP but has expired and needs to be renewed.
	404 (if account-id in path) 403 (if other resource in path)	RESOURCE_UNKNOWN	The addressed resource is unknown relative to the TPP.

PSD2 - TPP Technical Design

	400 (if goes in payload)		
	403 (if resource on path) 400 (if resource in payload)	RESOURCE_EXPIRED	The addressed resource is associated with the TPP but has expired, not addressable anymore.
	400	RESOURCE_BLOCKED	The addressed resource is not addressable by this request, since it is blocked e.g. by a grouping in a signing basket.
	400	TIMESTAMP_INVALID	Timestamp not in accepted time period.
	400	PERIOD_INVALID	Requested time period out of bound.
	400	SCA_METHOD_UNKNOWN	Addressed SCA method in the Authentication Method Select Request is unknown or cannot be matched by the ASPSP with the PSU.
	409	STATUS_INVALID	The addressed resource does not allow additional authorisation.
OAuth2	302	invalid_request	The request is not well formed because there are parameters missing, value not supported, or parameters repeated.
	302	unauthorized_client	The authenticated client is not authorised to use this type of authorisation.
	302	access_denied	The owner of the resources or the authorised server rejects the request.
	302	unsupported_response_type	The authorisation server does not support the method used to obtain the authorisation code.
	302	invalid_scope	The scope requested is invalid, unknown or badly formed.
	302	server_error	Error 500 that may not be returned in a redirect. It is

PSD2 - TPP Technical Design

			returned with this code.
	302	temporarily_unavailable	The authorisation server is temporarily unable to process the request, due to a temporary overload or due to maintenance.
	400	invalid_request	The request is not well formed because parameters are missing, the value is not supported, parameters are repeated, it includes multiple credentials or uses more than one of the client's authentication mechanisms.
	401	invalid_client	Client authentication failure.
	400	invalid_grant	The authorisation provided or the refresh token is invalid, expired, revoked, does not coincide with the redirect URL, or was issued by another client.
	400	unauthorized_client	The authenticated client is not authorised to use this type of authorisation.
	400	unsupported_grant_type	The type of authorisation requested is not supported by the authorisation server.
	400	invalid_scope	The scope requested is invalid, unknown, badly formed or exceeds what is permitted.
PIS	403	PRODUCT_INVALID	The addressed payment product is not available for the PSU.
	404	PRODUCT_UNKNOWN	The addressed payment product is not supported by the ASPSP.
	400	PAYMENT_FAILED	The payment initiation POST request failed during the initial process.

PSD2 - TPP Technical Design

			Additional information may be provided by the ASPSP.
	400	EXECUTION_DATE_INVALID	The requested execution date is not a valid execution date for the ASPSP.
	405	CANCELLATION_INVALID	The addressed payment is not cancellable e.g. due to cut off time passed or legal constraints.
AIS	401	CONSENT_INVALID	The consent was created by the TPP, but it is not valid for the recourse/service requested. Or, the consent definition is not complete or invalid. In case of being not complete, the bank is not supporting a completion of the consent towards the PSU.
	400	SESSIONS_NOT_SUPPORTED	The combined service flag may not be used with this ASPSP.
	429	ACCESS_EXCEEDED	The access on the account has been exceeding the consented multiplicity without PSU involvement per day.
	406	REQUESTED_FORMATS_INVALID	The requested formats in the Accept header entry are not matching the formats offered by the ASPSP.
FCS	400	CARD_INVALID	Addressed card number is unknown to the ASPSP or not associated to the PSU.
	400	NO_PIIS_ACTIVATION	The PSU has not activated the addressed account for the usage of the PIIS associated with the TPP.

6.4 Transaction status

Code	Name	Description
ACCC	AcceptedSettlementCompleted	Settlement on the creditor's account has been completed.
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACFC	AcceptedFundsChecked	Pre-ceeding check of technical validation and customer profile was successful and an automatic funds check was positive . Remark: This code is accepted as new code by ISO20022.
ACSC	AcceptedSettlementCompleted	Settlement on the debtor's account has been completed. Usage: this can be used by the first agent to report to the debtor that the transaction has been completed. Warning: this status is provided for transaction status reasons, not for financial information. It can only be used after bilateral agreement
ACSP	AcceptedSettlementInProcess	All preceding checks such as technical validation and customer profile were successful and therefore the payment initiation has been accepted for execution.
ACTC	AcceptedTechnicalValidation	Authentication and syntactical and semantical validation are successful
ACWC	AcceptedWithChange	The instruction has been accepted, but needs a change; for example, the date or other data has not been sent. Also to inform that a change has been applied, for example, on the payment initiation, and that the execution date has been changed.
ACWP	AcceptedWithoutPosting	Payment instruction included in the credit transfer is accepted without being posted to the creditor customer's account.
RCVD	Received	Payment initiation has been received by the receiving agent.
PATC	PartiallyAcceptedTechnical	The payment initiation needs multiple authentications, where some but not yet all

PSD2 - TPP Technical Design

	ICorrect	have been performed. Syntactical and semantical validations are successful. Remark: This code is accepted as new code by ISO20022.
PDNG	Pending	Payment initiation or individual transaction included in the payment initiation is pending. Further checks and status update will be performed.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.
CANC	Cancelled	Payment initiation has been cancelled before execution Remark: This code is accepted as new code by ISO20022.
PART	PartiallyAccepted	A number of transactions have been accepted, whereas another number of transactions have not yet achieved 'accepted' status. Remark: This code may be used only in case of bulk payments. It is only used in a situation where all mandated authorisations have been applied, but some payments have been rejected.

6.5 Consent status

Code	Description
received	The consent data have been received and are technically correct. The data is not authorised yet.
rejected	The consent data have been rejected e.g. since no successful authorisation has taken place.
partiallyAuthorised	The consent is due to a multi-level authorisation, some but not all mandated authorisations have been performed yet.
valid	The consent is accepted and valid for GET account data calls and others as specified in the consent object.
revokedByPsu	The consent has been revoked by the PSU towards the ASPSP.
expired	The consent expired.

terminated ByTpp	The corresponding TPP has terminated the consent by applying the DELETE method to the consent resource.
-------------------------	---

6.6 Types of authentication

Code	Description
SMS_OTP	An SCA method, where an OTP linked to the transaction to be authorised is sent to the PSU through a SMS channel.
CHIP_OTP	An SCA method, where an OTP is generated by a chip card, e.g. an TOP derived from an EMV cryptogram. To contact the card, the PSU normally needs a (handheld) device. With this device, the PSU either reads the challenging data through a visual interface like flickering or the PSU types in the challenge through the device key pad. The device then derives an OTP from the challenge data and displays the OTP to the PSU.
PHOTO_OTP	An SCA method, where the challenge is a QR code or similar encoded visual data which can be read in by a consumer device or specific mobile app. The device resp. the specific app than derives an OTP from the visual challenge data and displays the OTP to the PSU.
PUSH_OTP	An OTP is pushed to a dedicated authentication APP and displayed to the PSU.

6.7 Balance type

Code	Description
closingBooked	Balance of the account at the end of the pre-agreed account reporting period. It is the sum of the opening booked balance at the beginning of the period and all entries booked to the account during the pre-agreed account reporting period.
expected	Balance composed of booked entries and pending items known at the time of calculation, which projects the end of day balance if everything is booked on the account and no other entry is

	posted.
openingBooked	Book balance of the account at the beginning of the account reporting period. It always equals the closing book balance from the previous report.
interimAvailable	Available balance calculated in the course of the account 'servicer's business day, at the time specified, and subject to further changes during the business day. The interim balance is calculated on the basis of booked credit and debit items during the calculation time/period specified.
interimBooked	Balance calculated in the course of the account servicer's business day, at the time specified, and subject to further changes during the business day. The interim balance is calculated on the basis of booked credit and debit items during the calculation time/period specified.
forwardAvailable	Forward available balance of money that is at the disposal of the account owner on the date specified.

6.8 Charge Bearer

Code	Description
DEBT	All transaction charges are to be borne by the debtor.
CRED	All transaction charges are to be borne by the creditor.
SHAR	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	Charges are to be applied following the rules agreed in the service level and/or scheme.

6.9 Good practice guide

6.9.1 remittanceInformationUnstructured field

This field may be used following the EACT "Association of European Treasurers" standard adopted in BG in the "Mobile P2P Interoperability Framework – Implementation Guidelines v1.0"

The format is as follows:

Field	Description
/DNR/	Debtor's alias
/CNR/	Creditor's alias. (we recommend sending the merchant's FUC)
/DOC/	Reference data for the corresponding request. (The Hub mobilises X-Request-Id of the TPP)
/TXT/	Additional text/item

Example

"remittanceInformationUnstructured": "/DOC/db617660-d60d-11e8-9f8b-f2801f1b9fd1/TXT/Purchase in merchant xxx"

6.9.2 Life of the scaRedirect link

The Berlin Group recommends a duration of 5 minutes for this type of link.